

T068 € 131,00

LASER POINTER INFRARED TEMPERATURE METER

Not suitable for body temperature measurement



Blister

Range	-30°C÷550 °C -22 F÷1022 F
Accuracy	-30 °C ÷ 0 °C -22 F ÷ 32 F ±3 % or ±3 °C
Accuracy	0 °C ÷ 100 °C 32 F ÷ 212 F ±2 % or ±2 °C
Accuracy	> 100 °C > 212 F ±3 % or ±3 °C
Reading	0,1 °C 0,1 F
Emissivity	0,1 ÷ 1,0
Battery	9 V

€ 77,50



T064 € 101,00

LASER POINTER INFRARED TEMPERATURE METER

High precision. Non-contact temperature measurement. Not suitable for human beings



Blister

Range	-25°C÷400 °C -13 F÷752 F
Accuracy	-25 °C ÷ 400 °C ±(2 % + 1 °C)
Accuracy	-13 F ÷ 752 F ±(2 % + 1 F)
Reading	1 °C 2 F
Battery	9 V
Distance/Spot size	1 : 10
Sampling time	0.5 s

€ 74,60



0387A € 67,40

DIGITAL MULTI-FUNCTION DETECTOR

For measuring ferrous and non-ferrous metals, wood and live cables in walls, ceilings and floors.



Blister

Max depth of detecting	
Ferrous metal	100 ± 5 mm
No ferrous metal	70 ± 5 mm
Wood	20 ± 5 mm
Depth of AC	50 ± 5 mm
Battery	9 V
Dimensions	150 x 75 x 24 mm

€ 50,90



MD01 € 118,00

METAL DETECTOR

Analogue consisting of 2 color Leds for metal recognition. Audio sensor.



Box

Coil diameter	170 mm
Jack connector	1/4"
Sensitivity	> 15 cm per una moneta di ø 25 mm
Battery	9 V

€ 94,50



C070 € 154,00

CONTACT AND OPTICAL TYPE DIGITAL TACHOMETER

With reflective stripes



Carrying case

Rotation laser speed	2,5 ÷ 9999,9 rpm
Rotation contact speed	0,05 ÷ 999,9 rpm
Surface speed	0,1 ÷ 999,99 m / min
Reading	0,1 (2,5 ÷ 999,9) rpm
Reading	1 (1000 ÷ 9999,9) rpm
Use distance	da 50 ÷ 60 mm a 50 ÷ 250 mm (con ottico)
Accuracy	± 0,05 % + 1 digit
Working temperature	0°C ÷ 40°C
Sampling time	0.8 s

€ 119,00



C069 € 110,00

CONTACT TYPE DIGITAL TACHOMETER



Carrying case

Round speed	2,5 - 9999,9 rpm
Surface speed	0,05 - 999,99 m/min
Reading	0,1 (7,5 - 999,9) rpm
Reading	1 (1000-9999,9) rpm
Accuracy	± 0,05 % + 1 digit
Dimensions	190 x 72 x 37 mm
Battery	4 x 1,5 V AA

€ 72,00



C067 € 110,00

PHOTO TYPE DIGITAL TACHOMETER

With reflective stripes



Carrying case

Range	2,5 ÷ 9999,9 rpm
Reading	0,1 (2,5 ÷ 999,9) rpm
Reading	1 (1000 ÷ 9999,9) rpm
Use distance	da 50 ÷ 60 mm a 50 ÷ 250 mm
Accuracy	±0.05 % of reading + 1 digit
Dimensions	170 x 72 x 37 mm
Battery	4 x 1,5V AA

€ 67,30



0433 € 82,10

REFRACTOMETER

Brix, useful to check coolant oils



Carrying case

Range	0 ÷ 32% Brix
-------	--------------

€ 65,80

