

In-Wall Timer - 24-Hour Heavy-Duty Mechanical In-Wall Timer, 125VAC, 15 A, Removable Trippers, White

Item E1020



PRODUCT DESCRIPTION

These Heavy-Duty In-Wall Timers are ideal for turning on lights, fans, pumps and other heavy duty loads for energy savings, security and convenience. The timer provides up to 12 ON and 12 OFF operations per day.

FEATURES

- ▶ E1010 includes one ON/OFF permanently attached tripper for single ON/OFF control per 24-hour period
- ▶ E1020 includes two ON/OFF trippers and can accommodate up to 12 ON/OFF trippers
- ▶ Programmable in 30-minute intervals
- ▶ Turns ON/OFF heavy-duty loads for energy savings, security and convenience
- ▶ Mounts to any standard junction box
- ▶ Requires neutral connection

APPLICATIONS

- ▶ Air Movement & Ventilation
- ▶ Indoor Lighting Control
- ▶ Outdoor Lighting Control

TECHNICAL DATA

General

| | |
|--------------------------------|--|
| Model Number | E1020 |
| Description | 24-Hour Heavy-Duty Mechanical In-Wall Timer, 125VAC, 15 A, Removable Trippers, White |
| UPC Code | 078275440203 |
| Brand | Intermatic |
| Country of Origin (Intermatic) | MEXICO |
| Warranty Period | 1-Year limited |

Control Specifications

| | |
|-----------------------------|--------------------------------|
| Minimum ON/OFF Times | 30 min |
| Maximum ON/OFF Operations | 12 |
| Operation Mode | 24 hour |
| Mechanism Type | Analog/Mechanical |
| Application Compatibilities | Incandescent; Fluorescent; CFL |

Mechanical Specifications

| | |
|---------------------------|-------------|
| Wall Plate Configurations | Single-Gang |
|---------------------------|-------------|

Dimensions

| | |
|-----------------------------------|------------------------|
| Product Dimensions (H x W x D) in | 4.25 x 3.25 x 1.375 in |
|-----------------------------------|------------------------|

Material Specifications

| | |
|---------------------|-------|
| Color | White |
| Includes Wall Plate | Yes |

Load Ratings

| | |
|-------------------------------|----------------------|
| Resistive Load Ratings Ranges | 15 A, 125 VAC, 60 Hz |
|-------------------------------|----------------------|

| | |
|--|-------------------------|
| Motor Load Ratings Ranges | 12 FLA @ 125 VAC, 60 Hz |
| Incandescent Load Ratings (Single-Gang) | 1500 W, 125 VAC, 60 Hz |
| Incandescent Single Gang Load Ratings Ranges | 1500 W, 125 VAC, 60 Hz |

Electrical Specifications

| | |
|-----------------------------|----------------|
| Input Voltage Range(s) | 125 VAC, 60 Hz |
| Wiring Configurations | Single |
| Neutral Connection Required | Yes |
| Watts | 1500 |
| Supply Voltage | 125 volt |

Environmental Specifications

| | |
|-------------------------|--------------------------|
| Temperature (operation) | -4 - 77 °F / -20 - 25 °C |
|-------------------------|--------------------------|

Packaging

| | |
|---------------------------------------|--------------------------|
| Shipping Weight (lbs) | 0.748 |
| Unit Carton Dimensions (H x W x D) in | 3.251 x 3.501 x 5.751 in |

Standards and Certifications

| | |
|--|--------------|
| CSA Certification | cCSAus |
| Other Certifications and Compatibilities | Green Energy |
| California Proposition 65 | Nickel |
| RoHS Certification | X |

ACCESSORIES



156EB1945A
Trippers for E1020 (Pack of 2)



48EB937
Spring - Cam Passivate for E1020, E1010,
WH21



48EB938
Spring - Cam Green for E1020, E1010, WH21



WG230-13
Motor - 125 V 60 Hz with Leads & Cover