

# KERN NIB 600K-2



Compact, robust drive-through scale - particularly mobile thanks to its carrying handle, rollers and lightweight construction



## Services (optional)

Adjustment at the location of installation: 961-250

DAkkS Certificate: 963-130

## Category

Brand: KERN  
Category: Balances  
Product Group: Drive-through scale

## Packaging & shipping

Delivery: 48 h  
Dimensions packaging (WxDxH): 1135 x 1050 x 200 mm  
Gross weight: 62 kg  
Net weight: 40 kg  
Shipping method: Freight forwarder

## Construction

Cable length: 5 m  
Cable length of display device: 5 m  
Casing material: Steel lacquered  
Dimensions of display device (WxDxH): 200 x 130 x 60 mm  
Dimensions of weighing plate (WxDxH): 1000 x 1000 x 40 mm  
Level indicator: yes  
Material weighing plate: Steel lacquered  
Overall dimensions mounted (WxDxH): 1066 x 1000 x 80 mm  
Revolving screw feet: yes  
Wall mount: yes  
Weighing surface (WxD): 800 x 800 mm

## Piktogramme

### STANDARD



### OPTION



## Measuring system

Adjustment options: External calibration  
Linearity: 600 g  
Load cell connection: 4-wire  
Readability [d]: 200 g  
Recommended adjusting weight: 300 kg (M1)  
Repeatability: 200 g  
Resolution: 3000  
Warm up time: 10 min  
Weighing capacity [Max]: 600 kg  
Weighing system: Strain gauge  
Weighing units: lb kg PCS

## Display

Display digit height (large): 2,500 cm  
Display digit height (small): 2,500 cm

## Functions

BMI function: yes

## Environmental conditions

Maximum humidity: 80 %  
Maximum operating temperature: 40 °C  
Minimum ambient temperature: -10 °C  
Minimum humidity: 5 %

## Power supply

Battery: 4x1.5 V AA  
Input voltage: 100 V - 240V AC 50/60Hz  
0.3A  
Mains adapter: Mains adapter external  
Mains adapter/adaptor included: EURO AUS UK US  
Operating time: 60 h