

Lab Specialty Products Lab Ball Valves & Needle Valves



Lab Ball Valves



Pressure Rating @ 73°F (23°C), Water
 1/4" - 3/8" 150 psi
 Maximum Service Temperature
 PVC = 140°F (60°C)
 CPVC = 200°F (93°C)
 Temperature/Pressure De-ratings Apply
 Rated for Vacuum Service

Valve & Adapters includes:

- 1 - Threaded 1/4" Valve
- 2 - O-ring Sealed 1/4" MPT x Mipt Adapters
- 2 - EPDM or Viton® O-rings (AS568-013 size)
- 1 - End Connector Wrench
- 2 - O-ring Sealed 1/4" MPT x 3/8" I.D. Tubing Barb Adapters
- OR -
- 2 - O-ring Sealed 1/4" MPT x 1/4" I.D. Tubing Barb Adapters



Socket/Threaded Valve Only

All Valves Assembled with Silicone-Free, Water Soluble Lubricant

Valve & Adapters

PVC

Size	EPDM	Viton®	Std Pk	Mstr Pk	Disc Code
Valve & Adapters Threaded Ends					
1/4X1/4T	1529-002A 24.46	1539-002A 25.57	1	25	218
1/4X3/8T	1529-002 24.46	1539-002 25.57	1	25	218
Valve only Threaded Ends					
1/4	1521-002 19.55	1531-002 21.76	50	200	218
3/8	1521-003 27.48	1531-003 30.47	50	200	218
Valve only Socket Ends					
1/4	1522-002 19.55	1532-002 22.12	50	200	218
3/8	1522-003 27.48	1532-003 30.47	50	200	218

CPVC

Size	EPDM	Viton®	Std Pk	Mstr Pk	Disc Code
Valve & Adapters Threaded Ends					
1/4X1/4T	1529-002CA 29.36	1539-002CA 29.93	1	25	219
1/4X3/8T	1529-002C 29.36	1539-002C 29.93	1	25	219
Valve only Threaded Ends					
1/4	1521-002C 23.51	1531-002C 25.85	50	200	219
3/8	1521-003C 32.97	1531-003C 30.90	50	200	219
Valve only Socket Ends					
1/4	1522-002C 23.51	1532-002C 27.98	50	200	219
3/8	1522-003C 32.97	1532-003C 36.60	50	200	219

Needle Valves



Pressure Rating @ 73°F (23°C), Water
 PVC or CPVC 235 psi
 PP 150 psi

Maximum Service Temperature

PVC = 140°F (60°C)
 CPVC = 200°F (93°C)
 PP = 180°F (82°C)

Solid PTFE Stem Seals
 No Elastomer or Lubricants used
 Valves include Panel Mounting Nut

PVC Needle Valve

Size	Threaded	Socket	SR Threaded	Std Pk	Mstr Pk	Disc Code
Globe Pattern						
1/4	5591-002 67.71	5592-002 67.71	---	1	18	218
3/8	5591-003 67.71	5592-003 67.71	5591-003SR 61.76	1	18	218
1/2	5591-005 75.15	5592-005 75.15	5591-005SR 77.17	1	18	218
Angle Pattern						
1/4	5691-002 67.71	5692-002 67.71	---	1	18	218
3/8	5691-003 67.71	5692-003 67.71	---	1	18	218
1/2	5691-005 75.15	5692-005 75.15	5691-005SR 77.17	1	18	218

CPVC Needle Valve

Size	Threaded	Socket	SR Threaded	Std Pk	Mstr Pk	Disc Code
Globe Pattern						
1/4	5591-002C 79.74	5592-002C 79.74	---	1	18	219
3/8	5591-003C 79.74	5592-003C 79.74	5591-003CSR 79.56	1	18	219
1/2	5591-005C 84.33	5592-005C 84.33	5591-005CSR 86.49	1	18	219
Angle Pattern						
1/4	5691-002C 79.74	5692-002C 79.74	---	1	18	219
3/8	5691-003C 79.74	5692-003C 79.74	---	1	18	219
1/2	5691-005C 84.33	5692-005C 84.33	5691-005CSR 86.49	1	18	219

Made in the U.S.A.

NOT FOR DISTRIBUTION OF COMPRESSED AIR OR GAS
 Progressive Products from Spears® Innovation and Technology

Page 567

**Schedule 80 PVC Industrial Products & Accessories
Utility Ball Valves & Lab Ball Valves**



Utility Ball Valves



Pressure Rating @ 73°F (23°C), Water
1/2" - 4" 150 psi
Maximum Service Temperature
PVC = 140°F (60°C)
Temperature/Pressure De-ratings Apply

All Valves Assembled with Silicone-Free,
Water Soluble Lubricant

PVC w/EPDM O-ring Seal

Size	Threaded Ends	Socket Ends	Std Pk	Mstr Pk	Disc Code
PVC Gray					
1/2	2621-005G 8.90	2622-005G 8.90	50	0	215
3/4	2621-007G 10.56	2622-007G 10.56	25	0	215
1	2621-010G 14.36	2622-010G 14.36	25	0	215
1-1/4	2621-012G 19.03	2622-012G 19.03	20	0	215
1-1/2	2621-015G 29.04	2622-015G 29.04	20	0	215

PVC w/EPDM O-ring Seal (continued)

Size	Threaded Ends	Socket Ends	Std Pk	Mstr Pk	Disc Code
PVC Gray					
2	2621-020G 36.71	2622-020G 36.71	8	0	215
2-1/2	2621-025G 62.83	2622-025G 62.83	6	0	214
3	2621-030G 112.69	2622-030G 112.69	1	4	214
4	2621-040G 206.54	2622-040G 206.54	1	0	214

Lab Ball Valves



Pressure Rating @ 73°F (23°C), Water
1/4" - 3/8" 150 psi
Maximum Service Temperature
PVC = 140°F (60°C)
Temperature/Pressure De-ratings Apply
Rated for Vacuum Service

Valve & Adapters includes:

- 1 - Threaded 1/4" Valve
- 2 - O-ring Sealed 1/4" MPT x Mipt Adapters
- 2 - EPDM or Viton® O-rings (AS568-013 size)
- 1 - End Connector Wrench
- 2 - O-ring Sealed 1/4" MPT x 3/8" I.D. Tubing Barb Adapters
- OR -
- 2 - O-ring Sealed 1/4" MPT x 1/4" I.D. Tubing Barb Adapters



Socket/Threaded Valve Only

All Valves Assembled with Silicone-Free, Water Soluble Lubricant

Valve & Adapters

PVC

Size	EPDM	Viton®	Std Pk	Mstr Pk	Disc Code
------	------	--------	--------	---------	-----------

Valve & Adapters Threaded Ends

1/4X3/8T	1529-002 24.46	1539-002 25.57	1	25	218
1/4X1/4T	1529-002A 24.46	1539-002A 25.57	1	25	218

Valve only Threaded Ends

1/4	1521-002 19.55	1531-002 21.76	50	200	218
3/8	1521-003 27.48	1531-003 30.47	50	200	218

Valve only Socket Ends

1/4	1522-002 19.55	1532-002 22.12	50	200	218
3/8	1522-003 27.48	1532-003 30.47	50	200	218



Thermoplastic Valves Compact Ball Valves (Regular Style) & Lab Ball Valves

Compact Ball Valves (Regular Style)

CPVC (continued)

Size	EPDM	Viton®	Std Pk	Mstr Pk	Disc Code
Flanged Ends					
2	2123-020C 212.90	2133-020C 226.37	1	0	212
3	2123-030C 509.85	---	1	0	213
4	2123-040C 796.45	2133-040C 872.15	1	0	213
6 (Lever Handle)	2123-060C 1512.80	2133-060C 1622.91	1	0	213
6 (Tee Handle)	21236-060C 1512.80	21336-060C 1622.91	1	0	213

Lab Ball Valves



Socket/Threaded Valve Only

Pressure Rating @ 73°F (23°C), Water
1/4" - 3/8" 150 psi
Maximum Service Temperature
PVC = 140°F (60°C)
CPVC = 200°F (93°C)
Temperature/Pressure De-ratings Apply
Rated for Vacuum Service

All Valves Assembled with Silicone-Free, Water Soluble Lubricant

Valve & Adapters includes:

- 1 - Threaded 1/4" Valve
- 2 - O-ring Sealed 1/4" MPT x Mipt Adapters
- 2 - EPDM or Viton® O-rings (AS568-013 size)
- 1 - End Connector Wrench
- 2 - O-ring Sealed 1/4" MPT x 3/8" I.D. Tubing Barb Adapters
- OR -
- 2 - O-ring Sealed 1/4" MPT x 1/4" I.D. Tubing Barb Adapters



Valve & Adapters

PVC

Size	EPDM	Viton®	Std Pk	Mstr Pk	Disc Code
Valve & Adapters Threaded Ends					
1/4X1/4T	1529-002A 24.46	1539-002A 25.57	1	25	218
1/4X3/8T	1529-002 24.46	1539-002 25.57	1	25	218

Valve only Threaded Ends

1/4	1521-002 19.55	1531-002 21.76	50	200	218
3/8	1521-003 27.48	1531-003 30.47	50	200	218

Valve only Socket Ends

1/4	1522-002 19.55	1532-002 22.12	50	200	218
3/8	1522-003 27.48	1532-003 30.47	50	200	218

CPVC

Size	EPDM	Viton®	Std Pk	Mstr Pk	Disc Code
Valve & Adapters Threaded Ends					
1/4X1/4T	1529-002CA 29.36	1539-002CA 29.93	1	25	219
1/4X3/8T	1529-002C 29.36	1539-002C 29.93	1	25	219

Valve only Threaded Ends

1/4	1521-002C 23.51	1531-002C 25.85	50	200	219
3/8	1521-003C 32.97	1531-003C 30.90	50	200	219

Valve only Socket Ends

1/4	1522-002C 23.51	1532-002C 27.98	50	200	219
3/8	1522-003C 32.97	1532-003C 36.60	50	200	219