



True Union 2000 Industrial Ball Valves

CPVC 6" Industrial T-Handle Valve Option (Non-Locking) NOTICE: T-Handle is more compact, but will greatly increase difficulty of operation.

Size	EPDM	Viton®	Std Pk	Mstr Pk	Disc Code
Threaded Ends					
6	18216-060C 2122.69	18316-060C 2358.38	1	0	613
SR Threaded Ends					
6	18216-060CSR 2180.86	18316-060CSR 2416.54	1	0	613
Flanged Ends					
6	18236-060C 3461.83	18336-060C 3599.57	1	0	613

True Union 2000 Industrial Vented/Bleach Ball Valves



Pressure Rating @ 73°F (23°C), Water
 1/2" - 4" 235 psi
 6" 150 psi
 Flanged 150 psi

Same True Union 2000 Industrial Ball Valve with Special Ball Vent Design for Sodium Hypochlorite (Bleach) and other Chemical Applications where entrapped fluids may form caustic crystalline residues and pressure build up from gases developed. Valve has a 1/8" vent hole in ball to equalize internal fluid pressures. Install valve with ball vent on the pressure (upstream) side when in closed position.

All Valves assembled with Silicone-Free, Water Soluble Lubricant

Contact Spears® for Pricing & Availability on Custom Elastomer Seals. See Ball Valve Accessories & Repair Kits Section for Additional Options and Features

CPVC True Union 2000 Industrial Vented/Bleach Ball Valves

Size	EPDM	Viton®	Std Pk	Mstr Pk	Disc Code
Threaded & Socket Ends					
Threaded End Connectors available on request					
1/2	1829V-005C 73.34	1839V-005C 81.50	1	18	602
3/4	1829V-007C 92.37	1839V-007C 102.67	1	18	602
1	1829V-010C 109.98	1839V-010C 122.19	1	12	602
1-1/4	1829V-012C 174.84	1839V-012C 194.34	1	8	602
1-1/2	1829V-015C 184.65	1839V-015C 205.16	1	8	602
2	1829V-020C 246.96	1839V-020C 283.87	1	4	602

Socket Ends

2-1/2	1822V-025C 553.67	1832V-025C 615.13	1	0	603
3	1822V-030C 647.37	1832V-030C 719.33	1	0	603
4	1822V-040C 1173.05	1832V-040C 1303.40	1	0	603
6	1822V-060C 2497.30	1832V-060C 2774.57	1	0	613

SR Threaded Ends

1/2	1821V-005CSR 74.51	1831V-005CSR 82.70	1	18	602
3/4	1821V-007CSR 95.27	1831V-007CSR 105.52	1	18	602
1	1821V-010CSR 112.83	1831V-010CSR 125.04	1	12	602
1-1/4	1821V-012CSR 183.46	1831V-012CSR 202.97	1	8	602
1-1/2	1821V-015CSR 193.94	1831V-015CSR 214.44	1	8	602

CPVC True Union 2000 Industrial Vented/Bleach Ball Valves (continued)

Size	EPDM	Viton®	Std Pk	Mstr Pk	Disc Code
SR Threaded Ends					
2	1821V-020CSR 257.01	1831V-020CSR 293.94	1	4	602
2-1/2	1821V-025CSR 580.70	1831V-025CSR 642.17	1	0	603
3	1821V-030CSR 674.40	1831V-030CSR 746.37	1	0	603
4	1821V-040CSR 1204.61	1831V-040CSR 1334.97	1	0	603

Flanged Ends

1/2	1823V-005C 124.45	1833V-005C 127.13	1	8	602
3/4	1823V-007C 152.56	1833V-007C 158.93	1	8	602
1	1823V-010C 174.65	1833V-010C 185.40	1	8	602
1-1/4	1823V-012C 260.96	1833V-012C 270.11	1	8	602
1-1/2	1823V-015C 287.03	1833V-015C 296.61	1	4	602
2	1823V-020C 399.43	1833V-020C 475.69	1	0	602
2-1/2	1823V-025C 745.50	1833V-025C 894.83	1	0	603
3	1823V-030C 1090.23	1833V-030C 1115.07	1	0	603
4	1823V-040C 1988.55	1833V-040C 1988.57	1	0	603
6	1823V-060C 4234.79	1833V-060C 4234.79	1	0	613



Thermoplastic Valves True Union 2000 Industrial Ball Valves

PVC Industrial (continued)

Size	EPDM	Viton®	Std Pk	Mstr Pk	Disc Code
4	1823-040 1000.54	1833-040 1159.79	1	0	601
6	1823-060 2130.35	1833-060 2470.10	1	0	612
8	1823-080 2833.36	1833-080 3285.23	1	0	612

Flanged Ends

8" Venturied valves are 6" ball valves fitted with 6x8 end connector adapters.

PVC 6" Industrial T-Handle Valve Option (Non-Locking)

NOTICE: T-Handle is more compact, but will greatly increase difficulty of operation.

Size	EPDM	Viton®	Std Pk	Mstr Pk	Disc Code
------	------	--------	--------	---------	-----------

Socket Ends

6	18226-060 1352.89	18326-060 1501.36	1	0	612
----------	-----------------------------	-----------------------------	---	---	-----

Threaded Ends

6	18216-060 1352.89	18316-060 1501.36	1	0	612
----------	-----------------------------	-----------------------------	---	---	-----

SR Threaded Ends

6	18216-060SR 1391.15	18316-060SR 1539.60	1	0	612
----------	-------------------------------	-------------------------------	---	---	-----

Flanged Ends

6	18236-060 2130.35	18336-060 2470.10	1	0	612
----------	-----------------------------	-----------------------------	---	---	-----

CPVC Industrial

Size	EPDM	Viton®	Std Pk	Mstr Pk	Disc Code
------	------	--------	--------	---------	-----------

Threaded & Socket Ends

1/2	1829-005C 62.35	1839-005C 69.28	1	18	602
3/4	1829-007C 78.52	1839-007C 87.27	1	18	602
1	1829-010C 93.48	1839-010C 103.86	1	12	602
1-1/4	1829-012C 148.61	1839-012C 165.17	1	8	602
1-1/2	1829-015C 156.95	1839-015C 174.39	1	8	602
2	1829-020C 209.90	1839-020C 241.30	1	4	602

Socket Ends

2-1/2	1822-025C 470.62	1832-025C 522.88	1	0	603
3	1822-030C 550.26	1832-030C 611.45	1	0	603
4	1822-040C 997.11	1832-040C 1107.88	1	0	603
6	1822-060C 2122.69	1832-060C 2358.38	1	0	613
8	1822-080C 2823.20	1832-080C 3136.67	1	0	613

8" Venturied valves are 6" ball valves fitted with 6x8 end connector adapters.

Threaded Ends

2-1/2	1821-025C 470.62	1831-025C 522.88	1	0	603
3	1821-030C 550.26	1831-030C 611.45	1	0	603
4	1821-040C 997.11	1831-040C 1107.88	1	0	603
6	1821-060C 2122.69	1831-060C 2358.38	1	0	613

SR Threaded Ends

1/2	1821-005CSR 63.35	1831-005CSR 70.29	1	18	602
3/4	1821-007CSR 80.97	1831-007CSR 89.71	1	18	602
1	1821-010CSR 95.93	1831-010CSR 106.29	1	12	602

CPVC Industrial (continued)

Size	EPDM	Viton®	Std Pk	Mstr Pk	Disc Code
1-1/4	1821-012CSR 155.96	1831-012CSR 172.52	1	8	602
1-1/2	1821-015CSR 164.85	1831-015CSR 182.26	1	8	602
2	1821-020CSR 218.45	1831-020CSR 249.85	1	4	602
2-1/2	1821-025CSR 493.60	1831-025CSR 545.85	1	0	603
3	1821-030CSR 573.23	1831-030CSR 634.41	1	0	603
4	1821-040CSR 1023.91	1831-040CSR 1134.72	1	0	603
6	1821-060CSR 2180.86	1831-060CSR 2416.54	1	0	613

SR Threaded Ends

Spigot Ends

1/2	1827-005C 62.35	1837-005C 69.28	1	18	602
3/4	1827-007C 78.52	1837-007C 87.27	1	18	602
1	1827-010C 93.48	1837-010C 103.86	1	12	602
1-1/4	1827-012C 148.61	1837-012C 165.17	1	8	602
1-1/2	1827-015C 156.95	1837-015C 174.39	1	8	602
2	1827-020C 209.90	1837-020C 241.30	1	4	602
2-1/2	1827-025C 470.62	1837-025C 522.88	1	0	603
3	1827-030C 550.26	1837-030C 611.45	1	0	603
4	1827-040C 997.11	1837-040C 1107.88	1	0	603
6	1827-060C 2122.69	1837-060C 2358.38	1	0	613

Flanged Ends

1/2	1823-005C 105.79	1833-005C 108.07	1	8	602
3/4	1823-007C 129.68	1833-007C 135.06	1	8	602
1	1823-010C 148.45	1833-010C 157.59	1	8	602
1-1/4	1823-012C 221.81	1833-012C 229.60	1	8	602
1-1/2	1823-015C 243.98	1833-015C 252.11	1	4	602
2	1823-020C 339.51	1833-020C 404.35	1	0	602
2-1/2	1823-025C 633.67	1833-025C 760.61	1	0	603
3	1823-030C 926.70	1833-030C 947.83	1	0	603
4	1823-040C 1625.28	1833-040C 1690.28	1	0	603
6	1823-060C 3461.83	1833-060C 3599.57	1	0	613
8	1823-080C 4604.22	1833-080C 4787.41	1	0	613

8" Venturied valves are 6" ball valves fitted with 6x8 end connector adapters.

CPVC 6" Industrial T-Handle Valve Option (Non-Locking) NOTICE: T-Handle is more compact, but will greatly increase difficulty of operation.

Size	EPDM	Viton®	Std Pk	Mstr Pk	Disc Code
------	------	--------	--------	---------	-----------

Socket Ends

6	18226-060C 2122.69	18326-060C 2358.38	1	0	613
----------	------------------------------	------------------------------	---	---	-----

Threaded Ends

6	18216-060C 2122.69	18316-060C 2358.38	1	0	613
----------	------------------------------	------------------------------	---	---	-----