



Thermoplastic Valves
True Union 2000 Industrial Vented/Bleach Ball Valves

CPVC True Union 2000 Industrial Vented/Bleach Ball Valves (continued)

Size	EPDM	Viton®	Std Pk	Mstr Pk	Disc Code
------	------	--------	--------	---------	-----------

Threaded & Socket Ends

1	1829V-010C 109.98	1839V-010C 122.19	1	12	602
1-1/4	1829V-012C 174.84	1839V-012C 194.34	1	8	602
1-1/2	1829V-015C 184.65	1839V-015C 205.16	1	8	602
2	1829V-020C 246.96	1839V-020C 283.87	1	4	602

Socket Ends

2-1/2	1822V-025C 553.67	1832V-025C 615.13	1	0	603
3	1822V-030C 647.37	1832V-030C 719.33	1	0	603
4	1822V-040C 1173.05	1832V-040C 1303.40	1	0	603
6	1822V-060C 2497.30	1832V-060C 2774.57	1	0	613

SR Threaded Ends

1/2	1821V-005CSR 74.51	1831V-005CSR 82.70	1	18	602
3/4	1821V-007CSR 95.27	1831V-007CSR 105.52	1	18	602
1	1821V-010CSR 112.83	1831V-010CSR 125.04	1	12	602
1-1/4	1821V-012CSR 183.46	1831V-012CSR 202.97	1	8	602
1-1/2	1821V-015CSR 193.94	1831V-015CSR 214.44	1	8	602
2	1821V-020CSR 257.01	1831V-020CSR 293.94	1	4	602
2-1/2	1821V-025CSR 580.70	1831V-025CSR 642.17	1	0	603
3	1821V-030CSR 674.40	1831V-030CSR 746.37	1	0	603
4	1821V-040CSR 1204.61	1831V-040CSR 1334.97	1	0	603

Flanged Ends

1/2	1823V-005C 124.45	1833V-005C 127.13	1	8	602
3/4	1823V-007C 152.56	1833V-007C 158.93	1	8	602
1	1823V-010C 174.65	1833V-010C 185.40	1	8	602
1-1/4	1823V-012C 260.96	1833V-012C 270.11	1	8	602
1-1/2	1823V-015C 287.03	1833V-015C 296.61	1	4	602
2	1823V-020C 399.43	1833V-020C 475.69	1	0	602
2-1/2	1823V-025C 745.50	1833V-025C 894.83	1	0	603
3	1823V-030C 1090.23	1833V-030C 1115.07	1	0	603
4	1823V-040C 1988.55	1833V-040C 1988.57	1	0	603
6	1823V-060C 4234.79	1833V-060C 4234.79	1	0	613



True Union 2000 Industrial Ball Valves

CPVC 6" Industrial T-Handle Valve Option (Non-Locking) NOTICE: T-Handle is more compact, but will greatly increase difficulty of operation.

Size	EPDM	Viton®	Std Pk	Mstr Pk	Disc Code
Threaded Ends					
6	18216-060C 2122.69	18316-060C 2358.38	1	0	613
SR Threaded Ends					
6	18216-060CSR 2180.86	18316-060CSR 2416.54	1	0	613
Flanged Ends					
6	18236-060C 3461.83	18336-060C 3599.57	1	0	613

True Union 2000 Industrial Vented/Bleach Ball Valves



Pressure Rating @ 73°F (23°C), Water
 1/2" - 4" 235 psi
 6" 150 psi
 Flanged 150 psi

Same True Union 2000 Industrial Ball Valve with Special Ball Vent Design for Sodium Hypochlorite (Bleach) and other Chemical Applications where entrapped fluids may form caustic crystalline residues and pressure build up from gases developed. Valve has a 1/8" vent hole in ball to equalize internal fluid pressures. Install valve with ball vent on the pressure (upstream) side when in closed position.

All Valves assembled with Silicone-Free, Water Soluble Lubricant

Contact Spears® for Pricing & Availability on Custom Elastomer Seals. See Ball Valve Accessories & Repair Kits Section for Additional Options and Features

CPVC True Union 2000 Industrial Vented/Bleach Ball Valves

Size	EPDM	Viton®	Std Pk	Mstr Pk	Disc Code
Threaded & Socket Ends					
Threaded End Connectors available on request					
1/2	1829V-005C 73.34	1839V-005C 81.50	1	18	602
3/4	1829V-007C 92.37	1839V-007C 102.67	1	18	602
1	1829V-010C 109.98	1839V-010C 122.19	1	12	602
1-1/4	1829V-012C 174.84	1839V-012C 194.34	1	8	602
1-1/2	1829V-015C 184.65	1839V-015C 205.16	1	8	602
2	1829V-020C 246.96	1839V-020C 283.87	1	4	602

Socket Ends

2-1/2	1822V-025C 553.67	1832V-025C 615.13	1	0	603
3	1822V-030C 647.37	1832V-030C 719.33	1	0	603
4	1822V-040C 1173.05	1832V-040C 1303.40	1	0	603
6	1822V-060C 2497.30	1832V-060C 2774.57	1	0	613

SR Threaded Ends

1/2	1821V-005CSR 74.51	1831V-005CSR 82.70	1	18	602
3/4	1821V-007CSR 95.27	1831V-007CSR 105.52	1	18	602
1	1821V-010CSR 112.83	1831V-010CSR 125.04	1	12	602
1-1/4	1821V-012CSR 183.46	1831V-012CSR 202.97	1	8	602
1-1/2	1821V-015CSR 193.94	1831V-015CSR 214.44	1	8	602

CPVC True Union 2000 Industrial Vented/Bleach Ball Valves (continued)

Size	EPDM	Viton®	Std Pk	Mstr Pk	Disc Code
SR Threaded Ends					
2	1821V-020CSR 257.01	1831V-020CSR 293.94	1	4	602
2-1/2	1821V-025CSR 580.70	1831V-025CSR 642.17	1	0	603
3	1821V-030CSR 674.40	1831V-030CSR 746.37	1	0	603
4	1821V-040CSR 1204.61	1831V-040CSR 1334.97	1	0	603

Flanged Ends

1/2	1823V-005C 124.45	1833V-005C 127.13	1	8	602
3/4	1823V-007C 152.56	1833V-007C 158.93	1	8	602
1	1823V-010C 174.65	1833V-010C 185.40	1	8	602
1-1/4	1823V-012C 260.96	1833V-012C 270.11	1	8	602
1-1/2	1823V-015C 287.03	1833V-015C 296.61	1	4	602
2	1823V-020C 399.43	1833V-020C 475.69	1	0	602
2-1/2	1823V-025C 745.50	1833V-025C 894.83	1	0	603
3	1823V-030C 1090.23	1833V-030C 1115.07	1	0	603
4	1823V-040C 1988.55	1833V-040C 1988.57	1	0	603
6	1823V-060C 4234.79	1833V-060C 4234.79	1	0	613