



**Schedule 80 PVC Industrial Products & Accessories
Compact 2000 Ball Valves & Compact Ball Valves (Regular Style)**

Compact 2000 Ball Valves

PVC 2000 Compact Ball Valve (continued)

Size	EPDM	Viton®	Std Pk	Mstr Pk	Disc Code
Flanged Ends					
1	6623-010 62.33	6633-010 65.67	10	120	210
1-1/4	6623-012 77.83	6633-012 83.50	10	120	210
1-1/2	6623-015 94.16	6633-015 102.35	10	120	210
2	6623-020 125.66	6633-020 131.17	10	120	210

Compact Ball Valves (Regular Style)



Socket/Threaded Style

Pressure Rating @ 73°F (23°C), Water
 1/2" - 2" 235 psi
 3" - 6" 150 psi
 Flanged 150 psi
 Maximum Service Temperature
 PVC = 140°F (60°C)
 Temperature/Pressure De-ratings Apply
 Rated for Vacuum Service

All Valves Assembled with Silicone-Free, Water Soluble Lubricants.
 See Ball Valve Accessories & Repair Kits Section for Additional
 Options & Features

Note: Standard 6" Valve uses Lever-Style Handle for proper
 leverage.
 T-Handle option is more compact but will increase difficulty of
 operation.

PVC

Size	EPDM	Viton®	Std Pk	Mstr Pk	Disc Code
Socket Ends					
1/2	2122-005 21.16	2132-005 23.83	10	80	210
3/4	2122-007 28.88	2132-007 29.57	10	0	210
1	2122-010 31.51	2132-010 35.38	10	0	210
1-1/4	2122-012 56.51	2132-012 62.82	6	0	210
1-1/2	2122-015 69.97	2132-015 73.11	5	0	210
2	2122-020 75.41	2132-020 84.74	6	0	210
3	2122-030 245.11	2132-030 275.37	1	4	211
4	2122-040 377.10	2132-040 542.81	1	0	211
6 (Lever Handle)	2122-060 489.73	2132-060 704.95	1	0	211
6 (Tee Handle)	21226-060 489.73	21326-060 704.95	1	0	211

Threaded Ends

1/2	2121-005 21.16	2131-005 23.83	10	80	210
3/4	2121-007 28.88	2131-007 29.57	10	0	210
1	2121-010 31.51	2131-010 35.38	10	0	210
1-1/4	2121-012 56.51	2131-012 62.82	6	0	210
1-1/2	2121-015 69.97	2131-015 73.11	5	0	210
2	2121-020 75.41	2131-020 84.74	6	0	210
3	2121-030 245.11	2131-030 275.37	1	4	211
4	2121-040 377.10	2131-040 542.81	1	0	211

PVC

Size	EPDM	Viton®	Std Pk	Mstr Pk	Disc Code
Flanged Ends					
1/2	2123-005 46.78	2133-005 49.83	1	8	210
3/4	2123-007 56.60	2133-007 58.85	1	8	210
1	2123-010 62.44	2133-010 66.29	1	8	210
1-1/4	2123-012 88.40	2133-012 94.71	1	8	210
1-1/2	2123-015 102.28	2133-015 107.09	1	4	210
2	2123-020 118.72	2133-020 127.96	1	0	210
3	2123-030 318.94	2133-030 349.21	1	0	211
4	2123-040 470.46	2133-040 636.16	1	0	211
6 (Lever Handle)	2123-060 905.83	2133-060 997.09	1	0	211
6 (Tee Handle)	21236-060 905.83	21336-060 997.09	1	0	211

Thermoplastic Valves Compact Ball Valves (Regular Style)



Pressure Rating @ 73°F (23°C), Water
 1/2" - 2" 235 psi
 3" - 6" 150 psi
 Flanged 150 psi
 Maximum Service Temperature
 PVC = 140°F (60°C)
 CPVC = 200°F (93°C)
 Temperature/Pressure De-ratings Apply
 Rated for Vacuum Service

All Valves Assembled with Silicone-Free, Water Soluble Lubricants.

See Ball Valve Accessories & Repair Kits Section
 for Additional Options and Features

Note: Standard 6" Valve uses Lever-Style Handle for proper leverage.

T-Handle option is more compact but will increase difficulty of operation.

Socket/Threaded Style

PVC

Size	EPDM	Viton®	Std Pk	Mstr Pk	Disc Code
Socket Ends					
1/2	2122-005 21.16	2132-005 23.83	10	80	210
3/4	2122-007 28.88	2132-007 29.57	10	0	210
1	2122-010 31.51	2132-010 35.38	10	0	210
1-1/4	2122-012 56.51	2132-012 62.82	6	0	210
1-1/2	2122-015 69.97	2132-015 73.11	5	0	210
2	2122-020 75.41	2132-020 84.74	6	0	210
3	2122-030 245.11	2132-030 275.37	1	4	211
4	2122-040 377.10	2132-040 542.81	1	0	211
6 (Lever Handle)	2122-060 489.73	2132-060 704.95	1	0	211
6 (Tee Handle)	21226-060 489.73	21326-060 704.95	1	0	211

Threaded Ends

1/2	2121-005 21.16	2131-005 23.83	10	80	210
3/4	2121-007 28.88	2131-007 29.57	10	0	210
1	2121-010 31.51	2131-010 35.38	10	0	210
1-1/4	2121-012 56.51	2131-012 62.82	6	0	210
1-1/2	2121-015 69.97	2131-015 73.11	5	0	210
2	2121-020 75.41	2131-020 84.74	6	0	210
3	2121-030 245.11	2131-030 275.37	1	4	211
4	2121-040 377.10	2131-040 542.81	1	0	211

Flanged Ends

1/2	2123-005 46.78	2133-005 49.83	1	8	210
3/4	2123-007 56.60	2133-007 58.85	1	8	210
1	2123-010 62.44	2133-010 66.29	1	8	210
1-1/4	2123-012 88.40	2133-012 94.71	1	8	210
1-1/2	2123-015 102.28	2133-015 107.09	1	4	210
2	2123-020 118.72	2133-020 127.96	1	0	210
3	2123-030 318.94	2133-030 349.21	1	0	211
4	2123-040 470.46	2133-040 636.16	1	0	211
6 (Lever Handle)	2123-060 905.83	2133-060 997.09	1	0	211

PVC (continued)

Size	EPDM	Viton®	Std Pk	Mstr Pk	Disc Code
Flanged Ends					
6 (Tee Handle)	21236-060 905.83	21336-060 997.09	1	0	211

CPVC

Size	EPDM	Viton®	Std Pk	Mstr Pk	Disc Code
Socket Ends					
1/2	2122-005C 24.93	2132-005C 27.72	10	80	212
3/4	2122-007C 32.88	2132-007C 36.96	10	0	212
1	2122-010C 41.11	2132-010C 46.21	10	0	212
1-1/4	2122-012C 83.18	2132-012C 92.39	6	0	212
1-1/2	2122-015C 102.77	2132-015C 108.04	5	0	212
2	2122-020C 108.98	2132-020C 122.45	6	0	212
3	2122-030C 331.59	2132-030C 369.84	1	4	213
4	2122-040C 612.98	2132-040C 688.69	1	0	213
6 (Lever Handle)	2122-060C 1001.78	2132-060C 1067.44	1	0	213
6 (Tee Handle)	21226-060C 1001.78	21326-060C 1067.44	1	0	213

Threaded Ends

1/2	2121-005C 24.93	2131-005C 27.72	10	80	212
3/4	2121-007C 32.88	2131-007C 36.96	10	0	212
1	2121-010C 41.11	2131-010C 46.21	10	0	212
1-1/4	2121-012C 83.18	2131-012C 92.39	6	0	212
1-1/2	2121-015C 102.77	2131-015C 108.04	5	0	212
2	2121-020C 108.98	2131-020C 122.45	6	0	212
3	2121-030C 331.59	2131-030C 369.84	1	4	213
4	2121-040C 612.98	2131-040C 688.69	1	0	213

Flanged Ends

1/2	2123-005C 69.49	2133-005C 72.30	1	8	212
3/4	2123-007C 80.68	2133-007C 84.76	1	8	212
1	2123-010C 95.40	2133-010C 100.52	1	8	212
1-1/4	2123-012C 150.33	2133-012C 159.56	1	8	212
1-1/2	2123-015C 188.00	2133-015C 193.81	1	4	212