



**Schedule 80 CPVC Industrial Products & Accessories**  
**True Union Ball Check Valves (Regular Style) & Foot Valve Screens**

**True Union Ball Check Valves (Regular Style)**



Socket/Threaded Style

Pressure Rating @ 73°F (23°C), Water  
 1/2" - 2" 235 psi  
 2-1/2" - 6" 150 psi  
 Flanged 150 psi  
 Maximum Service Temperature  
 CPVC = 200°F (93°C)  
 Temperature/Pressure De-ratings Apply  
 Rated for Vacuum Service

All Valves assembled with Silicone-Free,  
 Water Soluble Lubricant

6" Venturied Valves are 4" Ball Check Valves equipped with  
 4x6 End Connectors.

**General Installation Information:** Ball check valves may be installed in either horizontal or vertical position. A minimum of ten (10) pipe diameters' distance maintained from any pump or other source of turbulence. Check valves MUST be installed with the valve's FLOW arrow pointing in the direction of flow.

**CPVC**

Size	EPDM	Viton®	Std Pk	Mstr Pk	Disc Code
<b>Socket &amp; Threaded Ends</b>					
<b>1/2</b>	2229-005C 86.59	2239-005C 96.40	1	18	222
<b>3/4</b>	2229-007C 103.65	2239-007C 115.18	1	12	222
<b>1</b>	2229-010C 122.30	2239-010C 135.87	1	8	222
<b>1-1/4</b>	2229-012C 210.61	2239-012C 233.81	1	8	222
<b>1-1/2</b>	2229-015C 254.68	2239-015C 269.20	1	8	222
<b>2</b>	2229-020C 282.03	2239-020C 313.45	1	4	222

**Socket Ends**

<b>2-1/2</b>	2222-025C 589.49	2232-025C 654.97	1	0	222
<b>3</b>	2222-030C 960.18	2232-030C 1050.76	1	0	222
<b>4</b>	2222-040C 1293.59	2232-040C 1438.23	1	0	222

**Socket Venturied Ends**

<b>6 VENTURIED</b>	2222-060C 1668.73	2232-060C 1869.67	1	0	223
--------------------	----------------------	----------------------	---	---	-----

**Threaded Ends**

<b>2-1/2</b>	2221-025C 589.49	2231-025C 654.97	1	0	222
<b>3</b>	2221-030C 960.18	2231-030C 1050.76	1	0	222
<b>4</b>	2221-040C 1293.59	2231-040C 1438.23	1	0	222

**CPVC**

Size	EPDM	Viton®	Std Pk	Mstr Pk	Disc Code
<b>Flanged Ends</b>					
<b>1/2</b>	2223-005C 107.52	2233-005C 134.35	6	0	222
<b>3/4</b>	2223-007C 128.27	2233-007C 162.39	5	0	222
<b>1</b>	2223-010C 153.16	2233-010C 188.82	5	0	222
<b>1-1/4</b>	2223-012C 258.35	2233-012C 320.33	2	0	222
<b>1-1/2</b>	2223-015C 276.00	2233-015C 344.88	3	0	222
<b>2</b>	2223-020C 488.01	2233-020C 523.21	2	0	222
<b>2-1/2</b>	2223-025C 776.52	2233-025C 884.18	1	0	222
<b>3</b>	2223-030C 987.29	2233-030C 1083.11	1	0	222
<b>4</b>	2223-040C 1633.40	2233-040C 1753.98	1	0	222

**Flanged Venturied Ends**

<b>6 VENTURIED</b>	2223-060C 1969.11	2233-060C 2131.44	1	0	223
--------------------	----------------------	----------------------	---	---	-----

**Foot Valve Screens**

Convert to Foot Valve using adapter - Fits all Socket Ball Check Valves  
 or any IPS fitting socket



CPVC Foot Valve Screen

**Foot Valve Screens**

Part Number	Size	Std Pk	Mstr Ctn	Disc Code	Price Each
<b>CPVC</b>					
FVS-005C	<b>1/2</b>	10	60	299	59.71
FVS-007C	<b>3/4</b>	10	60	299	64.41
FVS-010C	<b>1</b>	10	40	299	73.12
FVS-012C	<b>1-1/4</b>	5	30	299	112.93
FVS-015C	<b>1-1/2</b>	5	0	299	117.26
FVS-020C	<b>2</b>	5	0	299	129.45
FVS-025C	<b>2-1/2</b>	5	0	299	188.60

**Foot Valve Screens (continued)**

Part Number	Size	Std Pk	Mstr Ctn	Disc Code	Price Each
FVS-030C	<b>3</b>	5	0	299	210.03
FVS-040C	<b>4</b>	5	0	299	300.18
FVS-060C	<b>6</b>	5	0	299	428.95