

## Thermoplastic Valves Single Entry Ball Valves



PVC White – Socket/Threaded Style

Pressure Rating @ 73°F (23°C), Water  
 1/2" - 2" 235 psi  
 3" - 4" 150 psi  
 Maximum Service Temperature  
 PVC = 140°F (60°C)  
 Temperature/Pressure Deratings Apply  
 Rated for Vacuum Service

All Valves Assembled with Silicone-Free, Water Soluble Lubricant. See  
 Ball Valve Accessories & Repair Kits Section for Additional Options and  
 Features



PVC Gray – Socket/Threaded Style

### PVC White

Size	Buna-N	EPDM	Viton®	Std Pk	Mstr Pk	Disc Code
<b>Threaded Ends</b>						
1/2	2411-005W 18.07	2421-005W 20.04	2431-005W 22.29	10	120	240
3/4	2411-007W 24.46	2421-007W 25.22	2431-007W 28.03	10	80	240
1	2411-010W 26.70	2421-010W 29.66	2431-010W 32.98	10	0	240
1-1/4	2411-012W 37.13	2421-012W 41.29	2431-012W 45.87	6	0	240
1-1/2	2411-015W 48.13	2421-015W 55.88	2431-015W 60.59	5	0	240
2	2411-020W 54.18	2421-020W 60.14	2431-020W 66.85	5	0	240
3	2411-030W 197.05	2421-030W 244.45	2431-030W 281.85	1	0	240
4	2411-040W 416.55	2421-040W 458.93	2431-040W 498.88	1	0	240

### Socket Ends

1/2	2412-005W 18.07	2422-005W 20.04	2432-005W 22.29	10	120	240
3/4	2412-007W 24.46	2422-007W 25.22	2432-007W 28.03	10	80	240
1	2412-010W 26.70	2422-010W 29.66	2432-010W 32.98	10	0	240
1-1/4	2412-012W 37.13	2422-012W 41.29	2432-012W 45.87	6	0	240
1-1/2	2412-015W 48.13	2422-015W 55.88	2432-015W 60.60	5	0	240
2	2412-020W 54.18	2422-020W 60.14	2432-020W 66.85	5	0	240
3	2412-030W 197.05	2422-030W 244.45	2432-030W 281.85	1	0	240
4	2412-040W 416.55	2422-040W 458.93	2432-040W 498.88	1	0	240

### PVC Gray

Size	Buna-N	EPDM	Viton®	Std Pk	Mstr Pk	Disc Code
<b>Threaded Ends</b>						
1/2	2411-005G 19.84	2421-005G 21.99	2431-005G 24.46	10	120	240
3/4	2411-007G 24.99	2421-007G 27.80	2431-007G 30.87	10	80	240
1	2411-010G 29.40	2421-010G 32.63	2431-010G 36.27	10	0	240
1-1/4	2411-012G 40.83	2421-012G 45.39	2431-012G 50.37	6	0	240
1-1/2	2411-015G 51.40	2421-015G 60.21	2431-015G 66.96	5	0	240
2	2411-020G 59.52	2421-020G 66.14	2431-020G 73.45	5	0	240
3	2411-030G 207.45	2421-030G 257.29	2431-030G 296.69	1	0	240
4	2411-040G 438.45	2421-040G 483.10	2431-040G 525.12	1	0	240

### Socket Ends

1/2	2412-005G 19.84	2422-005G 21.99	2432-005G 24.46	10	120	240
-----	--------------------	--------------------	--------------------	----	-----	-----

### PVC Gray (continued)

Size	Buna-N	EPDM	Viton®	Std Pk	Mstr Pk	Disc Code
<b>Socket Ends</b>						
3/4	2412-007G 24.99	2422-007G 27.80	2432-007G 30.87	10	80	240
1	2412-010G 29.40	2422-010G 32.63	2432-010G 36.27	10	0	240
1-1/4	2412-012G 40.83	2422-012G 45.39	2432-012G 50.37	5	0	240
1-1/2	2412-015G 51.46	2422-015G 60.21	2432-015G 66.96	5	0	240
2	2412-020G 59.52	2422-020G 66.14	2432-020G 73.45	5	0	240
3	2412-030G 207.45	2422-030G 257.29	2432-030G 296.69	1	0	240
4	2412-040G 438.45	2422-040G 483.10	2432-040G 525.12	1	0	240

# Schedule 80 PVC Industrial Products & Accessories Single Entry Ball Valves & Compact 2000 Ball Valves



## Single Entry Ball Valves

Pressure Rating @ 73°F (23°C), Water  
 1/2" - 2" 235 psi  
 3" - 4" 150 psi  
 Maximum Service Temperature  
 PVC = 140°F (60°C)  
 Temperature/Pressure De-ratings Apply  
 Rated for Vacuum Service

All Valves Assembled with Silicone-Free, Water Soluble Lubricant. See Ball Valve Accessories & Repair Kits Section for Additional Options and Features



PVC Gray – Socket/Threaded Style

### PVC Gray

Size	Buna-N	EPDM	Viton®	Std Pk	Mstr Pk	Disc Code
<b>Threaded Ends</b>						
1/2	2411-005G 19.84	2421-005G 21.99	2431-005G 24.46	10	120	240
3/4	2411-007G 24.99	2421-007G 27.80	2431-007G 30.87	10	80	240
1	2411-010G 29.40	2421-010G 32.63	2431-010G 36.27	10	0	240
1-1/4	2411-012G 40.83	2421-012G 45.39	2431-012G 50.37	6	0	240
1-1/2	2411-015G 51.40	2421-015G 60.21	2431-015G 66.96	5	0	240
2	2411-020G 59.52	2421-020G 66.14	2431-020G 73.45	5	0	240
3	2411-030G 207.45	2421-030G 257.29	2431-030G 296.69	1	0	240
4	2411-040G 438.45	2421-040G 483.10	2431-040G 525.12	1	0	240

### PVC Gray

Size	Buna-N	EPDM	Viton®	Std Pk	Mstr Pk	Disc Code
<b>Socket Ends</b>						
1/2	2412-005G 19.84	2422-005G 21.99	2432-005G 24.46	10	120	240
3/4	2412-007G 24.99	2422-007G 27.80	2432-007G 30.87	10	80	240
1	2412-010G 29.40	2422-010G 32.63	2432-010G 36.27	10	0	240
1-1/4	2412-012G 40.83	2422-012G 45.39	2432-012G 50.37	5	0	240
1-1/2	2412-015G 51.46	2422-015G 60.21	2432-015G 66.96	5	0	240
2	2412-020G 59.52	2422-020G 66.14	2432-020G 73.45	5	0	240
3	2412-030G 207.45	2422-030G 257.29	2432-030G 296.69	1	0	240
4	2412-040G 438.45	2422-040G 483.10	2432-040G 525.12	1	0	240

## Compact 2000 Ball Valves



Pressure Rating @ 73°F (23°C), Water  
 1/2" - 2" 235 psi  
 Maximum Service Temperature  
 PVC = 140°F (60°C)  
 Temperature/Pressure De-ratings Apply

All Valves Assembled with Silicone-Free, Water Soluble Lubricants.  
 Rated for Vacuum Service  
 Compact 2000 Ball Valves are a Maintenance-Free, Sealed Unit (non-repairable).  
 See Ball Valve Accessories & Repair Kits Section for Additional Options and Features.

### PVC 2000 Compact Ball Valve

Size	EPDM	Viton®	Std Pk	Mstr Pk	Disc Code
<b>Socket Ends</b>					
1/2	6622-005 20.11	6632-005 22.64	10	120	210
3/4	6622-007 27.44	6632-007 28.09	10	80	210
1	6622-010 29.95	6632-010 33.59	10	0	210
1-1/4	6622-012 45.06	6632-012 52.07	6	0	210
1-1/2	6622-015 53.67	6632-015 59.69	5	0	210
2	6622-020 71.65	6632-020 80.50	8	0	210
<b>Threaded Ends</b>					
1/2	6621-005 20.11	6631-005 22.64	10	120	210

### PVC 2000 Compact Ball Valve (continued)

Size	EPDM	Viton®	Std Pk	Mstr Pk	Disc Code
<b>Threaded Ends</b>					
3/4	6621-007 27.44	6631-007 28.09	10	80	210
1	6621-010 29.95	6631-010 33.59	10	0	210
1-1/4	6621-012 49.32	6631-012 52.07	6	0	210
1-1/2	6621-015 53.67	6631-015 59.69	5	0	210
2	6621-020 71.65	6631-020 80.50	8	0	210
<b>Flanged Ends</b>					
1/2	6623-005 42.35	6633-005 44.50	10	120	210
3/4	6623-007 47.83	6633-007 49.50	10	120	210

Made in the U.S.A.

NOT FOR DISTRIBUTION OF COMPRESSED AIR OR GAS  
 Progressive Products from Spears® Innovation and Technology

Page 221