

Thermoplastic Valves Single Entry Ball Valves



PVC White – Socket/Threaded Style

Pressure Rating @ 73°F (23°C), Water
 1/2" - 2" 235 psi
 3" - 4" 150 psi
 Maximum Service Temperature
 PVC = 140°F (60°C)
 Temperature/Pressure Deratings Apply
 Rated for Vacuum Service

All Valves Assembled with Silicone-Free, Water Soluble Lubricant. See
 Ball Valve Accessories & Repair Kits Section for Additional Options and
 Features



PVC Gray – Socket/Threaded Style

PVC White

Size	Buna-N	EPDM	Viton®	Std Pk	Mstr Pk	Disc Code
Threaded Ends						
1/2	2411-005W 18.07	2421-005W 20.04	2431-005W 22.29	10	120	240
3/4	2411-007W 24.46	2421-007W 25.22	2431-007W 28.03	10	80	240
1	2411-010W 26.70	2421-010W 29.66	2431-010W 32.98	10	0	240
1-1/4	2411-012W 37.13	2421-012W 41.29	2431-012W 45.87	6	0	240
1-1/2	2411-015W 48.13	2421-015W 55.88	2431-015W 60.59	5	0	240
2	2411-020W 54.18	2421-020W 60.14	2431-020W 66.85	5	0	240
3	2411-030W 197.05	2421-030W 244.45	2431-030W 281.85	1	0	240
4	2411-040W 416.55	2421-040W 458.93	2431-040W 498.88	1	0	240

Socket Ends

1/2	2412-005W 18.07	2422-005W 20.04	2432-005W 22.29	10	120	240
3/4	2412-007W 24.46	2422-007W 25.22	2432-007W 28.03	10	80	240
1	2412-010W 26.70	2422-010W 29.66	2432-010W 32.98	10	0	240
1-1/4	2412-012W 37.13	2422-012W 41.29	2432-012W 45.87	6	0	240
1-1/2	2412-015W 48.13	2422-015W 55.88	2432-015W 60.60	5	0	240
2	2412-020W 54.18	2422-020W 60.14	2432-020W 66.85	5	0	240
3	2412-030W 197.05	2422-030W 244.45	2432-030W 281.85	1	0	240
4	2412-040W 416.55	2422-040W 458.93	2432-040W 498.88	1	0	240

PVC Gray

Size	Buna-N	EPDM	Viton®	Std Pk	Mstr Pk	Disc Code
Threaded Ends						
1/2	2411-005G 19.84	2421-005G 21.99	2431-005G 24.46	10	120	240
3/4	2411-007G 24.99	2421-007G 27.80	2431-007G 30.87	10	80	240
1	2411-010G 29.40	2421-010G 32.63	2431-010G 36.27	10	0	240
1-1/4	2411-012G 40.83	2421-012G 45.39	2431-012G 50.37	6	0	240
1-1/2	2411-015G 51.40	2421-015G 60.21	2431-015G 66.96	5	0	240
2	2411-020G 59.52	2421-020G 66.14	2431-020G 73.45	5	0	240
3	2411-030G 207.45	2421-030G 257.29	2431-030G 296.69	1	0	240
4	2411-040G 438.45	2421-040G 483.10	2431-040G 525.12	1	0	240

Socket Ends

1/2	2412-005G 19.84	2422-005G 21.99	2432-005G 24.46	10	120	240
-----	--------------------	--------------------	--------------------	----	-----	-----

PVC Gray (continued)

Size	Buna-N	EPDM	Viton®	Std Pk	Mstr Pk	Disc Code
Socket Ends						
3/4	2412-007G 24.99	2422-007G 27.80	2432-007G 30.87	10	80	240
1	2412-010G 29.40	2422-010G 32.63	2432-010G 36.27	10	0	240
1-1/4	2412-012G 40.83	2422-012G 45.39	2432-012G 50.37	5	0	240
1-1/2	2412-015G 51.46	2422-015G 60.21	2432-015G 66.96	5	0	240
2	2412-020G 59.52	2422-020G 66.14	2432-020G 73.45	5	0	240
3	2412-030G 207.45	2422-030G 257.29	2432-030G 296.69	1	0	240
4	2412-040G 438.45	2422-040G 483.10	2432-040G 525.12	1	0	240



Schedule 40 Fittings & Accessories Single Entry Ball Valves



PVC White – Socket/Threaded Style

Pressure Rating @ 73°F (23°C), Water
 1/2" - 2" 235 psi
 3" - 4" 150 psi
 Maximum Service Temperature
 PVC = 140°F (60°C)
 Temperature/Pressure De-ratings Apply
 Rated for Vacuum Service

All Valves Assembled with Silicone-Free, Water Soluble Lubricant.
 See Ball Valve Accessories & Repair Kits Section for Additional Options and Features

PVC White

Size	Buna-N	EPDM	Viton®	Std Pk	Mstr Pk	Disc Code
------	--------	------	--------	--------	---------	-----------

Threaded Ends

1/2	2411-005W 18.07	2421-005W 20.04	2431-005W 22.29	10	120	240
3/4	2411-007W 24.46	2421-007W 25.22	2431-007W 28.03	10	80	240
1	2411-010W 26.70	2421-010W 29.66	2431-010W 32.98	10	0	240
1-1/4	2411-012W 37.13	2421-012W 41.29	2431-012W 45.87	6	0	240
1-1/2	2411-015W 48.13	2421-015W 55.88	2431-015W 60.59	5	0	240
2	2411-020W 54.18	2421-020W 60.14	2431-020W 66.85	5	0	240
3	2411-030W 197.05	2421-030W 244.45	2431-030W 281.85	1	0	240
4	2411-040W 416.55	2421-040W 458.93	2431-040W 498.88	1	0	240

Socket Ends

1/2	2412-005W 18.07	2422-005W 20.04	2432-005W 22.29	10	120	240
3/4	2412-007W 24.46	2422-007W 25.22	2432-007W 28.03	10	80	240
1	2412-010W 26.70	2422-010W 29.66	2432-010W 32.98	10	0	240
1-1/4	2412-012W 37.13	2422-012W 41.29	2432-012W 45.87	6	0	240
1-1/2	2412-015W 48.13	2422-015W 55.88	2432-015W 60.60	5	0	240
2	2412-020W 54.18	2422-020W 60.14	2432-020W 66.85	5	0	240
3	2412-030W 197.05	2422-030W 244.45	2432-030W 281.85	1	0	240
4	2412-040W 416.55	2422-040W 458.93	2432-040W 498.88	1	0	240