

**Schedule 40 Fittings & Accessories
CWV Ball Valves & Utility Ball Valves**



CWV Ball Valves



**A Combination of Economy & Quality - Made in the U.S.A.
For Greater Value in a General Purpose Cold Water Valve**

Pressure Rating @ 73°F (23°C), Water = 125 psi

You don't have to go overseas to find an economical general purpose ball valve! Spears® CWV BALL VALVES are produced in the U.S.A. with Spears® high quality construction and NSF® Certified for potable water service. Designed for use with cold water, these PVC valves may be suitable for some applications previously handled by Spears® Utility Valves. Available in IPS sizes 1/2" through 2" with a Full 1-Year Warranty.

CWV PVC Ball Valve

Part Number	Size	Std Pk	Mstr Ctn	Disc Code	Price Each
-------------	------	--------	----------	-----------	------------

Socket Ends

8722-005	1/2	50	0	204	8.01
8722-007	3/4	25	0	204	9.50
8722-010	1	25	0	204	12.92
8722-012	1-1/4	20	0	204	17.13
8722-015	1-1/2	20	0	204	26.14
8722-020	2	10	0	204	33.04

CWV PVC Ball Valve

Part Number	Size	Std Pk	Mstr Ctn	Disc Code	Price Each
-------------	------	--------	----------	-----------	------------

Threaded Ends

8721-005	1/2	50	0	204	9.89
8721-007	3/4	25	0	204	11.73
8721-010	1	25	0	204	15.96
8721-012	1-1/4	20	0	204	21.14
8721-015	1-1/2	20	0	204	32.27
8721-020	2	10	0	204	40.79

Utility Ball Valves



Pressure Rating @ 73°F (23°C), Water
1/2" - 6" 150 psi
Maximum Service Temperature
PVC = 140°F (60°C)
Temperature/Pressure De-ratings Apply

All Valves Assembled with Silicone-Free,
Water Soluble Lubricant

PVC w/EPDM O-ring Seal

Size	Threaded Ends	Socket Ends	Std Pk	Mstr Pk	Disc Code
------	---------------	-------------	--------	---------	-----------

PVC White

1/2	2621-005 8.90	2622-005 8.90	50	0	215
3/4	2621-007 10.56	2622-007 10.56	25	0	215
1	2621-010 14.36	2622-010 14.36	25	0	215
1-1/4	2621-012 19.03	2622-012 19.03	20	0	215
1-1/2	2621-015 29.04	2622-015 29.04	20	0	215
2	2621-020 36.71	2622-020 36.71	8	0	215
2-1/2	2621-025 62.83	2622-025 62.83	6	0	214
3	2621-030 112.69	2622-030 112.69	1	4	214
4	2621-040 206.54	2622-040 206.54	1	0	214
6 (Lever Handle)	---	2622-060 333.22	1	0	214

PVC Gray

1/2	2621-005G 8.90	2622-005G 8.90	50	0	215
-----	-------------------	-------------------	----	---	-----

PVC w/EPDM O-ring Seal (continued)

Size	Threaded Ends	Socket Ends	Std Pk	Mstr Pk	Disc Code
------	---------------	-------------	--------	---------	-----------

PVC Gray

3/4	2621-007G 10.56	2622-007G 10.56	25	0	215
1	2621-010G 14.36	2622-010G 14.36	25	0	215
1-1/4	2621-012G 19.03	2622-012G 19.03	20	0	215
1-1/2	2621-015G 29.04	2622-015G 29.04	20	0	215
2	2621-020G 36.71	2622-020G 36.71	8	0	215
2-1/2	2621-025G 62.83	2622-025G 62.83	6	0	214
3	2621-030G 112.69	2622-030G 112.69	1	4	214
4	2621-040G 206.54	2622-040G 206.54	1	0	214

Made in the U.S.A.

**NOT FOR DISTRIBUTION OF COMPRESSED AIR OR GAS
Progressive Products from Spears® Innovation and Technology**