



**Schedule 80 CPVC Industrial Products & Accessories
Utility Ball Valves & Lab Ball Valves**

Utility Ball Valves



Pressure Rating @ 73°F (23°C), Water
1/2" - 2" 150 psi
Maximum Service Temperature
CPVC = 200°F (93°C)
Temperature/Pressure De-ratings Apply

All Valves Assembled with Silicone-Free,
Water Soluble Lubricant

See Ball Valve Accessories & Repair Kits
Section for Additional Options and Features

CPVC w/EPDM O-ring Seal

Size	Threaded Ends	Socket Ends	Std Pk	Mstr Pk	Disc Code
CPVC					
1/2	2621-005C 11.73	2622-005C 11.73	50	0	216
3/4	2621-007C 14.91	2622-007C 14.91	25	0	216
1	2621-010C 16.20	2622-010C 16.20	25	0	216

CPVC w/EPDM O-ring Seal (continued)

Size	Threaded Ends	Socket Ends	Std Pk	Mstr Pk	Disc Code
CPVC					
1-1/4	2621-012C 22.83	2622-012C 22.83	20	0	216
1-1/2	2621-015C 35.40	2622-015C 35.40	20	0	216
2	2621-020C 44.03	2622-020C 44.03	8	0	216

Lab Ball Valves



Socket/Threaded Valve Only

Pressure Rating @ 73°F (23°C),
Water
1/4" - 3/8" 150 psi
Maximum Service Temperature
CPVC = 200°F (93°C)
Temperature/Pressure De-ratings
Apply
Rated for Vacuum Service

Valve & Adapters includes:

- 1 - Threaded 1/4" Valve
- 2 - O-ring Sealed 1/4" MPT x Mipt Adapters
- 2 - EPDM or Viton® O-rings (AS568-013 size)
- 1 - End Connector Wrench
- 2 - O-ring Sealed 1/4" MPT x 3/8" I.D. Tubing Barb Adapters
- OR -
- 2 - O-ring Sealed 1/4" MPT x 1/4" I.D. Tubing Barb Adapters



Valve & Adapters

All Valves Assembled with Silicone-Free, Water Soluble Lubricant

CPVC

Size	EPDM	Viton®	Std Pk	Mstr Pk	Disc Code
------	------	--------	--------	---------	-----------

Valve & Adapters Threaded Ends

1/4X3/8T	1529-002C 29.36	1539-002C 29.93	1	25	219
1/4X1/4T	1529-002CA 29.36	1539-002CA 29.93	1	25	219

Valve only Threaded Ends

1/4	1521-002C 23.51	1531-002C 25.85	50	200	219
3/8	1521-003C 32.97	1531-003C 30.90	50	200	219

Valve only Socket Ends

1/4	1522-002C 23.51	1532-002C 27.98	50	200	219
3/8	1522-003C 32.97	1532-003C 36.60	50	200	219

Thermoplastic Valves Utility Ball Valves



Pressure Rating @ 73°F (23°C), Water
1/2" - 6" 150 psi
Maximum Service Temperature
PVC = 140°F (60°C)
CPVC = 200°F (93°C)
Temperature/Pressure De-ratings Apply

All Valves Assembled with Silicone-Free,
Water Soluble Lubricant

Note: Standard 6" Valve uses Lever-Style Handle for proper leverage.

PVC w/EPDM O-ring Seal

Size	Threaded Ends	Socket Ends	Std Pk	Mstr Pk	Disc Code
PVC White					
1/2	2621-005 8.90	2622-005 8.90	50	0	215
3/4	2621-007 10.56	2622-007 10.56	25	0	215
1	2621-010 14.36	2622-010 14.36	25	0	215
1-1/4	2621-012 19.03	2622-012 19.03	20	0	215
1-1/2	2621-015 29.04	2622-015 29.04	20	0	215
2	2621-020 36.71	2622-020 36.71	8	0	215
2-1/2	2621-025 62.83	2622-025 62.83	6	0	214
3	2621-030 112.69	2622-030 112.69	1	4	214
4	2621-040 206.54	2622-040 206.54	1	0	214
6 (Lever Handle)	---	2622-060 333.22	1	0	214

PVC Gray

1/2	2621-005G 8.90	2622-005G 8.90	50	0	215
3/4	2621-007G 10.56	2622-007G 10.56	25	0	215
1	2621-010G 14.36	2622-010G 14.36	25	0	215
1-1/4	2621-012G 19.03	2622-012G 19.03	20	0	215
1-1/2	2621-015G 29.04	2622-015G 29.04	20	0	215
2	2621-020G 36.71	2622-020G 36.71	8	0	215
2-1/2	2621-025G 62.83	2622-025G 62.83	6	0	214
3	2621-030G 112.69	2622-030G 112.69	1	4	214
4	2621-040G 206.54	2622-040G 206.54	1	0	214

CPVC w/EPDM O-ring Seal

Size	Threaded Ends	Socket Ends	Std Pk	Mstr Pk	Disc Code
CPVC					
1/2	2621-005C 11.73	2622-005C 11.73	50	0	216
3/4	2621-007C 14.91	2622-007C 14.91	25	0	216
1	2621-010C 16.20	2622-010C 16.20	25	0	216
1-1/4	2621-012C 22.83	2622-012C 22.83	20	0	216
1-1/2	2621-015C 35.40	2622-015C 35.40	20	0	216
2	2621-020C 44.03	2622-020C 44.03	8	0	216