

**CTS CPVC Hot & Cold Water Distribution System
EverTUFF® CPVC CTS Fittings, Valves & Pipe**



Part Number	Size	Std Pk	Mstr Ctn	Disc Code	Price Each
-------------	------	--------	----------	-----------	------------

REDUCING TEE (continued)

Socket x Socket x Socket

4101-248*	2X2X3/4	5	40	035	49.75
4101-249	2X1	5	15	035	47.14
4101-250*	2X2X1-1/4	5	0	035	47.14
4101-251	2X2X1-1/2	5	15	035	50.30
4101-257*	2X1-1/2X2	5	0	035	50.30

* Outlet sized with bushing.

90° ELL

Socket x Socket



4106-005	1/2	25	600	035	1.15
4106-007	3/4	25	300	035	1.90
4106-010	1	10	150	035	5.55
4106-012	1-1/4	10	80	035	11.05
4106-015	1-1/2	10	80	035	19.94
4106-020	2	5	30	035	38.24

REDUCING 90° ELL

Socket x Socket



4106-101	3/4X1/2	25	300	035	4.00
4106-130*	1X1/2	25	200	035	14.07
4106-131*	1X3/4	25	200	035	14.07
4106-167*	1-1/4X3/4	10	80	035	21.66
4106-168*	1-1/4X1	10	80	035	21.66
4106-209*	1-1/2X1/2	10	0	035	30.00
4106-210*	1-1/2X3/4	10	0	035	30.00
4106-211*	1-1/2X1	10	0	035	30.00
4106-212*	1-1/2X1-1/4	10	0	035	30.00
4106-247*	2X1/2	5	30	035	66.65
4106-248*	2X3/4	5	30	035	66.65
4106-249*	2X1	5	30	035	66.65
4106-250*	2X1-1/4	5	30	035	66.65
4106-251*	2X1-1/2	5	30	035	66.65

* Outlet sized with bushing.

SPECIAL REINFORCED 90° ELL

Socket x SR Fipt - Stainless Steel Collar



4107-005SR	1/2	50	300	035	8.56
------------	-----	----	-----	-----	------

**ZINC DROP EAR REINFORCED CTS 90° ELL
(One Piece Unit)**

Socket x SR Fipt - Zinc Collar



DEZ4107-005SR	1/2	10	150	035	19.25
---------------	-----	----	-----	-----	-------

DROP EAR 90° ELL (Fitting with Bracket)

Socket x Socket



DE4106-005	1/2	25	150	035	3.44
------------	-----	----	-----	-----	------

DROP EAR BRACKET ONLY

For 4101-005 and 4106-005



DES-005	1/2	800	0	035	5.86
---------	-----	-----	---	-----	------

**DROP EAR SPECIAL REINFORCED 90° ELL
(Fitting Plus Bracket)**

Socket x SR Fipt - Stainless Steel Collar



DE4107-005SR	1/2	10	200	035	13.23
--------------	-----	----	-----	-----	-------

Part Number	Size	Std Pk	Mstr Ctn	Disc Code	Price Each
-------------	------	--------	----------	-----------	------------

DROP EAR BRACKET ONLY

For 4107-005SR



DET-005	1/2	400	0	035	5.86
---------	-----	-----	---	-----	------

90° STREET ELL

Spigot x Socket



4109-005	1/2	25	500	035	1.36
4109-007	3/4	25	300	035	2.13
4109-010	1	10	100	035	9.74

45° ELL

Socket x Socket



4117-005	1/2	25	500	035	1.46
4117-007	3/4	25	300	035	2.53
4117-010	1	10	100	035	6.43
4117-012	1-1/4	10	120	035	13.62
4117-015	1-1/2	10	80	035	19.74
4117-020	2	10	0	035	41.33

45° STREET ELL

Spigot x Socket



4127-005	1/2	25	600	035	3.10
4127-007	3/4	25	400	035	4.15
4127-010	1	10	150	035	11.93

COUPLING

Socket x Socket



4129-005	1/2	25	600	035	.95
4129-007	3/4	25	300	035	1.25
4129-010	1	10	250	035	5.64
4129-012	1-1/4	10	120	035	7.29
4129-015	1-1/2	10	120	035	10.30
4129-020	2	10	0	035	19.61

REDUCER COUPLING

Socket x Socket



4129-101	3/4X1/2	25	300	035	2.01
4129-130	1X1/2	25	150	035	11.89
4129-131	1X3/4	25	150	035	6.44
4129-166*	1-1/4X1/2	10	120	035	14.91
4129-167*	1-1/4X3/4	10	120	035	14.91
4129-168*	1-1/4X1	10	120	035	21.21
4129-209*	1-1/2X1/2	10	80	035	20.22
4129-210*	1-1/2X3/4	10	80	035	20.22
4129-211*	1-1/2X1	10	80	035	20.22
4129-212*	1-1/2X1-1/4	10	80	035	20.22
4129-247*	2X1/2	10	0	035	43.79
4129-248*	2X3/4	10	0	035	43.79
4129-249*	2X1	10	0	035	43.79
4129-250*	2X1-1/4	10	0	035	43.79
4129-251*	2X1-1/2	10	0	035	43.79

* Outlet sized with bushing.

FEMALE ADAPTER with Gasket

Socket x NPSC



For Cold Water Service Only

4135-005OR	1/2	25	200	035	4.47
4135-007OR	3/4	25	300	035	6.35