



**CTS CPVC Hot & Cold Water Distribution System
EverTUFF® CPVC CTS Fittings, Valves & Pipe**

Part Number	Size	Std Pk	Mstr Ctn	Disc Code	Price Each
-------------	------	--------	----------	-----------	------------

FEMALE ADAPTER with Gasket (continued)

Socket x NPSC

4135-010OR	1	5	100	035	7.24
------------	---	---	-----	-----	------

GASKET SEALED BRASS THREAD

TRANSITION FEMALE ADAPTER

Socket x Gasket FPT - Use NO Thread Sealant



NSF Certified Lead Free

4135-005BRG	1/2	25	150	035	38.20
4135-007BRG	3/4	25	150	035	42.07
4135-010BRG	1	15	90	035	125.49
4135-012BRG	1-1/4	15	60	035	238.42
4135-015BRG	1-1/2	10	40	035	310.76
4135-020BRG	2	8	32	035	456.90

GASKET SEALED BRASS THREAD

TRANSITION REDUCING FEMALE ADAPTER

Socket x Gasket FPT - Use NO Thread Sealant



NSF Certified Lead Free

4135-101BRG	3/4X1/2	25	150	035	41.58
4135-130BRG	1X1/2	50	0	035	65.69

SPECIAL REINFORCED FEMALE ADAPTER

Socket x SR Fipt - Stainless Steel Collar



4135-005SR	1/2	25	200	035	6.61
4135-007SR	3/4	25	300	035	7.27
4135-010SR	1	5	100	035	9.22

SPECIAL REINFORCED REDUCING FEMALE ADAPTER

Socket x SR Fipt - Stainless Steel Collar



4135-131SR	1X3/4	25	150	035	14.52
------------	-------	----	-----	-----	-------

MALE ADAPTER

Mipt x Socket



For Cold Water Service Only

4136-005	1/2	25	600	035	1.20
4136-007	3/4	25	300	035	2.04
4136-010	1	10	250	035	9.65
4136-012	1-1/4	25	200	035	14.95
4136-015	1-1/2	10	80	035	18.44
4136-020	2	10	80	035	30.40

REDUCING MALE ADAPTER

Mipt x Socket



For Cold Water Service Only

4136-074	1/2X3/4	25	600	035	4.37
4136-101	3/4X1/2	25	600	035	4.68

MALE ADAPTER

Mipt x Spigot



For Cold Water Service Only

4161-005	1/2	50	700	035	3.71
----------	-----	----	-----	-----	------

REINFORCED MALE ADAPTER (Internal Stainless Steel Reinforced)

R Mipt x Socket - Stainless Steel Sleeve



4136-005R	1/2	25	300	035	8.48
4136-007R	3/4	25	300	035	9.43
4136-010R	1	10	120	035	14.05

Part Number	Size	Std Pk	Mstr Ctn	Disc Code	Price Each
-------------	------	--------	----------	-----------	------------

TRANSITION MALE ADAPTER w/BRASS THREAD

Brass Mipt x Socket




NSF Certified Lead Free

4136-005BR	1/2	60	360	035	38.20
4136-007BR	3/4	40	160	035	42.07
4136-010BR	1	10	60	035	125.49
4136-012BR	1-1/4	10	60	035	154.77
4136-015BR	1-1/2	10	40	035	204.31
4136-020BR	2	8	32	035	339.62

REDUCER BUSHING


Spigot x Socket



4137-101	3/4X1/2	25	600	035	1.43
4137-130	1X1/2	10	300	035	4.70
4137-131	1X3/4	10	400	035	4.70
4137-166	1-1/4X1/2	10	120	035	6.52
4137-167	1-1/4X3/4	10	300	035	6.10
4137-168	1-1/4X1	10	300	035	5.33
4137-209	1-1/2X1/2	25	100	035	7.67
4137-210	1-1/2X3/4	25	100	035	7.67
4137-211	1-1/2X1	10	120	035	7.52
4137-212	1-1/2X1-1/4	10	200	035	7.52
4137-247	2X1/2	10	60	035	18.20
4137-248	2X3/4	10	60	035	16.99
4137-249	2X1	10	60	035	16.99
4137-250	2X1-1/4	10	120	035	18.20
4137-251	2X1-1/2	10	120	035	16.99

TRANSITION BUSHING


IPS Spigot x CTS Socket



4140-005	1/2	10	600	035	6.08
4140-007	3/4	10	600	035	6.35
4140-010	1	10	400	035	7.01
4140-012	1-1/4	10	60	035	8.68
4140-015	1-1/2	10	60	035	10.94
4140-020	2	10	60	035	11.93

TRANSITION COUPLING

IPS Socket x CTS Socket



4141-007	3/4	25	300	035	4.14
4141-010	1	10	150	035	7.31

CAP


Socket



4147-005	1/2	25	600	035	1.04
4147-007	3/4	25	300	035	1.32
4147-010	1	10	400	035	4.82
4147-012	1-1/4	10	120	035	6.62
4147-015	1-1/2	10	120	035	10.18
4147-020	2	10	80	035	20.55

CTS Union

Socket with EPDM O-ring Seal



100 psi Maximum Internal Pressure @ 180°F (82°C)

4197-005	1/2	25	150	035	13.54
4197-007	3/4	10	60	035	20.61
4197-010	1	10	60	035	26.60