

## Schedule 40 Fittings & Accessories PVC Clear Sch 40 Pipe & Fittings



Part Number	Size	Std Pk	Mstr Ctn	Disc Code	Price Each
-------------	------	--------	----------	-----------	------------

### Coupling (continued)

#### Soc

429-003L	3/8	50	300	039	5.86
429-005L	1/2	50	300	039	4.36
429-007L	3/4	50	200	039	5.87
429-010L	1	50	0	039	10.20
429-012L	1-1/4	25	150	039	13.89
429-015L	1-1/2	25	0	039	14.95
429-020L	2	10	60	039	23.30
429-025L	2-1/2	10	0	039	51.06
429-030L	3	10	0	039	80.11
429-040L	4	6	0	039	115.65
429-060L	6	5	0	039	208.19
429-080L	8	6	0	039	374.72

### Female Adapter

#### Soc x SR Fipt



435-002SRL	1/4	25	450	039	12.30
435-003SRL	3/8	25	300	039	12.30
435-005SRL	1/2	25	300	039	7.29
435-007SRL	3/4	25	300	039	9.12
435-010SRL	1	25	200	039	10.54
435-012SRL	1-1/4	10	80	039	16.19
435-015SRL	1-1/2	10	80	039	18.99
435-020SRL	2	10	0	039	25.57
435-025SRL	2-1/2	5	0	039	53.15
435-030SRL	3	10	0	039	86.76
435-040SRL	4	6	0	039	143.51

### Male Adapter

#### Mipt x Soc



436-003L	3/8	50	300	039	7.87
436-005L	1/2	50	300	039	5.87
436-007L	3/4	50	400	039	6.59
436-010L	1	50	300	039	11.57
436-012L	1-1/4	25	0	039	13.97
436-015L	1-1/2	25	0	039	18.97
436-020L	2	25	0	039	24.74
436-025L	2-1/2	10	0	039	73.38
436-030L	3	10	0	039	107.20
436-040L	4	5	0	039	136.71

### Reducer Bushing

#### Spig x Soc



437-101L	3/4X1/2	50	300	039	6.78
437-131L	1X3/4	50	200	039	12.47
437-168L	1-1/4X1	25	150	039	16.43
437-211L	1-1/2X1	25	100	039	17.35
437-212L	1-1/2X1-1/4	25	100	039	17.35
437-251L	2X1-1/2	10	80	039	28.73
437-292L	2-1/2X2	10	40	039	46.21
437-338L	3X2	10	0	039	68.56
437-339L	3X2-1/2	10	0	039	68.56
437-422L	4X3	6	0	039	153.19
437-532L	6X4	5	0	039	308.28
437-585L	8X6	4	0	039	496.35

### Cap

#### Soc



447-002L	1/4	25	150	039	7.87
447-003L	3/8	50	300	039	7.87
447-005L	1/2	50	300	039	5.87

Part Number	Size	Std Pk	Mstr Ctn	Disc Code	Price Each
-------------	------	--------	----------	-----------	------------

### Cap (continued)

#### Soc

447-007L	3/4	50	300	039	6.78
447-010L	1	50	200	039	10.74
447-012L	1-1/4	25	100	039	14.95
447-015L	1-1/2	25	0	039	16.43
447-020L	2	10	80	039	19.80
447-025L	2-1/2	10	0	039	63.35
447-030L	3	10	0	039	62.37
447-040L	4	6	0	039	141.84
447-060L	6	4	0	039	255.32
447-080L	8	3	0	039	459.56

### Wyes & Reducing Wyes

#### Soc



1/2" - 2" - 235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

2-1/2" - 6" - 150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

475-015L	1-1/2	20	0	039	43.39
475-020L	2	10	0	039	63.87
475-030L	3	4	0	039	266.03
475-040L	4	4	0	039	484.36
475-060L	6	3	0	039	828.04
475-532L	6X4	5	0	039	828.04