



Schedule 40 Fittings & Accessories
Pool & Spa Fittings & True Union 2000 Standard Ball Valve - PVC White

Pool & Spa Fittings

Part Number	Size	Std Pk	Mstr Ctn	Disc Code	Price Each
-------------	------	--------	----------	-----------	------------

Multi Configuration Venturied Tee - Socket Style Sch 40



1" Socket x 3/4" Socket (1" Spigot) x 3/4" Socket (1" Spigot)

Special spa jet fitting with standard 7/16" nozzle plus optional 3/8" or 1/4".

473-825	with 7/16" Nozzle	50	0	015	6.07
473-825-3/8	with 3/8" Nozzle	50	0	015	6.07
473-825-1/4	with 1/4" Nozzle	50	0	015	6.07

Multi Configuration Venturied Tee - Socket Style Sch 40



Individual Nozzles Only

Special spa jet fitting with standard 7/16" nozzle plus optional 3/8" or 1/4".

473-1	7/16" Nozzle	100	600	015	1.96
473-2	1/4" Nozzle	100	600	015	1.96
473-3	3/8" Nozzle	100	600	015	1.96

Part Number	Size	Std Pk	Mstr Ctn	Disc Code	Price Each
-------------	------	--------	----------	-----------	------------

Smooth Barb Adapter



1/2" Smooth Barb x 3/4" Spigot

Special adapter for making connections to 1/2" Vinyl Hose

432-007525	3/4X1/2	100	600	015	1.77
------------	---------	-----	-----	-----	------

Nesting Union



2" Socket x 1-1/2" Socket (2" Spigot) Buna-N O-ring

235 psi @ 73°F (23°C)

8057-251W	2X1-1/2 (2)	5	0	080	58.89
-----------	-------------	---	---	-----	-------

Nesting Union



2" Socket x 1-1/2" Socket (2" Spigot) EPDM O-ring

235 psi @ 73°F (23°C)

8097-251W	2X1-1/2 (2)	5	0	080	69.30
-----------	-------------	---	---	-----	-------

True Union 2000 Standard Ball Valve - PVC White

Part Number	Size	Std Pk	Mstr Ctn	Disc Code	Price Each
-------------	------	--------	----------	-----------	------------

PVC White True Union 2000 Standard Ball Valve



Socket Ends - EPDM O-rings

Pressure Rating @73° F (23° C) = 235 psi

Maximum Service Pressure = 140° F (60° C)

Temperature/Pressure De-ratings Apply

3622-015W	1-1/2	1	8	608	88.68
3622-020W	2	1	8	608	117.02

Check with Spears® for additional size availability

PVC White True Union 2000 Standard Ball Valves



SR Threaded Ends - EPDM O-rings

Pressure Rating @73° F (23° C) = 235 psi

Maximum Service Pressure = 140° F (60° C)

Temperature/Pressure De-ratings Apply

3621-015WSR	1-1/2	1	8	608	94.98
3621-020WSR	2	1	8	608	123.83

Check with Spears® for additional size availability