

**Schedule 40 Fittings & Accessories
Pool & Spa Fittings**



All Pool & Spa Specialty Fittings have a maximum use service pressure of 150 psi @ 73° F (22° C). Standard pressure de-ratings must be applied for use at elevated temperatures with a maximum service temperature of 140° F (60° C).

Part Number	Size	Std Pk	Mstr Ctn	Disc Code	Price Each
-------------	------	--------	----------	-----------	------------

Short Socket Tees
Socket Style Sch 40



Special short-socket end allows close connection at pumps, filters and other areas with minimum available space.

S401-249	2X2X1	25	0	015	7.49
S401-251	2x2x1-1/2	25	0	015	7.49

2" Spigot Tee
Spigot x Spigot x Spigot Sch 40



404A-020	2	30	0	015	7.81
----------	----------	----	---	-----	------

Male Thread Tee (Branch)
Socket x Socket x Mipt



402B-010	1	50	0	040	3.29
----------	----------	----	---	-----	------

2"x1-1/2" Reducing 90° Ell, Socket Style Sch 40



2"x2" 90° Street Ell, Socket x Spigot Sch 40
Handy dual-purpose configuration is 2"x1-1/2" Socket Reducing 90° Ell and also a 2" Socket x 2" Spigot 90° Street Ell.

406-251N	2X1-1/2	10	0	015	9.40
----------	----------------	----	---	-----	------

1-1/2" 90° Spigot Elbow
Spigot x Spigot Sch 40



422-015	1-1/2	25	0	015	7.54
---------	--------------	----	---	-----	------

2-1/2"x2" Reducing 90° Ell, Socket Style Sch 40



2-1/2"x2-1/2" 90° Street Ell, Socket x Spigot Sch 40
Handy dual-purpose configuration is 2-1/2" x 2" Socket Reducing 90° Ell and also a 2-1/2" Socket x 2-1/2" Spigot 90° Street Ell.

406-292N	2-1/2X2 (2-1/2 Spigot)	10	0	040	11.01
----------	-------------------------------	----	---	-----	-------

2" Short Spigot 45° Street Ell
Spigot x Socket Sch 40



Special short-spigot end allows close connection in extra-tight spaces.

S427-020	2	10	0	015	6.66
----------	----------	----	---	-----	------

45° Street Ell
Spig x Soc



427-005	1/2	50	400	040	1.01
427-007	3/4	50	0	040	1.56
427-010	1	50	0	040	1.88
427-012	1-1/4	25	0	040	2.62
427-015	1-1/2	25	0	040	3.29
427-020	2	25	0	040	4.28
427-025	2-1/2	10	0	040	13.95
427-030	3	10	0	040	17.32
427-040	4	5	0	040	31.05
427-050	5	4	0	040	93.36
427-060	6	4	0	040	95.89
427-080	8	2	0	040	230.64
427-100	10	1	0	041	606.88

Part Number	Size	Std Pk	Mstr Ctn	Disc Code	Price Each
-------------	------	--------	----------	-----------	------------

45° Street Ell (continued)
Spig x Soc

427-120	12	1	0	041	889.74
427-140F	14	1	0	047	663.09
427-160F	16	1	0	047	901.29
427-180F	18	1	0	047	983.84
427-200F	20	1	0	047	1248.79
427-240F	24	1	0	047	1967.09

22-1/2" Street Ell
Spig x Soc



442-005	1/2	50	400	040	1.43
442-007	3/4	50	0	040	2.23
442-010	1	50	0	040	2.67
442-012	1-1/4	20	0	040	3.73
442-015	1-1/2	25	0	040	4.68
442-020	2	20	0	040	6.13
442-025F	2-1/2	1	18	047	34.70
442-030	3	5	0	040	35.80
442-040	4	4	0	040	55.24
442-060	6	4	0	040	136.38
442-060F	6	1	5	047	80.48
442-080	8	1	4	040	328.04
442-080F	8	1	4	047	121.22
442-100F	10	1	0	047	187.60
442-120F	12	1	0	047	281.59

2" Sch 40 Grated Coupling
Socket Style Sch 40



Specially designed internal grate at pipe stop gives extra protection to pumps, filters and equipment from damaging gravel and debris.

429GR-020	2	25	0	015	4.11
-----------	----------	----	---	-----	------

1-1/2"x1"x1" 120° Wye
Spigot x Socket x Socket Sch 40



Unique spigot end take off with 120° branched wye pattern for special distribution connections.

475-21131T	1-1/2X1X1	25	0	015	10.56
------------	------------------	----	---	-----	-------

2" 120° Wye
Socket



475-020120	2	10	0	015	12.41
------------	----------	----	---	-----	-------

Multi Configuration Venturied Tee - Socket Style Sch 40



1-1/2" Socket (2" Spigot) x 1-1/2" Socket x 3/4" Socket (1" Spigot)

Special spa jet fitting with standard 7/16" nozzle plus optional 3/8" or 1/4".

473-210	with 7/16" Nozzle	25	0	015	7.43
473-210-3/8	with 3/8" Nozzle	25	0	015	7.43
473-210-1/4	with 1/4" Nozzle	25	0	015	7.43