



**Transition Fittings & Adapters
PVC White Special Reinforced (SR) Fittings & PVC White Brass Thread Fittings**

PVC White Special Reinforced (SR) Fittings

Part Number	Size	Std Pk	Mstr Ctn	Disc Code	Price Each
-------------	------	--------	----------	-----------	------------

Special Reinforced Reducer Bushing Flush Style
(continued)

Spig x SR Fipt - Stainless Steel Collar

438-532SR	6X4	5	0	046	67.91
-----------	------------	---	---	-----	-------

Special Reinforced Reducer Bushing Flush Style

Mipt X SR Fipt - Stainless Steel Collar

439-209SR	1-1/2X1/2	25	200	046	8.30
439-249SR	2X1	10	120	046	12.19



Special Reinforced Cap

SR Fipt - Stainless Steel Collar

448-012SR	1-1/4	25	100	046	6.40
-----------	--------------	----	-----	-----	------



Special Reinforced Union

Soc x SR Fipt with Buna O-ring Seal - Stainless Steel Collar

235 psi @ 73°F (23°C)

459-002SR	1/4	25	150	046	14.55
459-003SR	3/8	25	100	046	14.55
459-005SR	1/2	10	60	046	7.90
459-007SR	3/4	10	40	046	10.88
459-010SR	1	10	40	046	14.48



Part Number	Size	Std Pk	Mstr Ctn	Disc Code	Price Each
-------------	------	--------	----------	-----------	------------

Special Reinforced Union (continued)

Soc x SR Fipt with Buna O-ring Seal - Stainless Steel Collar


459-012SR	1-1/4	5	20	046	27.64
459-015SR	1-1/2	5	0	046	34.21
459-020SR	2	5	0	046	52.69
459-030SR	3	5	0	046	124.40
459-040SR	4	4	0	046	142.83
459-060SR	6	1	0	046	317.40

Special Reinforced Union

Soc x SR Fipt with EPDM O-ring Seal - Stainless Steel Collar

235 psi @ 73°F (23°C)

499-002SR	1/4	25	150	046	15.98
499-003SR	3/8	25	100	046	15.98
499-005SR	1/2	10	60	046	8.68
499-007SR	3/4	10	40	046	11.96
499-010SR	1	10	40	046	15.89
499-012SR	1-1/4	5	20	046	30.37
499-015SR	1-1/2	5	0	046	37.60
499-020SR	2	5	0	046	57.90
499-030SR	3	5	0	046	136.71
499-040SR	4	4	0	046	156.95
499-060SR	6	1	0	046	348.80



PVC White Brass Thread Fittings

Part Number	Size	Std Pk	Mstr Ctn	Disc Code	Price Each
-------------	------	--------	----------	-----------	------------

Transition Union

Soc x Fipt with Brass Thread Insert & Buna-N O-ring Seal

235 psi @ 73°F (23°C)

459-010BR	1	10	0	046	61.50
459-012BR	1-1/4	5	20	046	103.32
459-015BR	1-1/2	5	0	046	136.70
459-020BR	2	5	0	046	182.34



Transition Union

Soc x Fipt with Brass Thread Insert & EPDM O-ring Seal

235 psi @ 73°F (23°C)

499-010BR	1	10	0	046	61.50
499-012BR	1-1/4	5	20	046	103.32
499-015BR	1-1/2	5	0	046	136.70
499-020BR	2	5	0	046	182.34



Not intended to convey or dispense water for human consumption through drinking or cooking