

High Purity PVC System Low-Extractable Piping For Ultra-Pure Water Systems



Part Number	Size	Std Pk	Mstr Ctn	Disc Code	Price Each
-------------	------	--------	----------	-----------	------------


Spears® True Union 2000 Industrial Ball Check Valves (continued)

Viton® O-rings

4532-030BL	3	1	0	066	842.69
4532-040BL	4	1	0	066	1563.68

Spears® Diaphragm Valves

EPDM O-ring Seals EPDM Backed PTFE Diaphragm




2729T-005BL	1/2	1	12	066	245.28
2729T-007BL	3/4	1	8	066	263.52
2729T-010BL	1	1	8	066	308.02
2729T-012BL	1-1/4	1	4	066	416.39
2729T-015BL	1-1/2	1	4	066	505.38
2729T-020BL	2	1	0	066	663.96

Note: Both socket and threaded end connectors are provided with valve sizes 1/2" -2" Diaphragm valves. Valves carry a maximum pressure rating of 150 psi for water, non-shock, @ 73°F (23°C).

Spears® Needle Valve

Globe Pattern - FIPT




5591-002BL	1/4	1	18	066	118.64
5591-003BL	3/8	1	18	066	118.64

Replaceable PTFE Stem Seal - no elastomer or lubricants used. Needle valves carry a maximum internal pressure rating of 235 psi at 73°F (23°C).

Spears® Needle Valve

Globe Pattern - Soc




5592-002BL	1/4	1	18	066	118.64
5592-003BL	3/8	1	18	066	118.64
5592-005BL	1/2	1	18	066	123.45

Replaceable PTFE Stem Seal - no elastomer or lubricants used. Needle valves carry a maximum internal pressure rating of 235 psi at 73°F (23°C).

Spears® Needle Valve

Globe Pattern - SR FIPT



5591-005BLSR	1/2	1	18	066	125.94
--------------	-----	---	----	-----	--------

Replaceable PTFE Stem Seal - no elastomer or lubricants used. Needle valves carry a maximum internal pressure rating of 235 psi at 73°F (23°C).

Spears® Needle Valve

Angle Pattern - FIPT



5691-002BL	1/4	1	18	066	118.64
5691-003BL	3/8	1	18	066	118.64

Replaceable PTFE Stem Seal - no elastomer or lubricants used. Needle valves carry a maximum internal pressure rating of 235 psi at 73°F (23°C).

Spears® Needle Valve

Angle Pattern - Soc




5692-002BL	1/4	1	18	066	118.64
5692-003BL	3/8	1	18	066	118.64
5692-005BL	1/2	1	18	066	125.94

Replaceable PTFE Stem Seal - no elastomer or lubricants used. Needle valves carry a maximum internal pressure rating of 235 psi at 73°F (23°C).

Spears® Needle Valve

Angle Pattern - SR FIPT



5691-005BLSR	1/2	1	18	066	125.94
--------------	-----	---	----	-----	--------

Replaceable PTFE Stem Seal - no elastomer or lubricants used. Needle valves carry a maximum internal pressure rating of 235 psi at 73°F (23°C).

Part Number	Size	Std Pk	Mstr Ctn	Disc Code	Price Each
-------------	------	--------	----------	-----------	------------

Spears® Gauge Guards

PTFE Diaphragm 1/4" Inlet Connection



G0004-002BL	No Gauge	1	18	623	134.77
G30V4-002BL	0-30 in-Hg	1	18	623	208.44
G0154-002BL	0-15 psi	1	18	623	197.00
G0304-002BL	0-30 psi	1	18	623	197.00
G0604-002BL	0-60 psi	1	18	623	197.00
G1004-002BL	0-100 psi	1	18	623	197.00
G1604-002BL	0-160 psi	1	18	623	197.00
G2004-002BL	0-200 psi	1	18	623	197.00
G3004-002BL	0-300 psi	1	18	623	197.00

No Gauge designates Gauge Guard only, unfilled. Other units are pre-filled and factory assembled with gauge specified in Size column. Gauge Guards carry a maximum pressure rating to 235 psi @ 73°F (23°C) and full vacuum service on vacuum gauges. All inlet connections are Spears® patented Special Reinforced (SR) female plastic NPT thread.

Spears® Gauge Guards

PTFE Diaphragm 1/2" Inlet Connection



G0004-005BL	No Gauge	1	18	623	134.77
G30V4-005BL	0-30 in-Hg	1	18	623	208.44
G0154-005BL	0-15 psi	1	18	623	197.00
G0304-005BL	0-30 psi	1	18	623	197.00
G0604-005BL	0-60 psi	1	18	623	197.00
G1004-005BL	0-100 psi	1	18	623	197.00
G1604-005BL	0-160 psi	1	18	623	197.00
G2004-005BL	0-200 psi	1	18	623	197.00
G3004-005BL	0-300 psi	1	18	623	197.00

No Gauge designates Gauge Guard only, unfilled. Other units are pre-filled and factory assembled with gauge specified in Size column. Gauge Guards carry a maximum pressure rating to 235 psi @ 73°F (23°C) and full vacuum service on vacuum gauges. All inlet connections are Spears® patented Special Reinforced (SR) female plastic NPT thread.

Spears® Gauge Guards

Viton® Diaphragm 1/4" Inlet Connection



G0003-002BL	No Gauge	1	18	623	134.77
G30V3-002BL	0-30 in-Hg	1	18	623	208.44
G0153-002BL	0-15 psi	1	18	623	197.00
G0303-002BL	0-30 psi	1	18	623	197.00
G0603-002BL	0-60 psi	1	18	623	197.00
G1003-002BL	0-100 psi	1	18	623	197.00
G1603-002BL	0-160 psi	1	18	623	197.00
G2003-002BL	0-200 psi	1	18	623	197.00
G3003-002BL	0-300 psi	1	18	623	197.00

No Gauge designates Gauge Guard only, unfilled. Other units are pre-filled and factory assembled with gauge specified in Size column. Gauge Guards carry a maximum pressure rating to 235 psi @ 73°F (23°C) and full vacuum service on vacuum gauges. All inlet connections are Spears® patented Special Reinforced (SR) female plastic NPT thread.

Spears® Gauge Guards

Viton® Diaphragm 1/2" Inlet Connection



G0003-005BL	No Gauge	1	18	623	134.77
G30V3-005BL	0-30 in-Hg	1	18	623	208.44
G0153-005BL	0-15 psi	1	18	623	197.00
G0303-005BL	0-30 psi	1	18	623	197.00
G0603-005BL	0-60 psi	1	18	623	197.00
G1003-005BL	0-100 psi	1	18	623	197.00
G1603-005BL	0-160 psi	1	18	623	197.00
G2003-005BL	0-200 psi	1	18	623	197.00
G3003-005BL	0-300 psi	1	18	623	197.00