



Schedule 80 PVC Industrial Products & Accessories Globe Valves & Needle Valves

Globe Valves



Pressure Rating @ 73°F (23°C), Water
2-1/2" - 6" 150 psi
Maximum Service Temperature
PVC = 140°F (60°C)
Temperature/Pressure De-ratings Apply
All Valves Assembled with Silicone-Free,
Water Soluble Lubricant
Suitable for Vacuum Service

Internal Repair Kit includes 1-Bonnet O-ring along with a factory assembled (required) internal component replacement unit consisting of Bonnet assembled with Stem/O-rings, Seat & Seal Carrier components. Install in valve using existing valve Bolts/Nuts/Washers, and Handle/Nut.

PVC Flanged Ends

Size	Buna-N	EPDM	Viton®	Std Pk	Mstr Pk	Disc Code
2-1/2	6013-025 577.86	6023-025 611.54	6033-025 658.81	1	0	620
	6013-030 662.40	6023-030 691.74	6033-030 769.81	1	0	620
4	6013-040 751.49	6023-040 898.36	6033-040 987.12	1	0	620
	6013-060 1155.72	6023-060 1381.97	6033-060 1409.51	1	0	620

PVC Internal Repair Kit

Size	Buna-N	EPDM	Viton®	Std Pk	Mstr Pk	Disc Code
2-1/2	GL-BRK-025 192.23	GL-ERK-025 464.95	GL-VRK-025 517.13	1	0	299
	GL-BRK-030 214.23	GL-ERK-030 515.16	GL-VRK-030 574.20	1	0	299
4	GL-BRK-040 251.35	GL-ERK-040 604.11	GL-VRK-040 664.20	1	0	299
	GL-BRK-060 547.67	GL-ERK-060 928.30	GL-VRK-060 947.30	1	0	299

Needle Valves



Pressure Rating @ 73°F (23°C), Water
PVC 235 psi
Maximum Service Temperature
PVC = 140°F (60°C)
Solid PTFE Stem Seals
No Elastomer or Lubricants used
Valves include Panel Mounting Nut

PVC Needle Valve

Size	Threaded	Socket	SR Threaded	Std Pk	Mstr Pk	Disc Code
------	----------	--------	-------------	--------	---------	-----------

Globe Pattern

1/4	5591-002 67.71	5592-002 67.71	---	1	18	218
	5591-003 67.71	5592-003 67.71	---	1	18	218
1/2	5591-005 75.15	5592-005 75.15	5591-005SR 77.17	1	18	218

Angle Pattern

1/4	5691-002 67.71	5692-002 67.71	---	1	18	218
	5691-003 67.71	5692-003 67.71	---	1	18	218
1/2	5691-005 75.15	5692-005 75.15	5691-005SR 77.17	1	18	218



Thermoplastic Valves Globe Valves



Pressure Rating @ 73°F (23°C), Water
 2-1/2" - 6" 150 psi
Maximum Service Temperature
 PVC = 140°F (60°C)
 CPVC = 200°F (93°C)
Temperature/Pressure De-ratings Apply
All Valves Assembled with Silicone-Free,
Water Soluble Lubricant
Suitable for Vacuum Service

Internal Repair Kit includes 1-Bonnet O-ring along with a factory assembled (required) internal component replacement unit consisting of Bonnet assembled with Stem/O-rings, Seat & Seal Carrier components. Install in valve using existing valve Bolts/Nuts/Washers, and Handle/Nut.

PVC Flanged Ends

Size	Buna-N	EPDM	Viton®	Std Pk	Mstr Pk	Disc Code
2-1/2	6013-025	6023-025	6033-025	1	0	620
	577.86	611.54	658.81			
3	6013-030	6023-030	6033-030	1	0	620
	662.40	691.74	769.81			
4	6013-040	6023-040	6033-040	1	0	620
	751.49	898.36	987.12			
6	6013-060	6023-060	6033-060	1	0	620
	1155.72	1381.97	1409.51			

CPVC Flanged Ends

Size	EPDM	Viton®	Std Pk	Mstr Pk	Disc Code
2-1/2	6023-025C	6033-025C	1	0	622
	927.20	973.79			
3	6023-030C	6033-030C	1	0	622
	973.34	1082.02			
4	6023-040C	6033-040C	1	0	622
	1264.14	1389.64			
6	6023-060C	6033-060C	1	0	622
	1968.31	1984.96			

PVC Internal Repair Kit

Size	Buna-N	EPDM	Viton®	Std Pk	Mstr Pk	Disc Code
2-1/2	GL-BRK-025	GL-ERK-025	GL-VRK-025	1	0	299
	192.23	464.95	517.13			
3	GL-BRK-030	GL-ERK-030	GL-VRK-030	1	0	299
	214.23	515.16	574.20			
4	GL-BRK-040	GL-ERK-040	GL-VRK-040	1	0	299
	251.35	604.11	664.20			
6	GL-BRK-060	GL-ERK-060	GL-VRK-060	1	0	299
	547.67	928.30	947.30			

CPVC Internal Repair Kits

Size	EPDM	Viton®	Std Pk	Mstr Pk	Disc Code
2-1/2	GL-ERK-025C	GL-VRK-025C	1	0	299
	654.71	727.47			
3	GL-ERK-030C	GL-VRK-030C	1	0	299
	748.96	822.46			
4	GL-ERK-040C	GL-VRK-040C	1	0	299
	849.24	934.62			
6	GL-ERK-060C	GL-VRK-060C	1	0	299
	1212.97	1334.74			