

Metric Fittings & Valves Class 10/12 PVC & CPVC Metric Fittings & Class 150 Flanges



Part Number	Size	Std Pk	Mstr Ctn	Disc Code	Price Each
-------------	------	--------	----------	-----------	------------

PVC TEE Socket



PN 10

6201-060	160 d	4	0	190	214.38
6201-080	225 d	2	0	190	497.20
6201-160040	160 d X 4	2	0	190	214.38
601-280	280 d	1	0	191	1642.65

PVC 90° ELL Socket



PN 10

6206-060	160 d	4	0	190	127.48
6206-080	225 d	2	0	190	351.37
606-280	280 d	1	0	191	1572.50

PVC 45° ELL Socket



PN 10

6217-060	160 d	5	0	190	153.20
6217-080	225 d	2	0	190	332.15
617-280	280 d	2	0	191	875.26

PVC REDUCER BUSHING Spigot x Socket



PN 10

637-225160	225 X 160 d	3	0	190	206.05
------------	--------------------	---	---	-----	--------

PVC CAP Socket



PN 10

6247-060	160 d	4	0	190	248.60
----------	--------------	---	---	-----	--------

CPVC WYE Socket



PN 10

6275-160110C	160 d X 110 d	5	0	192	603.56
--------------	----------------------	---	---	-----	--------

PVC FLANGE* Van Stone Style ASTM Socket x Multi-bolt Pattern Ring



150 psi

M854-020	2	10	0	080	28.63
M854-060	6	5	0	080	97.24
M854-080	8	2	0	080	158.35

* Hubs fit 2", 6" and 8" ASTM IPS pipe. Rings are manufactured to accept bolt patterns in size 2", 6" and 8" in ANSI Class 150, B.S. 4504 NP10 B.S. 4504 NP16 (except 8"), B.S. 10 Table D and B.S. 10 Table E. Consult Spears® Manufacturing Company Technical Services for additional information. Not for use with wafer valves.

PVC FLANGE* Van Stone Style Spigot x Multi-bolt Pattern Ring



150 psi

M856-020	2	10	0	080	28.85
M856-060	6	4	0	080	98.04
M856-080	8	2	0	080	159.54

Part Number	Size	Std Pk	Mstr Ctn	Disc Code	Price Each
-------------	------	--------	----------	-----------	------------

PVC FLANGE* Van Stone Style (continued) Spigot x Multi-bolt Pattern Ring

* Spigots fit 2", 6" and 8" ASTM IPS fitting socket. Rings are manufactured to accept bolt patterns in size 2", 6" and 8" in ANSI Class 150, B.S. 4504 NP10 B.S. 4504 NP16 (except 8"), B.S. 10 Table D and B.S. 10 Table E. Consult Spears® Manufacturing Company Technical Services for additional information. Not for use with wafer valves.

PVC FLANGE* Van Stone Style ASTM Socket x Table D&E Drilling



150 psi

854-030DE	3"/80 nom.	10	0	080	48.87
854-040DE	4"/110 nom.	5	0	080	61.82

* Hubs fit 3" or 4" ASTM IPS Pipe. Rings are manufactured to BS 10 Table D & Table E bolt patterns.

PVC FLANGE* Van Stone Style ASTM Spigot x Table D&E Drilling



150 psi

856-030DE	3"/80 nom.	10	0	080	49.26
856-040DE	4"/110 nom.	10	0	080	62.33

* Spigots fit 3" or 4" ASTM IPS fitting sockets. Rings are manufactured to BS 10 Table D & Table E bolt patterns.

PVC FLANGE* Van Stone Style ASTM Socket x DIN PN 10/16 Drilling



150 psi

854-030DIN	3"/80 nom.	10	0	080	48.87
854-040DIN	4"/110 nom.	5	0	080	61.82

* Hubs fit 3" or 4" ASTM IPS Pipe. Rings are manufactured to DIN 8063-4 PN 10 and PN 16 bolt patterns.

PVC FLANGE* Van Stone Style ASTM Spigot x DIN PN 10/16 Drilling



150 psi

856-030DIN	3"/80 nom.	10	0	080	49.26
856-040DIN	4"/110 nom.	5	0	080	62.33

* Spigots fit 3" or 4" ASTM IPS fitting sockets. Rings are manufactured to DIN 8063-4 PN 10 and PN 16 bolt patterns.

PVC FLANGE* Van Stone Style Metric Socket x Multi Pattern Ring



150 psi

6254-160	160 d	5	0	190	97.24
6254-200	200 d	2	0	190	158.35
6254-225	225 d	2	0	190	158.35
6254-280	280 d	2	0	191	205.00

* Hubs are manufactured to fit 160mm - 225mm and 280 mm O.D. Pipe. Rings are manufactured to accept bolt patterns for ANSI Class 150, B.S. 4504 NP10, B.S. 4504 NP16 (except 225mm), B.S. 10 Table D (except 280mm) and B.S. 10 Table E. Consult Spears® Manufacturing Company Technical Services for additional information. Not for use with wafer valves.