



Thermoplastic Valves Compact 2000 Ball Valves



Pressure Rating @ 73°F (23°C), Water
 1/2" - 2" 235 psi
 Maximum Service Temperature
 PVC = 140°F (60°C)
 CPVC = 200°F (93°C)
 Temperature/Pressure Deratings Apply
 All Valves Assembled with Silicone-Free, Water Soluble Lubricants.
 Rated for Vacuum Service
 Compact 2000 Ball Valves are a Maintenance-Free, Sealed Unit (non-repairable).
 See Ball Valve Accessories & Repair Kits Section for Additional Options and Features.

PVC 2000 Compact Ball Valve

Size	EPDM	Viton®	Std Pk	Mstr Pk	Disc Code
Socket Ends					
1/2	6622-005 20.11	6632-005 22.64	10	120	210
3/4	6622-007 27.44	6632-007 28.09	10	80	210
1	6622-010 29.95	6632-010 33.59	10	0	210
1-1/4	6622-012 45.06	6632-012 52.07	6	0	210
1-1/2	6622-015 53.67	6632-015 59.69	5	0	210
2	6622-020 71.65	6632-020 80.50	8	0	210

Threaded Ends

1/2	6621-005 20.11	6631-005 22.64	10	120	210
3/4	6621-007 27.44	6631-007 28.09	10	80	210
1	6621-010 29.95	6631-010 33.59	10	0	210
1-1/4	6621-012 49.32	6631-012 52.07	6	0	210
1-1/2	6621-015 53.67	6631-015 59.69	5	0	210
2	6621-020 71.65	6631-020 80.50	8	0	210

Flanged Ends

1/2	6623-005 42.35	6633-005 44.50	10	120	210
3/4	6623-007 47.83	6633-007 49.50	10	120	210
1	6623-010 62.33	6633-010 65.67	10	120	210
1-1/4	6623-012 77.83	6633-012 83.50	10	120	210
1-1/2	6623-015 94.16	6633-015 102.35	10	120	210
2	6623-020 125.66	6633-020 131.17	10	120	210

CPVC 2000 Compact Ball Valve

Size	EPDM	Viton®	Std Pk	Mstr Pk	Disc Code
Socket Ends					
1/2	6622-005C 23.68	6632-005C 26.35	10	120	212
3/4	6622-007C 31.24	6632-007C 35.10	10	80	212
1	6622-010C 39.04	6632-010C 43.90	10	0	212
1-1/4	6622-012C 63.89	6632-012C 78.96	6	0	212
1-1/2	6622-015C 79.02	6632-015C 87.80	5	0	212
2	6622-020C 103.52	6632-020C 116.31	8	0	212

Threaded Ends

1/2	6621-005C 23.68	6631-005C 26.35	10	120	212
------------	--------------------	--------------------	----	-----	-----

CPVC 2000 Compact Ball Valve (continued)

Size	EPDM	Viton®	Std Pk	Mstr Pk	Disc Code
Threaded Ends					
3/4	6621-007C 31.24	6631-007C 35.10	10	80	212
1	6621-010C 39.04	6631-010C 43.90	10	0	212
1-1/4	6621-012C 63.89	6631-012C 78.96	6	0	212
1-1/2	6621-015C 79.02	6631-015C 87.80	5	0	212
2	6621-020C 103.52	6631-020C 116.31	8	0	212

Flanged Ends

1/2	6623-005C 64.80	6633-005C 66.80	1	0	212
3/4	6623-007C 76.60	6633-007C 79.98	1	0	212
1	6623-010C 100.80	6633-010C 106.75	1	0	212
1-1/4	6623-012C 126.80	6633-012C 133.60	1	0	212
1-1/2	6623-015C 160.20	6633-015C 169.79	1	0	212
2	6623-020C 223.20	6633-020C 229.80	1	0	212



**Schedule 80 CPVC Industrial Products & Accessories
Compact 2000 Ball Valves**



Pressure Rating @ 73°F (23°C), Water
 1/2" - 2" 235 psi
 Maximum Service Temperature
 CPVC = 200°F (93°C)
 Temperature/Pressure De-ratings Apply
 All Valves Assembled with Silicone-Free, Water Soluble Lubricants.
 Rated for Vacuum Service
 Compact 2000 Ball Valves are a Maintenance-Free, Sealed Unit (non-repairable).
 See Ball Valve Accessories & Repair Kits Section for Additional Options and Features.

CPVC 2000 Compact Ball Valve

Size	EPDM	Viton®	Std Pk	Mstr Pk	Disc Code
------	------	--------	--------	---------	-----------

Socket Ends

1/2	6622-005C 23.68	6632-005C 26.35	10	120	212
3/4	6622-007C 31.24	6632-007C 35.10	10	80	212
1	6622-010C 39.04	6632-010C 43.90	10	0	212
1-1/4	6622-012C 63.89	6632-012C 78.96	6	0	212
1-1/2	6622-015C 79.02	6632-015C 87.80	5	0	212
2	6622-020C 103.52	6632-020C 116.31	8	0	212

Threaded Ends

1/2	6621-005C 23.68	6631-005C 26.35	10	120	212
3/4	6621-007C 31.24	6631-007C 35.10	10	80	212
1	6621-010C 39.04	6631-010C 43.90	10	0	212
1-1/4	6621-012C 63.89	6631-012C 78.96	6	0	212
1-1/2	6621-015C 79.02	6631-015C 87.80	5	0	212
2	6621-020C 103.52	6631-020C 116.31	8	0	212

Flanged Ends

1/2	6623-005C 64.80	6633-005C 66.80	1	0	212
3/4	6623-007C 76.60	6633-007C 79.98	1	0	212
1	6623-010C 100.80	6633-010C 106.75	1	0	212
1-1/4	6623-012C 126.80	6633-012C 133.60	1	0	212
1-1/2	6623-015C 160.20	6633-015C 169.79	1	0	212
2	6623-020C 223.20	6633-020C 229.80	1	0	212