



## Thermoplastic Valves Compact 2000 Ball Valves



Pressure Rating @ 73°F (23°C), Water  
 1/2" - 2" 235 psi  
 Maximum Service Temperature  
 PVC = 140°F (60°C)  
 CPVC = 200°F (93°C)  
 Temperature/Pressure Deratings Apply  
 All Valves Assembled with Silicone-Free, Water Soluble Lubricants.  
 Rated for Vacuum Service  
 Compact 2000 Ball Valves are a Maintenance-Free, Sealed Unit (non-repairable).  
 See Ball Valve Accessories & Repair Kits Section for Additional Options and Features.

### PVC 2000 Compact Ball Valve

Size	EPDM	Viton®	Std Pk	Mstr Pk	Disc Code
<b>Socket Ends</b>					
<b>1/2</b>	6622-005 20.11	6632-005 22.64	10	120	210
<b>3/4</b>	6622-007 27.44	6632-007 28.09	10	80	210
<b>1</b>	6622-010 29.95	6632-010 33.59	10	0	210
<b>1-1/4</b>	6622-012 45.06	6632-012 52.07	6	0	210
<b>1-1/2</b>	6622-015 53.67	6632-015 59.69	5	0	210
<b>2</b>	6622-020 71.65	6632-020 80.50	8	0	210

#### Threaded Ends

<b>1/2</b>	6621-005 20.11	6631-005 22.64	10	120	210
<b>3/4</b>	6621-007 27.44	6631-007 28.09	10	80	210
<b>1</b>	6621-010 29.95	6631-010 33.59	10	0	210
<b>1-1/4</b>	6621-012 49.32	6631-012 52.07	6	0	210
<b>1-1/2</b>	6621-015 53.67	6631-015 59.69	5	0	210
<b>2</b>	6621-020 71.65	6631-020 80.50	8	0	210

#### Flanged Ends

<b>1/2</b>	6623-005 42.35	6633-005 44.50	10	120	210
<b>3/4</b>	6623-007 47.83	6633-007 49.50	10	120	210
<b>1</b>	6623-010 62.33	6633-010 65.67	10	120	210
<b>1-1/4</b>	6623-012 77.83	6633-012 83.50	10	120	210
<b>1-1/2</b>	6623-015 94.16	6633-015 102.35	10	120	210
<b>2</b>	6623-020 125.66	6633-020 131.17	10	120	210

### CPVC 2000 Compact Ball Valve

Size	EPDM	Viton®	Std Pk	Mstr Pk	Disc Code
<b>Socket Ends</b>					
<b>1/2</b>	6622-005C 23.68	6632-005C 26.35	10	120	212
<b>3/4</b>	6622-007C 31.24	6632-007C 35.10	10	80	212
<b>1</b>	6622-010C 39.04	6632-010C 43.90	10	0	212
<b>1-1/4</b>	6622-012C 63.89	6632-012C 78.96	6	0	212
<b>1-1/2</b>	6622-015C 79.02	6632-015C 87.80	5	0	212
<b>2</b>	6622-020C 103.52	6632-020C 116.31	8	0	212

#### Threaded Ends

<b>1/2</b>	6621-005C 23.68	6631-005C 26.35	10	120	212
------------	--------------------	--------------------	----	-----	-----

### CPVC 2000 Compact Ball Valve (continued)

Size	EPDM	Viton®	Std Pk	Mstr Pk	Disc Code
<b>Threaded Ends</b>					
<b>3/4</b>	6621-007C 31.24	6631-007C 35.10	10	80	212
<b>1</b>	6621-010C 39.04	6631-010C 43.90	10	0	212
<b>1-1/4</b>	6621-012C 63.89	6631-012C 78.96	6	0	212
<b>1-1/2</b>	6621-015C 79.02	6631-015C 87.80	5	0	212
<b>2</b>	6621-020C 103.52	6631-020C 116.31	8	0	212

#### Flanged Ends

<b>1/2</b>	6623-005C 64.80	6633-005C 66.80	1	0	212
<b>3/4</b>	6623-007C 76.60	6633-007C 79.98	1	0	212
<b>1</b>	6623-010C 100.80	6633-010C 106.75	1	0	212
<b>1-1/4</b>	6623-012C 126.80	6633-012C 133.60	1	0	212
<b>1-1/2</b>	6623-015C 160.20	6633-015C 169.79	1	0	212
<b>2</b>	6623-020C 223.20	6633-020C 229.80	1	0	212

## Schedule 80 PVC Industrial Products & Accessories Single Entry Ball Valves & Compact 2000 Ball Valves



### Single Entry Ball Valves

Pressure Rating @ 73°F (23°C), Water  
 1/2" - 2" 235 psi  
 3" - 4" 150 psi  
 Maximum Service Temperature  
 PVC = 140°F (60°C)  
 Temperature/Pressure De-ratings Apply  
 Rated for Vacuum Service

All Valves Assembled with Silicone-Free, Water Soluble Lubricant. See Ball Valve Accessories & Repair Kits Section for Additional Options and Features



PVC Gray – Socket/Threaded Style

#### PVC Gray

Size	Buna-N	EPDM	Viton®	Std Pk	Mstr Pk	Disc Code
<b>Threaded Ends</b>						
1/2	2411-005G 19.84	2421-005G 21.99	2431-005G 24.46	10	120	240
3/4	2411-007G 24.99	2421-007G 27.80	2431-007G 30.87	10	80	240
1	2411-010G 29.40	2421-010G 32.63	2431-010G 36.27	10	0	240
1-1/4	2411-012G 40.83	2421-012G 45.39	2431-012G 50.37	6	0	240
1-1/2	2411-015G 51.40	2421-015G 60.21	2431-015G 66.96	5	0	240
2	2411-020G 59.52	2421-020G 66.14	2431-020G 73.45	5	0	240
3	2411-030G 207.45	2421-030G 257.29	2431-030G 296.69	1	0	240
4	2411-040G 438.45	2421-040G 483.10	2431-040G 525.12	1	0	240

#### PVC Gray

Size	Buna-N	EPDM	Viton®	Std Pk	Mstr Pk	Disc Code
<b>Socket Ends</b>						
1/2	2412-005G 19.84	2422-005G 21.99	2432-005G 24.46	10	120	240
3/4	2412-007G 24.99	2422-007G 27.80	2432-007G 30.87	10	80	240
1	2412-010G 29.40	2422-010G 32.63	2432-010G 36.27	10	0	240
1-1/4	2412-012G 40.83	2422-012G 45.39	2432-012G 50.37	5	0	240
1-1/2	2412-015G 51.46	2422-015G 60.21	2432-015G 66.96	5	0	240
2	2412-020G 59.52	2422-020G 66.14	2432-020G 73.45	5	0	240
3	2412-030G 207.45	2422-030G 257.29	2432-030G 296.69	1	0	240
4	2412-040G 438.45	2422-040G 483.10	2432-040G 525.12	1	0	240

### Compact 2000 Ball Valves



Pressure Rating @ 73°F (23°C), Water  
 1/2" - 2" 235 psi  
 Maximum Service Temperature  
 PVC = 140°F (60°C)  
 Temperature/Pressure De-ratings Apply

All Valves Assembled with Silicone-Free, Water Soluble Lubricants.  
 Rated for Vacuum Service  
 Compact 2000 Ball Valves are a Maintenance-Free, Sealed Unit (non-repairable).  
 See Ball Valve Accessories & Repair Kits Section for Additional Options and Features.

#### PVC 2000 Compact Ball Valve

Size	EPDM	Viton®	Std Pk	Mstr Pk	Disc Code
<b>Socket Ends</b>					
1/2	6622-005 20.11	6632-005 22.64	10	120	210
3/4	6622-007 27.44	6632-007 28.09	10	80	210
1	6622-010 29.95	6632-010 33.59	10	0	210
1-1/4	6622-012 45.06	6632-012 52.07	6	0	210
1-1/2	6622-015 53.67	6632-015 59.69	5	0	210
2	6622-020 71.65	6632-020 80.50	8	0	210
<b>Threaded Ends</b>					
1/2	6621-005 20.11	6631-005 22.64	10	120	210

#### PVC 2000 Compact Ball Valve (continued)

Size	EPDM	Viton®	Std Pk	Mstr Pk	Disc Code
<b>Threaded Ends</b>					
3/4	6621-007 27.44	6631-007 28.09	10	80	210
1	6621-010 29.95	6631-010 33.59	10	0	210
1-1/4	6621-012 49.32	6631-012 52.07	6	0	210
1-1/2	6621-015 53.67	6631-015 59.69	5	0	210
2	6621-020 71.65	6631-020 80.50	8	0	210
<b>Flanged Ends</b>					
1/2	6623-005 42.35	6633-005 44.50	10	120	210
3/4	6623-007 47.83	6633-007 49.50	10	120	210

Made in the U.S.A.

**NOT FOR DISTRIBUTION OF COMPRESSED AIR OR GAS**  
 Progressive Products from Spears® Innovation and Technology

Page 221