



**Schedule 80 PVC Industrial Products & Accessories
Compact 2000 Ball Valves & Compact Ball Valves (Regular Style)**

Compact 2000 Ball Valves

PVC 2000 Compact Ball Valve (continued)

Size	EPDM	Viton®	Std Pk	Mstr Pk	Disc Code
Flanged Ends					
1	6623-010 62.33	6633-010 65.67	10	120	210
1-1/4	6623-012 77.83	6633-012 83.50	10	120	210
1-1/2	6623-015 94.16	6633-015 102.35	10	120	210
2	6623-020 125.66	6633-020 131.17	10	120	210

Compact Ball Valves (Regular Style)



Socket/Threaded Style

Pressure Rating @ 73°F (23°C), Water
 1/2" - 2" 235 psi
 3" - 6" 150 psi
 Flanged 150 psi
 Maximum Service Temperature
 PVC = 140°F (60°C)
 Temperature/Pressure De-ratings Apply
 Rated for Vacuum Service

All Valves Assembled with Silicone-Free, Water Soluble Lubricants.
 See Ball Valve Accessories & Repair Kits Section for Additional
 Options & Features

Note: Standard 6" Valve uses Lever-Style Handle for proper
 leverage.
 T-Handle option is more compact but will increase difficulty of
 operation.

PVC

Size	EPDM	Viton®	Std Pk	Mstr Pk	Disc Code
Socket Ends					
1/2	2122-005 21.16	2132-005 23.83	10	80	210
3/4	2122-007 28.88	2132-007 29.57	10	0	210
1	2122-010 31.51	2132-010 35.38	10	0	210
1-1/4	2122-012 56.51	2132-012 62.82	6	0	210
1-1/2	2122-015 69.97	2132-015 73.11	5	0	210
2	2122-020 75.41	2132-020 84.74	6	0	210
3	2122-030 245.11	2132-030 275.37	1	4	211
4	2122-040 377.10	2132-040 542.81	1	0	211
6 (Lever Handle)	2122-060 489.73	2132-060 704.95	1	0	211
6 (Tee Handle)	21226-060 489.73	21326-060 704.95	1	0	211

Threaded Ends

1/2	2121-005 21.16	2131-005 23.83	10	80	210
3/4	2121-007 28.88	2131-007 29.57	10	0	210
1	2121-010 31.51	2131-010 35.38	10	0	210
1-1/4	2121-012 56.51	2131-012 62.82	6	0	210
1-1/2	2121-015 69.97	2131-015 73.11	5	0	210
2	2121-020 75.41	2131-020 84.74	6	0	210
3	2121-030 245.11	2131-030 275.37	1	4	211
4	2121-040 377.10	2131-040 542.81	1	0	211

PVC

Size	EPDM	Viton®	Std Pk	Mstr Pk	Disc Code
Flanged Ends					
1/2	2123-005 46.78	2133-005 49.83	1	8	210
3/4	2123-007 56.60	2133-007 58.85	1	8	210
1	2123-010 62.44	2133-010 66.29	1	8	210
1-1/4	2123-012 88.40	2133-012 94.71	1	8	210
1-1/2	2123-015 102.28	2133-015 107.09	1	4	210
2	2123-020 118.72	2133-020 127.96	1	0	210
3	2123-030 318.94	2133-030 349.21	1	0	211
4	2123-040 470.46	2133-040 636.16	1	0	211
6 (Lever Handle)	2123-060 905.83	2133-060 997.09	1	0	211
6 (Tee Handle)	21236-060 905.83	21336-060 997.09	1	0	211



Thermoplastic Valves Compact 2000 Ball Valves



Pressure Rating @ 73°F (23°C), Water
 1/2" - 2" 235 psi
 Maximum Service Temperature
 PVC = 140°F (60°C)
 CPVC = 200°F (93°C)
 Temperature/Pressure Deratings Apply
 All Valves Assembled with Silicone-Free, Water Soluble Lubricants.
 Rated for Vacuum Service
 Compact 2000 Ball Valves are a Maintenance-Free, Sealed Unit (non-repairable).
 See Ball Valve Accessories & Repair Kits Section for Additional Options and Features.

PVC 2000 Compact Ball Valve

Size	EPDM	Viton®	Std Pk	Mstr Pk	Disc Code
Socket Ends					
1/2	6622-005 20.11	6632-005 22.64	10	120	210
3/4	6622-007 27.44	6632-007 28.09	10	80	210
1	6622-010 29.95	6632-010 33.59	10	0	210
1-1/4	6622-012 45.06	6632-012 52.07	6	0	210
1-1/2	6622-015 53.67	6632-015 59.69	5	0	210
2	6622-020 71.65	6632-020 80.50	8	0	210

Threaded Ends

1/2	6621-005 20.11	6631-005 22.64	10	120	210
3/4	6621-007 27.44	6631-007 28.09	10	80	210
1	6621-010 29.95	6631-010 33.59	10	0	210
1-1/4	6621-012 49.32	6631-012 52.07	6	0	210
1-1/2	6621-015 53.67	6631-015 59.69	5	0	210
2	6621-020 71.65	6631-020 80.50	8	0	210

Flanged Ends

1/2	6623-005 42.35	6633-005 44.50	10	120	210
3/4	6623-007 47.83	6633-007 49.50	10	120	210
1	6623-010 62.33	6633-010 65.67	10	120	210
1-1/4	6623-012 77.83	6633-012 83.50	10	120	210
1-1/2	6623-015 94.16	6633-015 102.35	10	120	210
2	6623-020 125.66	6633-020 131.17	10	120	210

CPVC 2000 Compact Ball Valve

Size	EPDM	Viton®	Std Pk	Mstr Pk	Disc Code
Socket Ends					
1/2	6622-005C 23.68	6632-005C 26.35	10	120	212
3/4	6622-007C 31.24	6632-007C 35.10	10	80	212
1	6622-010C 39.04	6632-010C 43.90	10	0	212
1-1/4	6622-012C 63.89	6632-012C 78.96	6	0	212
1-1/2	6622-015C 79.02	6632-015C 87.80	5	0	212
2	6622-020C 103.52	6632-020C 116.31	8	0	212

Threaded Ends

1/2	6621-005C 23.68	6631-005C 26.35	10	120	212
------------	--------------------	--------------------	----	-----	-----

CPVC 2000 Compact Ball Valve (continued)

Size	EPDM	Viton®	Std Pk	Mstr Pk	Disc Code
Threaded Ends					
3/4	6621-007C 31.24	6631-007C 35.10	10	80	212
1	6621-010C 39.04	6631-010C 43.90	10	0	212
1-1/4	6621-012C 63.89	6631-012C 78.96	6	0	212
1-1/2	6621-015C 79.02	6631-015C 87.80	5	0	212
2	6621-020C 103.52	6631-020C 116.31	8	0	212

Flanged Ends

1/2	6623-005C 64.80	6633-005C 66.80	1	0	212
3/4	6623-007C 76.60	6633-007C 79.98	1	0	212
1	6623-010C 100.80	6633-010C 106.75	1	0	212
1-1/4	6623-012C 126.80	6633-012C 133.60	1	0	212
1-1/2	6623-015C 160.20	6633-015C 169.79	1	0	212
2	6623-020C 223.20	6633-020C 229.80	1	0	212