

## Schedule 80 CPVC Industrial Products & Accessories Butterfly Valves



Lever Handle Style



Gear Operator Style

Pressure Rating @ 73°F (23°C), Water  
1-1/2" - 12" 150 psi  
Maximum Service Temperature  
CPVC = 200°F (93°C)  
Temperature/Pressure De-ratings Apply  
See Butterfly Valve Accessories & Repair Kits Section for  
Additional Options and Features

### CPVC

Size	Buna-N	EPDM	Viton®	Std Pk	Mstr Pk	Disc Code
------	--------	------	--------	--------	---------	-----------

#### Lever Handle

1-1/2	721311-015C <b>356.16</b>	722311-015C <b>356.16</b>	723311-015C <b>720.84</b>	1	0	252
2	721311-020C <b>379.60</b>	722311-020C <b>379.60</b>	723311-020C <b>744.30</b>	1	0	252
2-1/2	721311-025C <b>403.09</b>	722311-025C <b>403.09</b>	723311-025C <b>808.28</b>	1	0	252
3	721311-030C <b>439.33</b>	722311-030C <b>439.33</b>	723311-030C <b>865.84</b>	1	0	252
4	721311-040C <b>507.59</b>	722311-040C <b>507.59</b>	723311-040C <b>1083.37</b>	1	0	252
6	721311-060C <b>750.70</b>	722311-060C <b>750.70</b>	723311-060C <b>1731.73</b>	1	0	252
8	721311-080C <b>1275.31</b>	722311-080C <b>1275.31</b>	723311-080C <b>2930.26</b>	1	0	252

#### Gear Operator

1-1/2	721321-015C <b>885.63</b>	722321-015C <b>885.63</b>	723321-015C <b>1209.41</b>	1	0	252
2	721321-020C <b>915.46</b>	722321-020C <b>915.46</b>	723321-020C <b>1246.83</b>	1	0	252
2-1/2	721321-025C <b>929.86</b>	722321-025C <b>929.86</b>	723321-025C <b>1310.23</b>	1	0	252
3	721321-030C <b>942.62</b>	722321-030C <b>942.62</b>	723321-030C <b>1369.16</b>	1	0	252
4	721321-040C <b>1010.87</b>	722321-040C <b>1010.87</b>	723321-040C <b>1586.69</b>	1	0	252
6	721321-060C <b>1258.26</b>	722321-060C <b>1258.26</b>	723321-060C <b>2235.01</b>	1	0	252
8	721321-080C <b>1778.60</b>	722321-080C <b>1778.60</b>	723321-080C <b>3433.56</b>	1	0	252
10	721321-100C <b>2490.91</b>	722321-100C <b>2490.91</b>	723321-100C <b>6363.76</b>	1	0	252
12	721321-120C <b>3518.83</b>	722321-120C <b>3518.83</b>	723321-120C <b>8272.46</b>	1	0	252

#### Valve Only

1-1/2	721301-015C <b>332.69</b>	722301-015C <b>332.69</b>	723301-015C <b>669.67</b>	1	0	252
2	721301-020C <b>356.16</b>	722301-020C <b>356.16</b>	723301-020C <b>684.56</b>	1	0	252
2-1/2	721301-025C <b>371.07</b>	722301-025C <b>371.07</b>	723301-025C <b>714.44</b>	1	0	252
3	721301-030C <b>400.95</b>	722301-030C <b>400.95</b>	723301-030C <b>780.54</b>	1	0	252
4	721301-040C <b>464.91</b>	722301-040C <b>464.91</b>	723301-040C <b>985.31</b>	1	0	252
6	721301-060C <b>699.49</b>	722301-060C <b>699.49</b>	723301-060C <b>1590.93</b>	1	0	252
8	721301-080C <b>1211.31</b>	722301-080C <b>1211.31</b>	723301-080C <b>2687.17</b>	1	0	252
10	721301-100C <b>2422.68</b>	722301-100C <b>2422.68</b>	723301-100C <b>5387.04</b>	1	0	252
12	721301-120C <b>3147.76</b>	722301-120C <b>3147.76</b>	723301-120C <b>7001.44</b>	1	0	252



## Thermoplastic Valves Butterfly Valves & Lug Insert Butterfly Valves

### Butterfly Valves

#### PVC (continued)

Size	Buna-N	EPDM	Viton®	Std Pk	Mstr Pk	Disc Code
<b>Gear Operator</b>						
10	721321-100 1863.89	722321-100 1863.89	723321-100 4111.68	1	0	250
12	721321-120 2567.68	722321-120 2567.68	723321-120 5907.41	1	0	250

#### Valve Only

1-1/2	721301-015 232.47	722301-015 232.47	723301-015 486.22	1	0	250
2	721301-020 258.03	722301-020 258.03	723301-020 509.70	1	0	250
2-1/2	721301-025 266.60	722301-025 266.60	723301-025 526.74	1	0	250
3	721301-030 272.99	722301-030 272.99	723301-030 537.41	1	0	250
4	721301-040 315.63	722301-040 315.63	723301-040 673.90	1	0	250
6	721301-060 477.69	722301-060 477.69	723301-060 1091.91	1	0	250
8	721301-080 827.48	722301-080 827.48	723301-080 1842.59	1	0	250
10	721301-100 1659.17	722301-100 1659.17	723301-100 3689.44	1	0	250
12	721301-120 2141.16	722301-120 2141.16	723301-120 5267.59	1	0	250

#### CPVC

Size	Buna-N	EPDM	Viton®	Std Pk	Mstr Pk	Disc Code
<b>Lever Handle</b>						
1-1/2	721311-015C 356.16	722311-015C 356.16	723311-015C 720.84	1	0	252
2	721311-020C 379.60	722311-020C 379.60	723311-020C 744.30	1	0	252
2-1/2	721311-025C 403.09	722311-025C 403.09	723311-025C 808.28	1	0	252
3	721311-030C 439.33	722311-030C 439.33	723311-030C 865.84	1	0	252
4	721311-040C 507.59	722311-040C 507.59	723311-040C 1083.37	1	0	252
6	721311-060C 750.70	722311-060C 750.70	723311-060C 1731.73	1	0	252
8	721311-080C 1275.31	722311-080C 1275.31	723311-080C 2930.26	1	0	252

#### Gear Operator

1-1/2	721321-015C 885.63	722321-015C 885.63	723321-015C 1209.41	1	0	252
-------	-----------------------	-----------------------	------------------------	---	---	-----

#### CPVC (continued)

Size	Buna-N	EPDM	Viton®	Std Pk	Mstr Pk	Disc Code
<b>Gear Operator</b>						
2	721321-020C 915.46	722321-020C 915.46	723321-020C 1246.83	1	0	252
2-1/2	721321-025C 929.86	722321-025C 929.86	723321-025C 1310.23	1	0	252
3	721321-030C 942.62	722321-030C 942.62	723321-030C 1369.16	1	0	252
4	721321-040C 1010.87	722321-040C 1010.87	723321-040C 1586.69	1	0	252
6	721321-060C 1258.26	722321-060C 1258.26	723321-060C 2235.01	1	0	252
8	721321-080C 1778.60	722321-080C 1778.60	723321-080C 3433.56	1	0	252
10	721321-100C 2490.91	722321-100C 2490.91	723321-100C 6363.76	1	0	252
12	721321-120C 3518.83	722321-120C 3518.83	723321-120C 8272.46	1	0	252

#### Valve Only

1-1/2	721301-015C 332.69	722301-015C 332.69	723301-015C 669.67	1	0	252
2	721301-020C 356.16	722301-020C 356.16	723301-020C 684.56	1	0	252
2-1/2	721301-025C 371.07	722301-025C 371.07	723301-025C 714.44	1	0	252
3	721301-030C 400.95	722301-030C 400.95	723301-030C 780.54	1	0	252
4	721301-040C 464.91	722301-040C 464.91	723301-040C 985.31	1	0	252
6	721301-060C 699.49	722301-060C 699.49	723301-060C 1590.93	1	0	252
8	721301-080C 1211.31	722301-080C 1211.31	723301-080C 2687.17	1	0	252
10	721301-100C 2422.68	722301-100C 2422.68	723301-100C 5387.04	1	0	252
12	721301-120C 3147.76	722301-120C 3147.76	723301-120C 7001.44	1	0	252

### Lug Insert Butterfly Valves



Spears® Standard Butterfly Valve with Lug Inserts Factory Assembled

Note: Lug (insert) Valves require attention to flow direction for dead-end service. Flange must be installed on side of valve *opposite* the hex nut recesses for Single-Side installation. See "True Lug Butterfly Valves," where dead-end service is required in either direction.

Pressure Rating @ 73°F (23°C), Water

1-1/2" - 12" 150 psi

Maximum Service Temperature

PVC = 140°F (60°C)

CPVC = 200°F (93°C)

Temperature/Pressure De-ratings Apply

See Butterfly Valve Accessories & Repair Kits Section for Additional Options and Features. Lug Valves Use Same Accessories, Repair Kits, and Overhaul Kits as Standard Butterfly Valves



#### PVC - Zinc-Plated Lug Inserts

Size	Buna-N	EPDM	Viton®	Std Pk	Mstr Pk	Disc Code
<b>Lever Handle</b>						
1-1/2	721311K-015 424.56	722311K-015 424.56	723311K-015 607.11	1	0	250

#### PVC - Zinc-Plated Lug Inserts (continued)

Size	Buna-N	EPDM	Viton®	Std Pk	Mstr Pk	Disc Code
<b>Lever Handle</b>						
2	721311K-020 434.03	722311K-020 434.03	723311K-020 630.11	1	0	250