



High Purity PVC System Low-Extractable Piping For Ultra-Pure Water Systems

| Part Number | Size | Std Pk | Mstr Ctn | Disc Code | Price Each |
|-------------|------|--------|----------|-----------|------------|
|-------------|------|--------|----------|-----------|------------|

Spears® Gauge Guards (continued)

Viton® Diaphragm 1/2" Inlet Connection

No Gauge designates Gauge Guard only, unfilled. Other units are pre-filled and factory assembled with gauge specified in Size column. Gauge Guards carry a maximum pressure rating to 235 psi @ 73°F (23°C) and full vacuum service on vacuum gauges. All inlet connections are Spears® patented Special Reinforced (SR) female plastic NPT thread.

Spears® Gauge Guards

EPDM Diaphragm 1/4" Inlet Connection

| | | | | | |
|-------------|------------|---|----|-----|--------|
| G0002-002BL | No Gauge | 1 | 18 | 623 | 129.38 |
| G30V2-002BL | 0-30 in-Hg | 1 | 18 | 623 | 200.10 |
| G0152-002BL | 0-15 psi | 1 | 18 | 623 | 189.14 |
| G0302-002BL | 0-30 psi | 1 | 18 | 623 | 189.14 |
| G0602-002BL | 0-60 psi | 1 | 18 | 623 | 189.14 |
| G1002-002BL | 0-100 psi | 1 | 18 | 623 | 189.14 |
| G1602-002BL | 0-160 psi | 1 | 18 | 623 | 189.14 |
| G2002-002BL | 0-200 psi | 1 | 18 | 623 | 189.14 |
| G3002-002BL | 0-300 psi | 1 | 18 | 623 | 189.14 |

No Gauge designates Gauge Guard only, unfilled. Other units are pre-filled and factory assembled with gauge specified in Size column. Gauge Guards carry a maximum pressure rating to 235 psi @ 73°F (23°C) and full vacuum service on vacuum gauges. All inlet connections are Spears® patented Special Reinforced (SR) female plastic NPT thread.

Spears® Gauge Guards

EPDM Diaphragm 1/2" Inlet Connection

| | | | | | |
|-------------|------------|---|----|-----|--------|
| G0002-005BL | No Gauge | 1 | 18 | 623 | 129.38 |
| G30V2-005BL | 0-30 in-Hg | 1 | 18 | 623 | 200.10 |
| G0152-005BL | 0-15 psi | 1 | 18 | 623 | 189.14 |
| G0302-005BL | 0-30 psi | 1 | 18 | 623 | 189.14 |
| G0602-005BL | 0-60 psi | 1 | 18 | 623 | 189.14 |
| G1002-005BL | 0-100 psi | 1 | 18 | 623 | 189.14 |
| G1602-005BL | 0-160 psi | 1 | 18 | 623 | 189.14 |
| G2002-005BL | 0-200 psi | 1 | 18 | 623 | 189.14 |
| G3002-005BL | 0-300 psi | 1 | 18 | 623 | 189.14 |

No Gauge designates Gauge Guard only, unfilled. Other units are pre-filled and factory assembled with gauge specified in Size column. Gauge Guards carry a maximum pressure rating to 235 psi @ 73°F (23°C) and full vacuum service on vacuum gauges. All inlet connections are Spears® patented Special Reinforced (SR) female plastic NPT thread.

LX-5 Low Extractable One-Step Cement

| | | | | | |
|----------|-------|----|---|-----|-------|
| LX5C-020 | Pint | 12 | 0 | 702 | 30.32 |
| LX5C-030 | Quart | 12 | 0 | 702 | 48.91 |

Empty Can

| | | | | | |
|--------|-------|----|---|-----|------|
| MT-654 | Pint | 12 | 0 | 710 | 6.61 |
| MT-651 | Quart | 12 | 0 | 710 | 7.46 |
| MT-653 | Quart | 12 | 0 | 710 | 7.46 |

MT-651 & MT-654 cans have 1-3/4" Screw Neck size
MT-653 is a TT Paint Type can

Brush

| | | | | | |
|-----|---|-----|---|-----|------|
| PB1 | 1 | 100 | 0 | 710 | 9.03 |
|-----|---|-----|---|-----|------|

Fits 1-3/4" Screw Cap

Roller

| | | | | | |
|------|-----------|----|---|-----|-------|
| 3020 | 3" length | 24 | 0 | 710 | 14.32 |
|------|-----------|----|---|-----|-------|

| Part Number | Size | Std Pk | Mstr Ctn | Disc Code | Price Each |
|-------------|------|--------|----------|-----------|------------|
|-------------|------|--------|----------|-----------|------------|

Roller (continued)

Fits Paint Type Quart Can (MT-653). For use with pipe sizes 3" to 6"

Cap Dauber

| | | | | | |
|--------|------------------|----|---|-----|------|
| DP-75 | 3/4" for Pint | 50 | 0 | 710 | 1.17 |
| DP-125 | 1-1/4" for Pint | 50 | 0 | 710 | 1.41 |
| DQ-125 | 1-1/4" for Quart | 50 | 0 | 710 | 1.41 |

1/2" Diameter for pipe sizes to 1"
3/4" Diameter for pipe size to 1-1/2"
1-1/4" Diameter for pipe size 1-1/2" to 3"

Can-Mate Dauber

| | | | | | |
|--------|--------|----|---|-----|------|
| CM-75 | 3/4" | 50 | 0 | 710 | 4.70 |
| CM-150 | 1-1/4" | 50 | 0 | 710 | 4.70 |

1/2" Diameter for pipe sizes to 1"
3/4" Diameter for pipe size to 1-1/2"
1-1/4" Diameter for pipe size 1-1/2" to 3"

Deburring Tool

Cone Type for pipe from 1/2" through 2"

| | | | | | |
|-------|---------------|---|---|-----|-------|
| DEB-2 | 1/2 to 2 Pipe | 1 | 6 | 710 | 87.25 |
|-------|---------------|---|---|-----|-------|

Tee Soc

| | | | | | |
|-----------|-------|----|-----|-----|--------|
| 801-005BL | 1/2 | 25 | 0 | 065 | 6.91 |
| 801-007BL | 3/4 | 15 | 120 | 065 | 8.44 |
| 801-010BL | 1 | 15 | 0 | 065 | 12.44 |
| 801-012BL | 1-1/4 | 10 | 0 | 065 | 19.38 |
| 801-015BL | 1-1/2 | 10 | 0 | 065 | 29.10 |
| 801-020BL | 2 | 10 | 0 | 065 | 46.20 |
| 801-030BL | 3 | 5 | 0 | 065 | 133.48 |
| 801-040BL | 4 | 5 | 0 | 065 | 223.18 |
| 801-060BL | 6 | 4 | 0 | 065 | 334.78 |

Reducing Tee Soc

| | | | | | |
|-----------|---------------|----|---|-----|--------|
| 801-131BL | 1X1X3/4 | 15 | 0 | 065 | 11.61 |
| 801-211BL | 1-1/2X1-1/2X1 | 10 | 0 | 065 | 25.22 |
| 801-249BL | 2X2X1 | 10 | 0 | 065 | 31.93 |
| 801-251BL | 2X2X1-1/2 | 10 | 0 | 065 | 31.93 |
| 801-338BL | 3X3X2 | 5 | 0 | 065 | 58.55 |
| 801-422BL | 4X4X3 | 5 | 0 | 065 | 94.65 |
| 801-530BL | 6X6X3 | 4 | 0 | 065 | 401.56 |
| 801-532BL | 6X6X4 | 5 | 0 | 065 | 401.56 |

90° Ell Soc

| | | | | | |
|-----------|-------|----|-----|-----|--------|
| 806-005BL | 1/2 | 20 | 160 | 065 | 4.28 |
| 806-007BL | 3/4 | 20 | 160 | 065 | 5.12 |
| 806-010BL | 1 | 10 | 80 | 065 | 10.15 |
| 806-012BL | 1-1/4 | 10 | 0 | 065 | 16.20 |
| 806-015BL | 1-1/2 | 10 | 0 | 065 | 23.97 |
| 806-020BL | 2 | 25 | 0 | 065 | 40.49 |
| 806-030BL | 3 | 5 | 0 | 065 | 103.83 |
| 806-040BL | 4 | 5 | 0 | 065 | 191.66 |
| 806-060BL | 6 | 4 | 0 | 065 | 287.49 |