Transition Fittings & Adapters PVC Gray Brass Thread Fittings



Part Number	Size			Disc	
i ait ivallibei	O126	l Pk	Ctn	Code	Fach

Part Number	Size	Mstr Ctn	Disc Code	Price Each

Transition Tee

Soc x Fipt With Brass Thread Insert

\Box		
	7	Ч
	<u> </u>	

802-005BR	1/2	20	160	086	31.27			
802-007BR	3/4	20	80	086	62.67			
Not intended to convey	Not intended to convey or dispense water for human consumption through drinking or							

Transiton Male Adapter w/ Brass Thread **Brass Mipt x Socket**



836-005BR	1/2	40	160	086	26.11
836-007BR	3/4	40	160	086	39.37
836-010BR	1	10	60	086	64.02
836-012BR	1-1/4	10	60	086	107.84
836-015BR	1-1/2	10	40	086	143.10
836-020BR	2	8	32	086	177.77

Transition Reducing Tee Soc x Fipt With Brass Thread Insert



802-101BR		3/4	X1/2		50	0	086	39	.03
Not intended to d	convey c	or dispense	water for	huma	an con	sumptic	n throu	gh drinkin	g or
cooking									

Union





Not intended to convey	or dispense	water for h	human	consumption	through	drinking	or
cooking							

235 psi Maximum Internal Pressure Rating @ 73°F (23°C)								
859-007BR	3/4	10	40	086	50.53			
859-010BR	1	10	0	086	62.36			
859-012BR	1-1/4	5	20	086	107.63			
859-015BR	1-1/2	5	0	086	142.44			
859-020BR	2	5	0	086	189.30			

Not intended to convey or dispense water for human consumption through drinking or

Transition 90° Ell Soc x Fipt With Brass Thread Insert

807-005BR 1/2 20 240 086 27.47 807-007BR 3/4 20 160 086 48.63

Not intended to convey or dispense water for human consumption through drinking or

Union

Soc x Fipt with Brass Thread Insert & EPDM O-ring Seal



Soc x Fipt With Brass Thread Insert

Not intended to convey or dispense water for human consumpti			
cooking	on thro	through	h drinking or

235 noi Maximum Internal Proceure Pating @ 73°F (23°C)

235 psi Maximum internal Pressure Rating @ 73 F (23 C)									
899-007BR	3/4	10	40	086	45.56				
899-010BR	1	10	0	086	61.45				
899-012BR	1-1/4	5	20	086	103.33				
899-015BR	1-1/2	5	0	086	136.76				
899-020BR	2	5	0	086	182.30				

Not intended to convey or dispense water for human consumption through drinking or

Transition Female Adapter

Transition Reducing 90° EII



835-005BR	1/2	25	150	086	23.72
835-007BR	3/4	25	150	086	34.07
835-010BR	1	15	90	086	58.71
835-012BR	1-1/4	15	60	086	96.68
835-015BR	1-1/2	10	40	086	127.01
835-020BR	2	8	32	086	157.31

Not intended to convey or dispense water for human consumption through drinking or cooking

Transition Female Adapter Spig x Fipt With Brass Thread Insert



878-005BR	1/2	25	150	086	19.95
878-010BR	1	15	90	086	63.47
Not intended to convey	or disponso water for hun	oon cor	acumatic	n throu	ah drinkina or

Not intended to convey or dispense water for human consumption through drinking or

Transition Reducing Female Adapter Soc x Fipt With Brass Thread Insert



835-101BR			3/4X1/2				50		0	086		35.22	
Not intended to	convey	or	dispense	water	for	hum	an	con	sumptio	n throu	ıgh	drinking	or

Transition Female Adapter

Soc x Fipt With 316 Stainless Steel Thread Insert



835-005SS	1/2	25	300	086	46.48
835-007SS	3/4	15	90	086	66.80
835-010SS	1	15	90	086	113.67
835-012SS	1-1/4	15	60	086	189.84
835-015SS	1-1/2	10	40	086	247.99
835-020SS	2	8	32	086	318.13