



Transition Fittings & Adapters PVC Gray Special Reinforced (SR) Fittings

Part Number	Size	Std Pk	Mstr Ctn	Disc Code	Price Each
-------------	------	--------	----------	-----------	------------

Encapsulated Special Reinforced Female Adapter (continued)

Soc x ESR Fipt

835-003ESR	3/8	25	300	086	7.69
835-005ESR	1/2	25	300	086	4.77
835-007ESR	3/4	25	300	086	7.04
835-010ESR	1	25	200	086	9.32
835-012ESR	1-1/4	10	80	086	15.04
835-015ESR	1-1/2	10	80	086	21.73
835-020ESR	2	10	0	086	32.30

Special Reinforced Spigot Female Adapter

Spig x SR Fipt - Stainless Steel Collar



878-005SR	1/2	50	600	086	3.88
878-007SR	3/4	25	300	086	4.57
878-010SR	1	50	0	086	7.04
878-012SR	1-1/4	25	0	086	11.21
878-015SR	1-1/2	25	0	086	13.44
878-020SR	2	15	0	086	22.37
878-030SR	3	5	0	086	41.12
878-040SR	4	5	0	086	69.81

Encapsulated Special Reinforced Spigot Female Adapter

Spig x ESR Fipt



878-005ESR	1/2	50	600	086	5.29
878-007ESR	3/4	25	300	086	7.29
878-010ESR	1	50	0	086	10.00
878-012ESR	1-1/4	25	0	086	15.39
878-015ESR	1-1/2	25	0	086	21.85
878-020ESR	2	15	0	086	32.93

Special Reinforced Reducing Female Adapter

Soc x SR Fipt - Stainless Steel Collar



835-074SR	1/2X3/4	50	400	086	4.29
835-101SR	3/4X1/2	50	400	086	4.29
835-102SR	3/4X1	50	0	086	6.38
835-130SR	1X1/2	50	0	086	6.38
835-131SR	1X3/4	25	200	086	6.38

Special Reinforced Reducing Spigot Female Adapter

Spig x SR Fipt - Stainless Steel Collar



878-072SR	1/2X1/4	25	450	086	10.78
878-098SR	3/4X1/4	50	400	086	14.86
878-128SR	1X1/4	50	400	086	15.32

Reinforced Male Adapter

R Mipt x Soc - Stainless Steel Sleeve



836-005R	1/2	25	150	086	3.65
836-007R	3/4	25	300	086	4.00
836-010R	1	10	60	086	7.01

Special Reinforced Reducer Bushing

Mipt x SR Fipt - Stainless Steel Collar



839-128SR	1X1/4	25	150	086	5.68
839-209SR	1-1/2X1/2	25	200	086	8.30
839-210SR	1-1/2X3/4	25	100	086	8.30
839-247SR	2X1/2	10	120	086	12.19
839-248SR	2X3/4	10	120	086	12.19
839-249SR	2X1	10	120	086	12.19
839-420SR	4X2	6	0	086	46.16

Part Number	Size	Std Pk	Mstr Ctn	Disc Code	Price Each
-------------	------	--------	----------	-----------	------------

Special Reinforced Reducer Bushing Flush Style

Spig x SR Fipt - Stainless Steel Collar



838-128SR	1X1/4	25	300	086	3.14
838-166SR	1-1/4X1/2	25	100	086	5.74
838-207SR	1-1/2X1/4	25	200	086	8.01
838-209SR	1-1/2X1/2	10	60	086	8.01
838-210SR	1-1/2X3/4	25	200	086	8.01
838-247SR	2X1/2	10	80	086	9.80
838-248SR	2X3/4	10	80	086	9.80
838-249SR	2X1	10	80	086	9.80
838-334SR	3X3/4	10	0	086	38.36
838-335SR	3X1	10	0	086	38.36
838-336SR	3X1-1/4	10	0	086	38.36
838-337SR	3X1-1/2	10	0	086	38.36
838-528SR	6X2	5	0	086	67.91
838-530SR	6X3	5	0	086	61.13
838-532SR	6X4	5	0	086	67.91

Special Reinforced Cap

SR Fipt - Stainless Steel Collar



848-002SR	1/4	25	500	086	3.83
848-003SR	3/8	25	450	086	3.83
848-005SR	1/2	50	300	086	4.19
848-007SR	3/4	25	300	086	5.37
848-030SR	3	5	0	086	33.10

Special Reinforced Union 2000

Soc x SR Fipt with EPDM O-ring Seal - Stainless Steel Collar



235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8099-005SR	1/2	20	160	086	7.60
8099-007SR	3/4	20	80	086	10.83
8099-010SR	1	15	90	086	13.97
8099-012SR	1-1/4	10	0	086	24.30
8099-015SR	1-1/2	10	0	086	31.49
8099-020SR	2	5	0	086	50.68
8099-025SR	2-1/2	5	0	086	108.41
8099-030SR	3	5	0	086	120.69
8099-040SR	4	4	0	086	137.74
8099-060SR	6	1	0	086	306.10

Special Reinforced Union 2000

Soc x SR Fipt with Viton® O-ring Seal - Stainless Steel Collar



235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8059-005SR	1/2	20	160	086	7.90
8059-007SR	3/4	20	80	086	10.88
8059-010SR	1	15	90	086	14.14
8059-012SR	1-1/4	10	0	086	27.02
8059-015SR	1-1/2	10	0	086	33.34
8059-020SR	2	5	0	086	50.91
8059-025SR	2-1/2	5	0	086	109.43
8059-030SR	3	5	0	086	124.40
8059-040SR	4	4	0	086	142.83
8059-060SR	6	1	0	086	317.40

Special Reinforced Union 2000

SR Fipt with EPDM O-ring Seal - Stainless Steel Collar



235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8098-005SR	1/2	20	120	086	8.01
8098-007SR	3/4	20	80	086	10.91
8098-010SR	1	15	90	086	14.44