

Schedule 80 CPVC Industrial Products & Accessories
CPVC Schedule 80 Fittings



Part Number	Size	Std Pk	Mstr Ctn	Disc Code	Price Each
-------------	------	--------	----------	-----------	------------

15° Ell (continued)

Soc

818-030CF	3	1	35	097	118.47
818-040CF	4	1	18	097	154.71
818-060CF	6	1	8	097	296.94
818-080CF	8	1	3	097	564.27
818-100CF	10	1	2	097	936.67
818-120CF	12	1	0	097	1233.68
818-140CF	14	1	0	097	2619.50
818-160CF	16	1	0	097	3687.61
818-180CF	18	1	0	097	5346.00

11-1/4° Ell

Soc



811-005CF	1/2	1	52	097	30.85
811-007CF	3/4	1	20	097	31.80
811-010CF	1	1	50	097	43.98
811-012CF	1-1/4	1	26	097	46.90
811-015C	1-1/2	25	0	090	35.07
811-020C	2	10	0	090	42.90
811-025CF	2-1/2	1	25	097	106.22
811-030C	3	10	0	090	112.64
811-040C	4	4	0	090	154.62
811-060CF	6	1	5	097	296.94
811-080CF	8	1	3	097	564.27
811-100CF	10	1	2	097	936.67
811-120CF	12	1	2	097	1233.68
811-140CF	14	1	0	097	2619.50
811-160CF	16	1	0	097	3687.61
811-180CF	18	1	0	097	5346.00

Wye

Soc



1/2" - 2" - 235 psi Maximum Internal Pressure Rating @ 73°F (23°C)
2-1/2" - 6" - 150 psi Maximum Internal Pressure Rating @ 73°F (23°C)
8" - Larger & All Fabricated Sizes - 100 psi Maximum Internal Pressure Rating @ 73°F (23°C)

875-005C	1/2	25	100	090	15.59
875-007C	3/4	25	0	090	16.10
875-010C	1	20	0	090	27.13
875-012C	1-1/4	20	0	090	41.09
875-015C	1-1/2	20	0	090	44.17
875-020C	2	10	0	090	108.16
875-025C ¹	2-1/2	4	0	090	762.43
875-030C	3	5	0	090	533.30
875-040C	4	4	0	090	563.83
875-060C	6	3	0	090	771.70
875-080C	8	1	0	090	1317.89
875-080CF*	8	1	0	097	1152.68
875-100CF*	10	1	0	097	1980.16
875-120CF*	12	1	0	097	2758.09
875-140CF*	14	1	0	097	9589.14
875-160CF*	16	1	0	097	12027.90
875-180CF*	18	1	0	097	17453.89

¹ Sized with Bushing

* An asterisk (*) appearing after a fabricated fitting part number indicates the item is fiberglass reinforced.

Part Number	Size	Std Pk	Mstr Ctn	Disc Code	Price Each
-------------	------	--------	----------	-----------	------------

Reducing Wye

Soc



1/2" - 2" - 235 psi Maximum Internal Pressure Rating @ 73°F (23°C)
3" - 6" - 150 psi Maximum Internal Pressure Rating @ 73°F (23°C)
8" - Larger & All Fabricated Sizes - 100 psi Maximum Internal Pressure Rating @ 73°F (23°C)

875-101C ¹	3/4X1/2	25	0	090	23.02
875-130C ¹	1X1/2	20	0	090	37.93
875-131C ¹	1X3/4	20	0	090	37.93
875-166C ¹	1-1/4X1/2	20	0	090	69.14
875-167C ¹	1-1/4X3/4	20	0	090	69.14
875-168C ¹	1-1/4X1	20	0	090	69.14
875-209C ¹	1-1/2X1/2	20	0	090	75.84
875-210C ¹	1-1/2X3/4	20	0	090	75.84
875-211C ¹	1-1/2X1	20	0	090	75.84
875-212C ¹	1-1/2X1-1/4	20	0	090	75.84
875-247C ¹	2X1/2	10	0	090	150.06
875-248C ¹	2X3/4	10	0	090	150.06
875-249C ¹	2X1	10	0	090	150.06
875-250C ¹	2X1-1/4	10	0	090	150.06
875-251C ¹	2X1-1/2	10	0	090	150.06
875-335C ¹	3X1	5	0	090	617.26
875-336C ¹	3X1-1/4	5	0	090	617.26
875-337C ¹	3X1-1/2	5	0	090	617.26
875-338C ¹	3X2	4	0	090	617.26
875-339C ¹	3X2-1/2	5	0	090	617.26
875-420C	4X2	4	0	090	624.18
875-422C ¹	4X3	4	0	090	624.18
875-528C ¹	6X2	5	0	090	790.59
875-528CF*	6X2	1	3	097	620.28
875-530C ¹	6X3	5	0	090	790.44
875-530CF*	6X3	1	2	097	689.64
875-532C	6X4	5	0	090	603.56
875-578C ¹	8X2	1	0	090	2090.67
875-578CF*	8X2	1	2	097	833.82
875-579CF*	8X2-1/2	1	2	097	873.94
875-580C ¹	8X3	1	0	090	2090.67
875-580CF*	8X3	1	2	097	854.56
875-582C ¹	8X4	1	0	090	2090.67
875-582CF*	8X4	1	2	097	877.67
875-585C ¹	8X6	1	0	090	1915.95
875-585CF*	8X6	1	0	097	988.98
875-621CF*	10X2	1	0	097	928.89
875-623CF*	10X3	1	0	097	988.88
875-624CF*	10X4	1	0	097	1208.48
875-626C	10X6	1	0	091	2159.80
875-626CF*	10X6	1	0	097	1372.14
875-628C	10X8	1	0	091	2274.03
875-628CF*	10X8	1	0	097	1615.82
875-661CF*	12X2	1	0	097	1532.59
875-663CF*	12X3	1	0	097	1610.11
875-664CF*	12X4	1	0	097	1836.67
875-666CF*	12X6	1	0	097	1910.63
875-668CF*	12X8	1	0	097	2016.67
875-670CF*	12X10	1	0	097	2482.91
875-694CF*	14X4	1	0	097	4110.98
875-696CF*	14X6	1	0	097	4515.36
875-698CF*	14X8	1	0	097	4884.46
875-702CF*	14X12	1	0	097	5950.41
875-754CF*	16X4	1	0	097	5172.83
875-756CF*	16X6	1	0	097	5446.73
875-758CF*	16X8	1	0	097	6324.47
875-760CF*	16X10	1	0	097	7107.81
875-762CF*	16X12	1	0	097	7708.76