


**Schedule 80 PVC Industrial Products & Accessories  
Tank Adapters**



Part Number	Size	Std Pk	Mstr Ctn	Disc Code	Price Each
-------------	------	--------	----------	-----------	------------

**PVC Spigot Tank Adapter with EPDM Gasket Spig**



150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8173E-005	1/2	25	0	100	33.62
8173E-007	3/4	25	0	100	37.93
8173E-010	1	25	0	100	45.73
8173E-015	1-1/2	20	0	100	59.21
8173E-020	2	15	0	100	87.13

Install with threaded end, gasket and one nut inside tank. Use thread sealant on internal nut.

**PVC Self Aligning Tank Adapter with Neoprene Gasket**



Fipt

75 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8172SA-010	1	5	0	100	140.46
8172SA-020	2	4	0	100	218.41
8172SA-030	3	2	0	100	330.48

**PVC Self Aligning Tank Adapter with EPDM Gasket**



Fipt

75 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8172ESA-010	1	5	0	100	147.81
8172ESA-020	2	4	0	100	224.30
8172ESA-030	3	2	0	100	347.98

**PVC Self Aligning Tank Adapter with Viton® Gasket**



Fipt

75 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8172VSA-010	1	5	0	100	382.99
8172VSA-020	2	4	0	100	543.73
8172VSA-030	3	2	0	100	854.35

**PVC New Style Standard Tank Adapters with Neoprene Gaskets**



Soc

150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8170-002	1/4	25	150	100	32.62
8170-003	3/8	25	150	100	32.62
8170-005	1/2	25	0	100	32.62
8170-007	3/4	25	0	100	37.19
8170-010	1	25	0	100	41.32
8170-012	1-1/4	20	0	100	49.78
8170-015	1-1/2	20	0	100	54.62
8170-020	2	15	0	100	80.96
8170-025	2-1/2	4	0	100	125.11
8170-030	3	4	0	100	148.93
8170-040	4	2	0	100	293.37
8170-060	6	1	0	100	569.45
8170-080	8	1	0	100	1263.73

**PVC New Style Standard Tank Adapters with EPDM Gaskets**



Soc

150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8170E-002	1/4	25	150	100	33.62
8170E-003	3/8	25	150	100	33.62
8170E-005	1/2	25	0	100	33.62
8170E-007	3/4	25	0	100	37.93
8170E-010	1	25	0	100	45.73
8170E-012	1-1/4	20	0	100	54.36
8170E-015	1-1/2	20	0	100	59.21


Part Number	Size	Std Pk	Mstr Ctn	Disc Code	Price Each
-------------	------	--------	----------	-----------	------------

**PVC New Style Standard Tank Adapters with EPDM Gaskets (continued)**

Soc

8170E-020	2	15	0	100	87.13
8170E-025	2-1/2	4	0	100	145.22
8170E-030	3	4	0	100	154.49
8170E-040	4	2	0	100	300.78
8170E-060	6	1	0	100	589.89
8170E-080	8	1	0	100	1310.59

**PVC New Style Standard Tank Adapters with Viton® Gaskets**




Soc

150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8170V-002	1/4	25	150	100	55.43
8170V-003	3/8	25	150	100	55.43
8170V-005	1/2	25	0	100	55.43
8170V-007	3/4	25	0	100	60.77
8170V-010	1	25	0	100	72.77
8170V-012	1-1/4	20	0	100	76.73
8170V-015	1-1/2	20	0	100	84.51
8170V-020	2	15	0	100	138.66
8170V-025	2-1/2	4	0	100	209.01
8170V-030	3	4	0	100	248.82
8170V-040	4	2	0	100	622.45
8170V-060	6	1	0	100	1119.54
8170V-080	8	1	0	100	2084.04

**PVC New Style Standard Tank Adapters with Neoprene Gasket**




Soc x Fipt

150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8171-002	1/4	25	150	100	32.62
8171-003	3/8	25	200	100	32.62
8171-005	1/2	25	0	100	32.62
8171-007	3/4	25	0	100	37.19
8171-010	1	25	0	100	41.32
8171-012	1-1/4	20	0	100	49.78
8171-015	1-1/2	20	0	100	54.62
8171-020	2	15	0	100	80.96
8171-025	2-1/2	4	0	100	125.11
8171-030	3	4	0	100	148.93
8171-040	4	2	0	100	293.37
8171-060	6	1	0	100	569.45

**PVC New Style Standard Tank Adapters with EPDM Gaskets**



Soc x Fipt

150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8171E-002	1/4	25	150	100	33.62
8171E-003	3/8	25	200	100	33.62
8171E-005	1/2	25	0	100	33.62
8171E-007	3/4	25	0	100	37.93
8171E-010	1	25	0	100	45.73
8171E-012	1-1/4	20	0	100	54.36
8171E-015	1-1/2	20	0	100	59.21
8171E-020	2	15	0	100	87.13
8171E-025	2-1/2	4	0	100	145.22
8171E-030	3	4	0	100	154.49
8171E-040	4	2	0	100	300.78
8171E-060	6	1	0	100	589.89