



**Schedule 80 PVC Industrial Products & Accessories
Tank Adapters**

Part Number	Size	Std Pk	Mstr Ctn	Disc Code	Price Each
-------------	------	--------	----------	-----------	------------

PVC New Style Standard Tank Adapters with Viton® Gaskets

Soc x Fipt

150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8171V-002	1/4	25	150	100	55.43
8171V-003	3/8	25	200	100	55.43
8171V-005	1/2	25	0	100	55.43
8171V-007	3/4	25	0	100	60.77
8171V-010	1	25	0	100	72.77
8171V-012	1-1/4	20	0	100	76.73
8171V-015	1-1/2	20	0	100	84.51
8171V-020	2	15	0	100	138.66
8171V-025	2-1/2	4	0	100	209.01
8171V-030	3	4	0	100	248.82
8171V-040	4	2	0	100	622.45
8171V-060	6	1	0	100	1119.54



PVC New Style Special Reinforced (SR) Threaded Tank Adapters with Neoprene Gaskets

Soc x SR Fipt - Stainless Steel Collar

150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8171-002SR	1/4	25	150	100	33.80
8171-003SR	3/8	25	200	100	33.80
8171-005SR	1/2	25	0	100	33.80
8171-007SR	3/4	25	0	100	39.16
8171-010SR	1	25	0	100	44.10
8171-012SR	1-1/4	20	0	100	54.21
8171-015SR	1-1/2	20	0	100	62.22
8171-020SR	2	15	0	100	89.17
8171-025SR	2-1/2	4	0	100	143.57
8171-030SR	3	4	0	100	170.90
8171-040SR	4	2	0	100	316.12
8171-060SR	6	1	0	100	591.63



PVC New Style Special Reinforced (SR) Threaded Tank Adapters with EPDM Gaskets

Soc x SR Fipt - Stainless Steel Collar

150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8171E-002SR	1/4	25	150	100	34.99
8171E-003SR	3/8	25	200	100	34.99
8171E-005SR	1/2	25	0	100	34.99
8171E-007SR	3/4	25	0	100	39.90
8171E-010SR	1	25	0	100	48.51
8171E-012SR	1-1/4	20	0	100	58.77
8171E-015SR	1-1/2	20	0	100	66.79
8171E-020SR	2	15	0	100	95.34
8171E-025SR	2-1/2	4	0	100	148.23
8171E-030SR	3	4	0	100	176.47
8171E-040SR	4	2	0	100	323.55
8171E-060SR	6	1	0	100	611.98



PVC New Style Special Reinforced (SR) Threaded Tank Adapters with Viton® Gaskets

Soc x SR Fipt - Stainless Steel Collar

150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8171V-002SR	1/4	25	150	100	56.80
8171V-003SR	3/8	25	200	100	56.80
8171V-005SR	1/2	25	0	100	56.80
8171V-007SR	3/4	25	0	100	62.33
8171V-010SR	1	25	0	100	76.83
8171V-012SR	1-1/4	20	0	100	86.03
8171V-015SR	1-1/2	20	0	100	96.98
8171V-020SR	2	15	0	100	148.51
8171V-025SR	2-1/2	4	0	100	226.10



Part Number	Size	Std Pk	Mstr Ctn	Disc Code	Price Each
-------------	------	--------	----------	-----------	------------

PVC New Style Special Reinforced (SR) Threaded Tank Adapters with Viton® Gaskets (continued)

Soc x SR Fipt - Stainless Steel Collar


8171V-030SR	3	4	0	100	269.15
8171V-040SR	4	2	0	100	646.67
8171V-060SR	6	2	0	100	1146.10

PVC New Style Standard Tank Adapters with Neoprene Gaskets

Fipt

150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8172-002	1/4	25	150	100	43.81
8172-003	3/8	25	200	100	43.81
8172-005	1/2	25	0	100	43.81
8172-007	3/4	25	0	100	48.05
8172-010	1	25	0	100	52.55
8172-012	1-1/4	20	0	100	70.06
8172-015	1-1/2	20	0	100	76.37
8172-020	2	15	0	100	100.57
8172-025	2-1/2	4	0	100	147.20
8172-030	3	4	0	100	175.21
8172-040	4	2	0	100	328.33
8172-060	6	1	0	100	657.06




PVC New Style Standard Tank Adapters with EPDM Gaskets

Fipt

150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8172E-002	1/4	25	150	100	45.11
8172E-003	3/8	25	200	100	45.11
8172E-005	1/2	25	0	100	45.11
8172E-007	3/4	25	0	100	48.99
8172E-010	1	25	0	100	58.20
8172E-012	1-1/4	50	0	100	76.50
8172E-015	1-1/2	20	0	100	82.74
8172E-020	2	15	0	100	108.23
8172E-025	2-1/2	4	0	100	152.68
8172E-030	3	4	0	100	181.79
8172E-040	4	2	0	100	336.70
8172E-060	6	1	0	100	680.67




PVC New Style Standard Tank Adapters with Viton® Gaskets

Fipt

150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8172V-002	1/4	25	150	100	67.78
8172V-003	3/8	25	200	100	67.78
8172V-005	1/2	25	0	100	67.78
8172V-007	3/4	25	0	100	72.24
8172V-010	1	25	0	100	82.51
8172V-012	1-1/4	20	0	100	93.63
8172V-015	1-1/2	20	0	100	106.87
8172V-020	2	15	0	100	158.35
8172V-025	2-1/2	4	0	100	226.17
8172V-030	3	4	0	100	269.32
8172V-040	4	2	0	100	656.38
8172V-060	6	1	0	100	1255.86



PVC New Style Special Reinforced (SR) Threaded Tank Adapters with Neoprene Gaskets

Fipt x SR Fipt - Stainless Steel Collar

150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8172-002SR	1/4	25	150	100	45.19
8172-003SR	3/8	25	200	100	45.19
8172-005SR	1/2	25	0	100	45.19

