

Transition Fittings & Adapters PVC Gray Special Reinforced (SR) Fittings



Part Number	Size	Std Pk	Mstr Ctn	Disc Code	Price Each
-------------	------	--------	----------	-----------	------------

Special Reinforced Union 2000 (continued)

SR Fipt with EPDM O-ring Seal - Stainless Steel Collar

8098-012SR	1-1/4	10	0	086	26.85
8098-015SR	1-1/2	10	0	086	33.77
8098-020SR	2	5	0	086	53.07
8098-025SR	2-1/2	5	0	086	107.11
8098-030SR	3	5	0	086	126.32
8098-040SR	4	4	0	086	145.02
8098-060SR	6	1	0	086	322.30

Special Reinforced Union 2000

SR Fipt with Viton® O-ring Seal - Stainless Steel Collar



235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8058-005SR	1/2	20	120	086	8.13
8058-007SR	3/4	20	80	086	11.01
8058-010SR	1	15	90	086	14.73
8058-012SR	1-1/4	10	0	086	28.06
8058-015SR	1-1/2	10	0	086	34.53
8058-020SR	2	5	0	086	53.62
8058-025SR	2-1/2	5	0	086	112.12
8058-030SR	3	5	0	086	127.54
8058-040SR	4	4	0	086	150.14
8058-060SR	6	1	0	086	333.63

Special Reinforced Union (Old Style)

Soc x SR Fipt with EPDM O-ring Seal - Stainless Steel Collar



235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

899-002SR	1/4	25	150	086	14.35
899-003SR	3/8	25	100	086	14.35
899-005SR	1/2	10	60	086	7.60
899-007SR	3/4	10	40	086	10.83
899-010SR	1	10	40	086	13.97
899-012SR	1-1/4	5	20	086	24.30
899-015SR	1-1/2	5	0	086	31.49
899-020SR	2	5	0	086	50.68
899-030SR	3	5	0	086	120.69
899-040SR	4	4	0	086	137.74

Special Reinforced Union (Old Style)

Soc x SR Fipt with Viton® O-ring Seal - Stainless Steel Collar



235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

859-005SR	1/2	10	60	086	7.90
859-007SR	3/4	10	40	086	10.88
859-010SR	1	10	40	086	14.14
859-012SR	1-1/4	5	20	086	27.02
859-015SR	1-1/2	5	0	086	33.34
859-020SR	2	5	0	086	50.91
859-030SR	3	5	0	086	124.40
859-040SR	4	4	0	086	142.83

Special Reinforced Flange One Piece Threaded

SR Fipt - Stainless Steel Collar



150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

852-005SR	1/2	25	0	086	11.31
852-007SR	3/4	25	0	086	13.29
852-010SR	1	15	0	086	14.53
852-012SR	1-1/4	15	0	086	20.02
852-015SR	1-1/2	15	0	086	21.91
852-020SR	2	10	0	086	22.44
852-025SR	2-1/2	10	0	086	51.39
852-030SR	3	10	0	086	52.91
852-040SR	4	5	0	086	99.46

Part Number	Size	Std Pk	Mstr Ctn	Disc Code	Price Each
-------------	------	--------	----------	-----------	------------

PVC New Style Special Reinforced (SR) Threaded Tank Adapters with Neoprene Gaskets



Soc x SR Fipt - Stainless Steel Collar

150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8171-002SR	1/4	25	150	100	33.80
8171-003SR	3/8	25	200	100	33.80
8171-005SR	1/2	25	0	100	33.80
8171-007SR	3/4	25	0	100	39.16
8171-010SR	1	25	0	100	44.10
8171-012SR	1-1/4	20	0	100	54.21
8171-015SR	1-1/2	20	0	100	62.22
8171-020SR	2	15	0	100	89.17
8171-025SR	2-1/2	4	0	100	143.57
8171-030SR	3	4	0	100	170.90
8171-040SR	4	2	0	100	316.12
8171-060SR	6	1	0	100	591.63

PVC New Style Special Reinforced (SR) Threaded Tank Adapters with EPDM Gaskets



Soc x SR Fipt - Stainless Steel Collar

150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8171E-002SR	1/4	25	150	100	34.99
8171E-003SR	3/8	25	200	100	34.99
8171E-005SR	1/2	25	0	100	34.99
8171E-007SR	3/4	25	0	100	39.90
8171E-010SR	1	25	0	100	48.51
8171E-012SR	1-1/4	20	0	100	58.77
8171E-015SR	1-1/2	20	0	100	66.79
8171E-020SR	2	15	0	100	95.34
8171E-025SR	2-1/2	4	0	100	148.23
8171E-030SR	3	4	0	100	176.47
8171E-040SR	4	2	0	100	323.55
8171E-060SR	6	1	0	100	611.98

PVC New Style Special Reinforced (SR) Threaded Tank Adapters with Viton® Gaskets



Soc x SR Fipt - Stainless Steel Collar

150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8171V-002SR	1/4	25	150	100	56.80
8171V-003SR	3/8	25	200	100	56.80
8171V-005SR	1/2	25	0	100	56.80
8171V-007SR	3/4	25	0	100	62.33
8171V-010SR	1	25	0	100	76.83
8171V-012SR	1-1/4	20	0	100	86.03
8171V-015SR	1-1/2	20	0	100	96.98
8171V-020SR	2	15	0	100	148.51
8171V-025SR	2-1/2	4	0	100	226.10
8171V-030SR	3	4	0	100	269.15
8171V-040SR	4	2	0	100	646.67
8171V-060SR	6	2	0	100	1146.10

PVC New Style Special Reinforced (SR) Threaded Tank Adapters with Neoprene Gaskets



Fipt x SR Fipt - Stainless Steel Collar

150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8172-002SR	1/4	25	150	100	45.19
8172-003SR	3/8	25	200	100	45.19
8172-005SR	1/2	25	0	100	45.19
8172-007SR	3/4	25	0	100	50.03
8172-010SR	1	25	0	100	55.33
8172-012SR	1-1/4	20	0	100	74.51
8172-015SR	1-1/2	20	0	100	83.97
8172-020SR	2	15	0	100	108.80
8172-025SR	2-1/2	4	0	100	165.65