

**Schedule 80 CPVC Industrial Products & Accessories
Tank Adapters**



Part Number	Size	Std Pk	Mstr Ctn	Disc Code	Price Each
-------------	------	--------	----------	-----------	------------

**CPVC New Style Special Reinforced (SR)
Threaded Tank Adapters with Neoprene
Gaskets**



Soc x SR Fipt - Stainless Steel Collar

150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8171-002CSR	1/4	25	150	101	47.31
8171-003CSR	3/8	25	200	101	47.31
8171-005CSR	1/2	25	0	101	47.31
8171-007CSR	3/4	25	0	101	56.62
8171-010CSR	1	25	0	101	64.05
8171-012CSR	1-1/4	20	0	101	82.62
8171-015CSR	1-1/2	20	0	101	92.76
8171-020CSR	2	15	0	101	128.27
8171-025CSR	2-1/2	4	0	101	195.12
8171-030CSR	3	4	0	101	232.24
8171-040CSR	4	2	0	101	373.24
8171-060CSR	6	1	0	101	985.77

**CPVC New Style Special Reinforced (SR)
Threaded Tank Adapters with EPDM Gaskets**



Soc x SR Fipt - Stainless Steel Collar

150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8171E-002CSR	1/4	25	150	101	53.62
8171E-003CSR	3/8	25	200	101	53.62
8171E-005CSR	1/2	25	0	101	53.62
8171E-007CSR	3/4	25	0	101	60.60
8171E-010CSR	1	25	0	101	72.46
8171E-012CSR	1-1/4	20	0	101	90.55
8171E-015CSR	1-1/2	20	0	101	97.97
8171E-020CSR	2	15	0	101	138.50
8171E-025CSR	2-1/2	4	0	101	203.53
8171E-030CSR	3	4	0	101	242.30
8171E-040CSR	4	2	0	101	388.48
8171E-060CSR	6	2	0	101	1025.93

**CPVC New Style Special Reinforced (SR)
Threaded Tank Adapters with Viton® Gaskets**



Soc x SR Fipt - Stainless Steel Collar

150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8171V-002CSR	1/4	25	150	101	69.86
8171V-003CSR	3/8	25	200	101	69.86
8171V-005CSR	1/2	25	0	101	69.86
8171V-007CSR	3/4	25	0	101	80.76
8171V-010CSR	1	25	0	101	93.95
8171V-012CSR	1-1/4	20	0	101	116.46
8171V-015CSR	1-1/2	20	0	101	124.36
8171V-020CSR	2	15	0	101	185.18
8171V-025CSR	2-1/2	4	0	101	272.90
8171V-030CSR	3	4	0	101	324.95
8171V-040CSR	4	2	0	101	693.84
8171V-060CSR	6	2	0	101	1713.06

**CPVC New Style Standard Tank Adapters with
Neoprene Gaskets**



Fipt

150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8172-002C	1/4	25	150	101	61.30
8172-003C	3/8	25	200	101	61.30
8172-005C	1/2	25	0	101	61.30
8172-007C	3/4	25	0	101	70.78
8172-010C	1	25	0	101	77.43
8172-012C	1-1/4	20	0	101	109.32
8172-015C	1-1/2	20	0	101	119.49
8172-020C	2	15	0	101	148.93
8172-025C	2-1/2	4	0	101	209.59


Part Number	Size	Std Pk	Mstr Ctn	Disc Code	Price Each
-------------	------	--------	----------	-----------	------------

**CPVC New Style Standard Tank Adapters with
Neoprene Gaskets (continued)**

Fipt

8172-030C	3	4	0	101	249.50
8172-040C	4	2	0	101	394.21
8172-060C	6	1	0	101	1095.10

**CPVC New Style Standard Tank Adapters with
EPDM Gaskets**




Fipt

150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8172E-002C	1/4	25	150	101	63.72
8172E-003C	3/8	25	200	101	63.72
8172E-005C	1/2	25	0	101	63.72
8172E-007C	3/4	25	0	101	75.13
8172E-010C	1	25	0	101	80.95
8172E-012C	1-1/4	20	0	101	113.72
8172E-015C	1-1/2	20	0	101	129.78
8172E-020C	2	15	0	101	160.40
8172E-025C	2-1/2	4	0	101	235.81
8172E-030C	3	4	0	101	280.76
8172E-040C	4	2	0	101	467.43
8172E-060C	6	1	0	101	1111.63

**CPVC New Style Standard Tank Adapters with
Viton® Gaskets**




Fipt

150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8172V-002C	1/4	25	150	101	98.60
8172V-003C	3/8	25	200	101	98.60
8172V-005C	1/2	25	0	101	98.60
8172V-007C	3/4	25	0	101	111.14
8172V-010C	1	25	0	101	127.89
8172V-012C	1-1/4	20	0	101	156.88
8172V-015C	1-1/2	20	0	101	162.33
8172V-020C	2	15	0	101	252.87
8172V-025C	2-1/2	4	0	101	358.84
8172V-030C	3	4	0	101	427.16
8172V-040C	4	2	0	101	1123.33
8172V-060C	6	1	0	101	2058.91

**CPVC New Style Special Reinforced (SR)
Threaded Tank Adapters with Neoprene
Gaskets**




Fipt x SR Fipt - Stainless Steel Collar

150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8172-002CSR	1/4	25	150	101	62.67
8172-003CSR	3/8	25	200	101	62.67
8172-005CSR	1/2	25	0	101	62.67
8172-007CSR	3/4	25	0	101	72.78
8172-010CSR	1	25	0	101	80.19
8172-012CSR	1-1/4	20	0	101	113.76
8172-015CSR	1-1/2	20	0	101	127.09
8172-020CSR	2	15	0	101	157.13
8172-025CSR	2-1/2	4	0	101	228.05
8172-030CSR	3	4	0	101	271.49
8172-040CSR	4	2	0	101	416.98
8172-060CSR	6	2	0	101	1117.17

**CPVC New Style Special Reinforced (SR)
Threaded Tank Adapters with EPDM Gaskets**



Fipt x SR Fipt - Stainless Steel Collar

150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8172E-002CSR	1/4	25	150	101	65.12
8172E-003CSR	3/8	25	200	101	65.12
8172E-005CSR	1/2	25	0	101	65.12