

Schedule 80 PVC Industrial Products & Accessories
PVC Schedule 80 Fittings



Part Number	Size	Std Pk	Mstr Ctn	Disc Code	Price Each
-------------	------	--------	----------	-----------	------------

22-1/2° EII (continued)

Soc

816-060	6	4	0	080	180.21
816-060F	6	1	8	083	99.33
816-080	8	4	0	080	390.78
816-080F	8	1	4	083	162.59
816-100F	10	1	2	083	288.16
816-120F	12	1	2	083	421.16
816-140F	14	1	0	083	644.76
816-160F	16	1	0	083	861.86
816-180F	18	1	0	083	1112.61
816-200F	20	1	0	083	1919.49
816-240F	24	1	0	083	2290.13

22-1/2° Street EII

Spig x Soc



842-005	1/2	50	400	080	7.24
842-007	3/4	50	0	080	11.12
842-010	1	50	0	080	17.48
842-012	1-1/4	20	0	080	21.76
842-015	1-1/2	25	0	080	24.67
842-020	2	20	0	080	31.07
842-025	2-1/2	5	0	080	81.11
842-030	3	5	0	080	89.04
842-040	4	4	0	080	156.60
842-040F	4	1	5	084	99.77
842-060	6	6	0	080	222.57
842-060F	6	1	6	083	125.16
842-080	8	1	2	080	481.21
842-080F	8	1	4	083	165.19
842-100F	10	1	0	083	337.59
842-120F	12	1	2	084	439.88

15° EII

Soc



818-005F	1/2	1	25	083	25.41
818-007F	3/4	1	23	083	25.59
818-010F	1	1	20	083	28.00
818-012F	1-1/4	15	0	083	30.32
818-015F	1-1/2	1	25	083	30.74
818-020F	2	1	25	083	33.52
818-025F	2-1/2	1	18	083	109.43
818-030F	3	1	35	083	40.52
818-040F	4	1	20	083	53.13
818-045F	4-1/2	1	18	083	80.93
818-050F	5	1	2	083	97.06
818-060F	6	1	8	083	99.33
818-080F	8	1	4	083	162.59
818-100F	10	1	2	083	288.16
818-120F	12	1	2	083	421.16
818-140F	14	1	0	083	644.76
818-160F	16	1	0	083	861.86
818-180F	18	1	0	083	1112.61
818-200F	20	1	0	083	1919.49
818-240F	24	1	0	083	2290.13

11-1/4° EII

Soc



811-005F	1/2	1	52	083	25.41
811-007F	3/4	1	52	083	25.59
811-010F	1	1	50	083	28.00
811-012F	1-1/4	1	26	083	30.32
811-015	1-1/2	25	0	080	25.35
811-020	2	10	0	080	31.07

Part Number	Size	Std Pk	Mstr Ctn	Disc Code	Price Each
-------------	------	--------	----------	-----------	------------

11-1/4° EII (continued)

Soc

811-025F	2-1/2	1	25	083	37.14
811-030	3	10	0	080	79.65
811-040	4	4	0	080	143.13
811-045F	4-1/2	1	18	083	80.93
811-050F	5	1	4	083	97.06
811-060F	6	1	10	083	99.33
811-080F	8	1	4	083	162.59
811-100F	10	1	2	083	288.16
811-120F	12	1	2	083	421.16
811-140F	14	1	0	083	644.76
811-160F	16	1	0	083	861.86
811-180F	18	1	0	083	1112.61
811-200F	20	1	0	083	1919.49
811-240F	24	1	0	083	2290.13

Wye

Soc



1/2" - 2" - 235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

2-1/2" - 6" - 150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8" - Larger & All Fabricated Sizes - 100 psi Maximum Internal Pressure Rating @ 73°F (23°C)

875-005	1/2	25	100	080	13.00
875-007	3/4	25	0	080	13.66
875-010	1	20	0	080	21.86
875-012	1-1/4	20	0	080	33.52
875-015	1-1/2	20	0	080	33.52
875-020	2	10	0	080	96.16
875-025 ¹	2-1/2	4	0	080	438.14
875-030	3	5	0	080	309.11
875-040	4	4	0	080	383.01
875-050F [*]	5	1	2	083	599.17
875-060	6	2	0	080	523.13
875-080	8	1	0	080	1052.03
875-080F	8	1	0	083	810.63
875-100F [*]	10	1	0	083	1272.04
875-120F [*]	12	1	0	083	1616.81
875-140F [*]	14	1	0	083	2700.31
875-160F [*]	16	1	0	083	3547.19
875-180F [*]	18	1	0	083	3976.87
875-200F [*]	20	1	0	083	5312.34
875-240F [*]	24	1	0	083	7070.04

¹ Sized with Bushing

* An asterisk (*) appearing after a fabricated fitting part number indicates the item is fiberglass reinforced.

Reducing Wye

Soc



1/2" - 2" - 235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

3" - 6" - 150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8" - Larger & All Fabricated Sizes - 100 psi Maximum Internal Pressure Rating @ 73°F (23°C)

875-101 ¹	3/4X1/2	25	0	080	15.77
875-130 ¹	1X1/2	20	0	080	27.65
875-131 ¹	1X3/4	20	0	080	27.65
875-166 ¹	1-1/4X1/2	20	0	080	42.60
875-167 ¹	1-1/4X3/4	20	0	080	42.60
875-168 ¹	1-1/4X1	20	0	080	42.60
875-209 ¹	1-1/2X1/2	20	0	080	45.63
875-210 ¹	1-1/2X3/4	20	0	080	45.63