



Schedule 80 CPVC Industrial Products & Accessories
CPVC Schedule 80 Fittings

Part Number	Size	Std Pk	Mstr Ctn	Disc Code	Price Each
-------------	------	--------	----------	-----------	------------

Encapsulated Special Reinforced (SR) Female Adapter (continued)

Spig x ESR Fipt

878-012CESR	1-1/4	25	0	096	19.71
878-015CESR	1-1/2	25	0	096	25.70
878-020CESR	2	15	0	096	39.72

Special Reinforced Reducing Spigot Female Adapter

Spig x SR Fipt - Stainless Steel Collar



878-072CSR	1/2X1/4	25	450	096	16.28
878-098CSR	3/4X1/4	50	400	096	18.95
878-128CSR	1X1/4	50	400	096	21.21

Male Adapter


Mipt x Soc



836-005C	1/2	25	150	090	7.83
836-007C	3/4	25	150	090	9.55
836-010C	1	20	240	090	16.09
836-131C	1X3/4	25	0	090	33.39
836-012C	1-1/4	10	60	090	23.72
836-015C	1-1/2	10	120	090	32.05
836-020C	2	10	80	090	43.48
836-025C	2-1/2	5	0	090	118.56
836-030C	3	5	0	090	159.32
836-040C	4	5	0	090	269.34
836-060C	6	5	0	090	386.02
836-060CF	6	1	8	097	273.59
836-080CF	8	1	2	097	349.30
836-100CF	10	1	2	097	647.21
836-120CF	12	1	0	097	753.18

Reinforced Male Adapter

R Mipt x Soc - Stainless Steel Sleeve



836-005CR	1/2	25	150	096	8.19
836-007CR	3/4	25	300	096	9.38
836-010CR	1	10	120	096	11.12

Male Adapter


Spig x Mipt



861-005C	1/2	50	300	090	9.54
861-007C	3/4	25	150	090	11.85
861-010C	1	50	0	090	20.10
861-131C	1X3/4	50	200	090	23.48
861-012C	1-1/4	25	200	090	22.80
861-015C	1-1/2	25	0	090	25.17
861-020C	2	25	0	090	29.45

Reducer (T.T.) Bushing Flush Style

Mipt x Fipt



839-041C	1/4X1/8	25	500	090	18.29
839-052C	3/8X1/4	50	450	090	18.29
839-072C	1/2X1/4	50	300	090	18.29
839-073C	1/2X3/8	50	600	090	18.29
839-098C	3/4X1/4	50	300	090	20.16
839-099C	3/4X3/8	50	300	090	20.16
839-101C	3/4X1/2	50	300	090	8.67
839-128C	1X1/4	25	150	090	21.77
839-129C	1X3/8	50	600	090	21.77
839-130C	1X1/2	50	300	090	14.61
839-131C	1X3/4	50	700	090	14.61
839-166C	1-1/4X1/2	25	300	090	29.02

Part Number	Size	Std Pk	Mstr Ctn	Disc Code	Price Each
-------------	------	--------	----------	-----------	------------


Reducer (T.T.) Bushing Flush Style (continued)

Mipt x Fipt

839-167C	1-1/4X3/4	25	300	090	29.02
839-168C	1-1/4X1	25	300	090	28.79
839-209C	1-1/2X1/2	25	200	090	34.95
839-210C	1-1/2X3/4	25	200	090	34.95
839-211C	1-1/2X1	25	200	090	34.95
839-212C	1-1/2X1-1/4	25	200	090	34.68
839-247C	2X1/2	10	60	090	38.66
839-248C	2X3/4	10	60	090	38.66
839-249C	2X1	10	60	090	38.66
839-250C	2X1-1/4	10	120	090	38.66
839-251C	2X1-1/2	10	60	090	34.68
839-292C	2-1/2X2	10	40	090	92.93
839-337C	3X1-1/2	10	0	090	125.02
839-338C	3X2	10	0	090	125.02
839-339C	3X2-1/2	10	0	090	125.02
839-420C	4X2	6	0	090	214.82
839-422C	4X3	6	0	090	214.82
839-530C	6X3	5	0	090	775.51
839-532C	6X4	5	0	090	775.51

Special Reinforced Reducing Bushing


Mipt x SR Fipt - Stainless Steel Collar



839-209CSR	1-1/2X1/2	25	200	096	21.00
839-210CSR	1-1/2X3/4	25	100	096	21.00
839-247CSR	2X1/2	10	120	096	23.21
839-248CSR	2X3/4	10	120	096	23.21
839-249CSR	2X1	10	120	096	23.21
839-420CSR	4X2	6	0	096	128.88

Reducer Bushing Flush Style

Spig x Soc



837-052C	3/8X1/4	50	450	090	12.67
837-072C	1/2X1/4	50	600	090	12.67
837-073C	1/2X3/8	50	300	090	12.67
837-101C	3/4X1/2	50	300	090	6.46
837-129C ¹	1X3/8	50	0	090	22.02
837-130C	1X1/2	50	400	090	10.04
837-131C	1X3/4	50	300	090	10.04
837-166C	1-1/4X1/2	25	300	090	26.66
837-167C	1-1/4X3/4	25	150	090	26.66
837-168C	1-1/4X1	25	150	090	26.66
837-209C	1-1/2X1/2	25	200	090	30.14
837-210C	1-1/2X3/4	25	200	090	30.14
837-211C	1-1/2X1	25	200	090	30.14
837-212C	1-1/2X1-1/4	25	200	090	30.14
837-247C	2X1/2	10	120	090	38.90
837-248C	2X3/4	10	60	090	38.90
837-249C	2X1	10	60	090	38.90
837-250C	2X1-1/4	10	60	090	38.90
837-251C	2X1-1/2	10	60	090	38.90
837-289C ¹	2-1/2X1	5	40	090	66.90
837-290C	2-1/2X1-1/4	10	80	090	47.38
837-291C	2-1/2X1-1/2	10	40	090	47.38
837-292C	2-1/2X2	15	0	090	47.38
837-334C ¹	3X3/4	10	0	090	82.52
837-335C	3X1	10	0	090	72.18
837-336C	3X1-1/4	10	0	090	72.18
837-337C	3X1-1/2	10	0	090	72.18
837-338C	3X2	10	0	090	72.18
837-339C	3X2-1/2	15	0	090	72.18
837-420C	4X2	6	0	090	79.81
837-421C ¹	4X2-1/2	6	0	090	79.81
837-422C	4X3	6	0	090	79.81