



Transition Fittings & Adapters CPVC Gray Brass Thread Fittings

Part Number	Size	Std Pk	Mstr Ctn	Disc Code	Price Each
-------------	------	--------	----------	-----------	------------

Transition Tee

Soc x Fipt With Brass Thread Insert



802-005CBR	1/2	20	160	096	55.46
802-007CBR	3/4	25	0	096	110.91

Not intended to convey or dispense water for human consumption through drinking or cooking

Transition Reducing Tee

Soc x Fipt With Brass Thread Insert



802-101CBR	3/4X1/2	50	0	096	68.74
------------	---------	----	---	-----	-------

Not intended to convey or dispense water for human consumption through drinking or cooking

Transition 90° Ell

Soc x Fipt With Brass Thread Insert



807-005CBR	1/2	20	240	096	48.76
807-007CBR	3/4	20	160	096	85.13

Not intended to convey or dispense water for human consumption through drinking or cooking

Transition Reducing 90° Ell

Soc x Fipt With Brass Thread Insert



807-101CBR	3/4X1/2	20	120	096	60.98
------------	---------	----	-----	-----	-------

Not intended to convey or dispense water for human consumption through drinking or cooking

Transition Female Adapter

Soc x Fipt With Brass Thread Insert



835-005CBR	1/2	25	150	096	30.06
835-007CBR	3/4	15	90	096	62.21
835-010CBR	1	15	90	096	109.17
835-012CBR	1-1/4	15	60	096	178.10
835-015CBR	1-1/2	10	80	096	234.82
835-020CBR	2	8	32	096	293.28

Not intended to convey or dispense water for human consumption through drinking or cooking

Transition Female Adapter

Soc x Fipt With Type 316 Stainless Steel Thread Insert



835-005CSS	1/2	25	150	096	59.02
835-007CSS	3/4	15	90	096	82.40
835-010CSS	1	15	90	096	144.22
835-012CSS	1-1/4	15	0	096	234.38
835-015CSS	1-1/2	10	60	096	305.78
835-020CSS	2	8	32	096	357.85

Transition Male Adapter w/Brass Thread

Brass Mipt x Socket




836-005CBR	1/2	40	160	096	66.63
836-007CBR	3/4	40	160	096	93.81
836-010CBR	1	10	60	096	163.39
836-012CBR	1-1/4	10	60	096	265.77
836-015CBR	1-1/2	10	40	096	345.52
836-020CBR	2	8	32	096	404.89

Part Number	Size	Std Pk	Mstr Ctn	Disc Code	Price Each
-------------	------	--------	----------	-----------	------------

Union

Soc x Fipt with Brass Thread Insert & Viton® O-ring Seal




235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

859-007CBR	3/4	10	20	096	138.86
859-010CBR	1	10	0	096	154.66
859-012CBR	1-1/4	5	0	096	259.26
859-015CBR	1-1/2	5	0	096	294.62
859-020CBR	2	5	0	096	332.98

Not intended to convey or dispense water for human consumption through drinking or cooking

Union

Soc x Fipt with Brass Thread Insert & EPDM O-ring Seal



235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

899-007CBR	3/4	10	40	096	136.51
899-010CBR	1	10	0	096	152.76
899-012CBR	1-1/4	5	20	096	255.99
899-015CBR	1-1/2	5	0	096	290.86
899-020CBR	2	5	0	096	328.90

Not intended to convey or dispense water for human consumption through drinking or cooking