



**Schedule 80 CPVC Industrial Products & Accessories
Pipe Flanges**

Part Number	Size	Std Pk	Mstr Ctn	Disc Code	Price Each
-------------	------	--------	----------	-----------	------------

Flange One Piece Soc



150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

851-005C	1/2	25	0	090	25.53
851-007C	3/4	25	0	090	26.12
851-010C	1	15	0	090	28.52
851-012C	1-1/4	15	0	090	34.81
851-015C	1-1/2	20	0	090	38.64
851-020C	2	10	0	090	46.77
851-025C	2-1/2	10	0	090	96.91
851-030C	3	10	0	090	101.34
851-040C	4	5	0	090	136.91
851-050C	5	5	0	090	250.91
851-060C	6	5	0	090	233.23
851-080C	8	2	0	090	532.81

Flange One Piece Fipt



150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

852-005C	1/2	25	0	090	35.69
852-007C	3/4	25	0	090	43.27
852-010C	1	15	0	090	47.22
852-012C	1-1/4	15	0	090	65.54
852-015C	1-1/2	20	0	090	69.38
852-020C	2	10	0	090	70.65
852-025C	2-1/2	10	0	090	114.68
852-030C	3	10	0	090	113.79
852-040C	4	5	0	090	176.90

Blind Flange



1/2" - 12" Molded - 150 psi Maximum Internal Pressure Rating @ 73°F (23°C)
14" - 24" Fabricated - 50 psi Maximum Internal Pressure Rating @ 73°F (23°C)

853-005C	1/2	25	100	090	38.27
853-007C	3/4	25	0	090	41.49
853-010C	1	20	0	090	51.72
853-012C	1-1/4	20	0	090	58.52
853-015C	1-1/2	15	0	090	81.90
853-020C	2	10	0	090	86.04
853-025C	2-1/2	10	0	090	130.16
853-030C	3	10	0	090	161.81
853-040C	4	8	0	090	219.18
853-060C	6	5	0	090	367.66
853-080C	8	5	0	090	681.96
853-100C	10	3	0	091	1229.64
853-120C	12	2	0	091	2065.79
853-140CF	14	1	0	097	2400.73
853-160CF	16	1	0	097	3722.30
853-180CF	18	1	0	097	4588.64
853-200CF	20	1	0	097	4916.88
853-240CF	24	1	0	097	5982.82

Flange Van Stone Style with Plastic Ring Soc



150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

854-005C	1/2	25	0	090	25.70
854-007C	3/4	25	0	090	26.28
854-010C	1	15	0	090	28.70
854-012C	1-1/4	15	0	090	35.04
854-015C	1-1/2	20	0	090	38.90

Part Number	Size	Std Pk	Mstr Ctn	Disc Code	Price Each
-------------	------	--------	----------	-----------	------------

Flange Van Stone Style with Plastic Ring (continued) Soc

854-020C	2	10	0	090	47.11
854-025C	2-1/2	10	0	090	97.59
854-030C	3	10	0	090	102.18
854-040C	4	5	0	090	137.99
854-050C	5	5	0	090	235.13
854-060C	6	5	0	090	235.13
854-080C	8	2	0	090	707.48
854-100C	10	2	0	091	1703.17
854-120C	12	2	0	091	2555.67
854-140C	14	1	0	091	2879.81
854-160C	16	1	0	091	3599.78
854-180C	18	1	0	091	5843.81

Flange Van Stone Style with Plastic Ring Spig



150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

856-005C	1/2	25	0	090	29.72
856-007C	3/4	25	0	090	31.90
856-010C	1	15	0	090	36.22
856-012C	1-1/4	15	0	090	44.82
856-015C	1-1/2	15	0	090	49.56
856-020C	2	10	0	090	69.37
856-025C	2-1/2	10	0	090	108.65
856-030C	3	10	0	090	118.98
856-040C	4	5	0	090	122.44
856-060C	6	4	0	090	267.33
856-080C	8	2	0	090	544.91
856-100C	10	2	0	091	1829.76
856-120C	12	2	0	091	2748.57
856-140CF	14	1	0	097	2924.49
856-160CF	16	1	0	097	3622.66

Flange Van Stone Style with Plastic Solid Ring Soc



150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

S854-030C	3	10	0	090	145.95
S854-040C	4	5	0	090	197.17
S854-060C	6	4	0	090	335.89
S854-080C	8	2	0	090	1010.67
S854-100C	10	2	0	091	2433.11
S854-120C	12	2	0	091	3650.95

Flange Van Stone Style Class 300 Bolt Pattern Fabricated with Plastic Ring Soc



Molded with fabricated ring - 150 psi = maximum internal pressure rating @ 73°F (23°C)

854-005CL300C	1/2	1	25	097	195.55
854-007CL300C	3/4	1	25	097	261.99
854-010CL300C	1	1	15	097	319.46
854-012CL300C	1-1/4	1	15	097	339.39
854-015CL300C	1-1/2	1	20	097	352.40
854-020CL300C	2	1	10	097	391.46
854-025CL300C	2-1/2	1	10	097	465.81
854-030CL300C	3	1	10	097	506.23
854-040CL300C	4	1	5	097	798.35
854-060CL300C	6	1	4	097	1507.56
854-080CL300C	8	1	3	097	1734.73
854-100CL300C	10	1	2	097	1961.37
854-120CL300C	12	1	0	097	2450.34
854-140CL300C	14	1	0	097	2721.45