



Schedule 40 Fittings & Accessories Pipe Flanges

Part Number	Size	Std Pk	Mstr Ctn	Disc Code	Price Each
-------------	------	--------	----------	-----------	------------

Flange Van Stone Style Flange x PIP Soc



125 psi Maximum Internal Pressure Rating @ 73°F (23°C)

354-060F	6X6.140	1	4	320	126.99
354-080F	8X8.160	1	2	320	192.30
354-100F	10X10.200	1	2	320	270.38
354-120F	12X12.240	1	2	320	391.60
354-150F	14X15.300	1	0	320	1043.82
354-151F	16X15.300	1	0	320	1190.79
354-181F	18X18.701	1	0	320	1809.00
354-182F	18X18.360	1	0	320	1809.00
354-201F	20X22.047	1	0	320	2755.48
354-241F	24X24.803	1	0	320	4035.33

For more information, refer to 80, 100 & 125 psi PIP Fabrication Fittings.

PIP = Plastic Irrigation Pipe (dimensions are NOT the same as IPS dimensions)

Sizes 6" - 16" are furnished with plastic ring.
Sizes 18" - 24" are furnished with steel ring.

Flange One Piece Soc



1/2" - 16" 150 psi Maximum Internal Pressure Rating @73°F (23°C)
18" - 24" 50 psi Maximum Internal Pressure Rating @73°F (23°C)

851-005	1/2	25	0	080	17.20
851-007	3/4	25	0	080	18.38
851-010	1	15	0	080	20.47
851-012	1-1/4	15	0	080	21.09
851-015	1-1/2	20	0	080	21.55
851-020	2	10	0	080	28.68
851-025	2-1/2	10	0	080	44.27
851-030	3	10	0	080	48.89
851-040	4	5	0	080	61.90
851-050	5	5	0	080	97.33
851-060	6	5	0	080	97.33
851-080	8	2	0	080	174.16
851-100F	10	1	2	083	473.27
851-120F	12	1	0	083	574.71
851-140F	14	1	0	083	1057.02
851-160F	16	1	0	083	1450.64
851-180F	18	1	0	083	3068.69
851-200F	20	1	0	083	3757.83
851-240F	24	1	0	083	4990.84

Flange One Piece Fipt



150 psi Maximum Internal Pressure Rating @73°F (23°C)

852-005	1/2	25	0	080	20.59
852-007	3/4	25	0	080	24.12
852-010	1	15	0	080	26.41
852-012	1-1/4	15	0	080	36.41
852-015	1-1/2	20	0	080	39.74
852-020	2	10	0	080	40.64
852-025	2-1/2	10	0	080	93.44
852-030	3	10	0	080	96.18
852-040	4	5	0	080	180.71
852-060F	6	1	5	083	217.09
852-080F	8	1	2	083	544.84

Part Number	Size	Std Pk	Mstr Ctn	Disc Code	Price Each
-------------	------	--------	----------	-----------	------------

Special Reinforced Flange One Piece Threaded SR Fipt - Stainless Steel Collar



150 psi Maximum Internal Pressure Rating @73°F (23°C)

852-005SR	1/2	25	0	086	11.31
852-007SR	3/4	25	0	086	13.29
852-010SR	1	15	0	086	14.53
852-012SR	1-1/4	15	0	086	20.02
852-015SR	1-1/2	15	0	086	21.91
852-020SR	2	10	0	086	22.44
852-025SR	2-1/2	10	0	086	51.39
852-030SR	3	10	0	086	52.91
852-040SR	4	5	0	086	99.46

Blind Flange



1/2" - 12" Molded - 150 psi Maximum Internal Pressure Rating @ 73°F (23°C)
14" - 24" Fabricated - 50 psi Maximum Internal Pressure Rating @ 73°F (23°C)

853-005	1/2	25	0	080	24.11
853-007	3/4	25	0	080	28.72
853-010	1	15	0	080	39.23
853-012	1-1/4	20	0	080	48.15
853-015	1-1/2	15	0	080	48.15
853-020	2	10	0	080	71.94
853-025	2-1/2	10	0	080	117.21
853-030	3	10	0	080	141.45
853-040	4	8	0	080	176.21
853-050F	5	1	5	083	441.70
853-060	6	5	0	080	214.13
853-080	8	5	0	080	268.02
853-100	10	3	0	081	448.18
853-120	12	2	0	081	698.01
853-140F	14	1	0	083	1327.90
853-160F	16	1	0	083	1574.63
853-180F	18	1	0	083	1770.89
853-200F	20	1	0	083	2862.36
853-240F	24	1	0	083	3816.12

Flange Van Stone Style with PVC Ring Soc



1/2" - 18" molded - 150 psi = maximum internal pressure rating @ 73°F (23°C)
18" - 24" fabricated - 50 psi = maximum internal pressure rating @ 73°F (23°C)

854-005	1/2	25	0	080	17.18
854-007	3/4	25	0	080	18.37
854-010	1	15	0	080	20.46
854-012	1-1/4	15	0	080	21.07
854-015	1-1/2	20	0	080	21.50
854-020	2	10	0	080	28.63
854-025	2-1/2	10	0	080	44.22
854P-030	3	10	0	080	48.87
854P-040	4	5	0	080	61.82
854P-050	5	5	0	080	97.24
854P-060	6	5	0	080	97.24
854P-080	8	2	0	080	158.35
854P-100	10	2	0	081	205.00
854P-120	12	2	0	081	221.03
854P-140	14	1	0	081	853.30
854P-160	16	1	0	081	1141.33
854P-180	18	1	0	081	1840.81
854-180FP	18	1	0	083	2912.47