



Schedule 80 PVC Industrial Products & Accessories Pipe Flanges

Part Number	Size	Std Pk	Mstr Ctn	Disc Code	Price Each
-------------	------	--------	----------	-----------	------------

Flange One Piece (continued)

Soc

851-180F	18	1	0	083	3068.69
851-200F	20	1	0	083	3757.83
851-240F	24	1	0	083	4990.84

Flange One Piece

Fipt

150 psi Maximum Internal Pressure Rating @73°F (23°C)

852-005	1/2	25	0	080	20.59
852-007	3/4	25	0	080	24.12
852-010	1	15	0	080	26.41
852-012	1-1/4	15	0	080	36.41
852-015	1-1/2	20	0	080	39.74
852-020	2	10	0	080	40.64
852-025	2-1/2	10	0	080	93.44
852-030	3	10	0	080	96.18
852-040	4	5	0	080	180.71
852-060F	6	1	5	083	217.09
852-080F	8	1	2	083	544.84

Special Reinforced Flange One Piece Threaded

SR Fipt - Stainless Steel Collar

150 psi Maximum Internal Pressure Rating @73°F (23°C)

852-005SR	1/2	25	0	086	11.31
852-007SR	3/4	25	0	086	13.29
852-010SR	1	15	0	086	14.53
852-012SR	1-1/4	15	0	086	20.02
852-015SR	1-1/2	15	0	086	21.91
852-020SR	2	10	0	086	22.44
852-025SR	2-1/2	10	0	086	51.39
852-030SR	3	10	0	086	52.91
852-040SR	4	5	0	086	99.46

Blind Flange

1/2" - 12" Molded - 150 psi Maximum Internal Pressure Rating @ 73°F (23°C)
14" - 24" Fabricated - 50 psi Maximum Internal Pressure Rating @ 73°F (23°C)

853-005	1/2	25	0	080	24.11
853-007	3/4	25	0	080	28.72
853-010	1	15	0	080	39.23
853-012	1-1/4	20	0	080	48.15
853-015	1-1/2	15	0	080	48.15
853-020	2	10	0	080	71.94
853-025	2-1/2	10	0	080	117.21
853-030	3	10	0	080	141.45
853-040	4	8	0	080	176.21
853-050F	5	1	5	083	441.70
853-060	6	5	0	080	214.13
853-080	8	5	0	080	268.02
853-100	10	3	0	081	448.18
853-120	12	2	0	081	698.01
853-140F	14	1	0	083	1327.90
853-160F	16	1	0	083	1574.63
853-180F	18	1	0	083	1770.89
853-200F	20	1	0	083	2862.36
853-240F	24	1	0	083	3816.12

Part Number	Size	Std Pk	Mstr Ctn	Disc Code	Price Each
-------------	------	--------	----------	-----------	------------

Flange Van Stone Style with PVC Ring

Soc

1/2" - 18" molded - 150 psi = maximum internal pressure rating @ 73°F (23°C)
18" - 24" fabricated - 50 psi = maximum internal pressure rating @ 73°F (23°C)

854-005	1/2	25	0	080	17.18
854-007	3/4	25	0	080	18.37
854-010	1	15	0	080	20.46
854-012	1-1/4	15	0	080	21.07
854-015	1-1/2	20	0	080	21.50
854-020	2	10	0	080	28.63
854-025	2-1/2	10	0	080	44.22
854P-030	3	10	0	080	48.87
854P-040	4	5	0	080	61.82
854P-050	5	5	0	080	97.24
854P-060	6	5	0	080	97.24
854P-080	8	2	0	080	158.35
854P-100	10	2	0	081	205.00
854P-120	12	2	0	081	221.03
854P-140	14	1	0	081	853.30
854P-160	16	1	0	081	1141.33
854P-180	18	1	0	081	1840.81
854-180FP	18	1	0	083	2912.47
854-200FP	20	1	0	083	3562.39
854-240FP	24	1	0	083	4846.02

Flange Van Stone Style with Glass Filled PVC Ring

Soc

3" - 18" molded - 150 psi = maximum internal pressure rating @ 73°F (23°C)

854-030	3	10	0	080	48.87
854-040	4	5	0	080	61.82
854-050	5	5	0	080	97.24
854-060	6	5	0	080	97.24
854-080	8	2	0	080	158.35
854-100	10	2	0	081	205.00
854-120	12	2	0	081	221.03
854-140	14	1	0	081	853.30
854-160	16	1	0	081	1141.33
854-180	18	1	0	081	1840.81

18" flange has 4-section ring

Flange Van Stone Style Class 300 Bolt Pattern Fabricated with PVC Ring

Soc

1/2" - 16" molded with fab ring - 150 psi = maximum internal pressure rating @ 73°F (23°C)

18" - 24" fabricated - 50 psi = maximum internal pressure rating @ 73°F (23°C)

854-005CL300	1/2	1	25	083	141.21
854-007CL300	3/4	1	25	083	164.07
854-010CL300	1	1	15	083	257.80
854-012CL300	1-1/4	1	15	083	263.24
854-015CL300	1-1/2	1	20	083	273.44
854-020CL300	2	10	0	083	287.90
854-025CL300	2-1/2	1	10	083	316.12
854-030CL300	3	1	10	083	347.18
854-040CL300	4	1	3	083	588.69
854-060CL300	6	1	4	083	1121.23
854-080CL300	8	1	3	083	1276.26
854-100CL300	10	1	2	083	1502.52
854-120CL300	12	1	0	083	1925.03
854-140CL300	14	1	0	083	2122.53