

Schedule 40 Fittings & Accessories Pipe Flanges



Part Number	Size	Std Pk	Mstr Ctn	Disc Code	Price Each
-------------	------	--------	----------	-----------	------------

Flange Van Stone Style with PVC Ring (continued)

Soc

854-200FP	20	1	0	083	3562.39
854-240FP	24	1	0	083	4846.02

Flange Van Stone Style with Glass Filled PVC Ring

Soc

3" - 18" molded - 150 psi = maximum internal pressure rating @ 73°F (23°C)

854-030	3	10	0	080	48.87
854-040	4	5	0	080	61.82
854-050	5	5	0	080	97.24
854-060	6	5	0	080	97.24
854-080	8	2	0	080	158.35
854-100	10	2	0	081	205.00
854-120	12	2	0	081	221.03
854-140	14	1	0	081	853.30
854-160	16	1	0	081	1141.33
854-180	18	1	0	081	1840.81

18" flange has 4-section ring

Flange Van Stone Style Class 300 Bolt Pattern Fabricated with PVC Ring

Soc

1/2" - 16" molded with fab ring - 150 psi = maximum internal pressure rating @ 73°F (23°C)

18" - 24" fabricated - 50 psi = maximum internal pressure rating @ 73°F (23°C)

854-005CL300	1/2	1	25	083	141.21
854-007CL300	3/4	1	25	083	164.07
854-010CL300	1	1	15	083	257.80
854-012CL300	1-1/4	1	15	083	263.24
854-015CL300	1-1/2	1	20	083	273.44
854-020CL300	2	10	0	083	287.90
854-025CL300	2-1/2	1	10	083	316.12
854-030CL300	3	1	10	083	347.18
854-040CL300	4	1	3	083	588.69
854-060CL300	6	1	4	083	1121.23
854-080CL300	8	1	3	083	1276.26
854-100CL300	10	1	2	083	1502.52
854-120CL300	12	1	0	083	1925.03
854-140CL300	14	1	0	083	2122.53
854-160CL300	16	1	0	083	2210.38
854-180CL300	18	1	0	083	3090.45
854-200CL300	20	1	0	083	4012.82
854-240CL300	24	1	0	083	5087.14

Flange Van Stone Style with PVC Ring

Spig

1/2" - 12" molded - 150 psi = maximum internal pressure rating @ 73°F (23°C)

20" - 24" fabricated - 50 psi = maximum internal pressure rating @ 73°F (23°C)

856-005	1/2	25	0	080	17.27
856-007	3/4	25	0	080	18.51
856-010	1	15	0	080	20.63
856-012	1-1/4	15	0	080	21.28
856-015	1-1/2	15	0	080	21.71
856-020	2	10	0	080	28.85
856-025	2-1/2	10	0	080	44.59
856P-030	3	10	0	080	49.26
856P-040	4	5	0	080	62.33
856P-060	6	4	0	080	98.04
856P-080	8	2	0	080	175.38

Part Number	Size	Std Pk	Mstr Ctn	Disc Code	Price Each
-------------	------	--------	----------	-----------	------------

Flange Van Stone Style with PVC Ring (continued)

Spig

856P-100	10	2	0	081	205.00
856P-120	12	2	0	081	221.03
856-200FP	20	1	0	083	3562.39
856-240FP	24	1	0	083	4846.02

Flange Van Stone Style with Glass Filled PVC Ring

Spig

3" - 12" molded, 14" - 18" molded/fabricated - 150 psi = maximum internal pressure rating @ 73°F (23°C)

856-030	3	10	0	080	49.26
856-040	4	5	0	080	62.33
856-060	6	4	0	080	98.04
856-080	8	2	0	080	175.38
856-100	10	2	0	081	205.00
856-120	12	2	0	081	221.03
856-140FP**	14	1	0	083	1830.60
856-160FP**	16	1	0	083	2221.02
856-180FP**	18	1	0	083	2912.47

** Fabricated from molded socket flanges with pipe spigot.

18" flange uses 4-piece ring

Flange Van Stone Style with Steel Ring

Soc

150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

854-180FS	18	1	0	083	1719.40
854-200FS	20	1	0	083	2083.53
854-240FS	24	1	0	083	2804.11

Flange Van Stone Style with Steel Ring

Spig

150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

856-140FS	14	1	0	083	926.46
856-160FS	16	1	0	083	1132.41
856-180FS	18	1	0	083	1283.14
856-200FS	20	1	0	083	1545.53
856-240FS	24	1	0	083	2098.65

Flange Van Stone Style PVC with Solid Ring

Soc

150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

S854-020	2	10	0	080	35.80
S854-030	3	10	0	080	61.10
S854-040	4	5	0	080	77.29

Flange Van Stone Style PVC with Glass Filled PVC Solid Ring

Soc

150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

S854-060	6	5	0	080	121.57
S854-080	8	2	0	080	197.93
S854-100	10	2	0	081	256.24
S854-120	12	2	0	081	276.26

Flange Van Stone Style with PVC Ring

ASTM Soc x Multi-bolt Pattern Ring

150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

M854-020	2	10	0	080	28.63
----------	---	----	---	-----	-------