

**Schedule 80 PVC Industrial Products & Accessories
Unions**



Part Number	Size	Std Pk	Mstr Ctn	Disc Code	Price Each
-------------	------	--------	----------	-----------	------------

Union 2000

Fipt with Viton® O-ring Seal



235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

858-002	1/4	25	150	080	23.44
858-003	3/8	25	150	080	23.44
8058-005	1/2	20	120	080	13.50
8058-007	3/4	20	80	080	18.91
8058-010	1	15	90	080	25.16
8058-012	1-1/4	10	0	080	48.00
8058-015	1-1/2	10	0	080	59.44
8058-020	2	5	0	080	91.45
8058-025	2-1/2	5	0	080	154.68
8058-030	3	5	0	080	231.97
8058-040	4	4	0	080	272.63
8058-060	6	1	0	080	605.82

Union 2000

Fipt with EPDM O-ring Seal



235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

898-002	1/4	25	150	080	23.16
898-003	3/8	25	150	080	23.16
8098-005	1/2	20	240	080	13.34
8098-007	3/4	20	80	080	18.66
8098-010	1	15	90	080	24.85
8098-012	1-1/4	10	0	080	47.40
8098-015	1-1/2	10	0	080	58.69
8098-020	2	5	0	080	90.31
8098-025	2-1/2	5	0	080	120.94
8098-030	3	5	0	080	229.10
8098-040	4	4	0	080	267.95
8098-060	6	1	0	080	595.26

Special Reinforced Union 2000

SR Fipt with Viton® O-ring Seal - Stainless Steel Collar



235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8058-005SR	1/2	20	120	086	8.13
8058-007SR	3/4	20	80	086	11.01
8058-010SR	1	15	90	086	14.73
8058-012SR	1-1/4	10	0	086	28.06
8058-015SR	1-1/2	10	0	086	34.53
8058-020SR	2	5	0	086	53.62
8058-025SR	2-1/2	5	0	086	112.12
8058-030SR	3	5	0	086	127.54
8058-040SR	4	4	0	086	150.14
8058-060SR	6	1	0	086	333.63

Special Reinforced Union 2000

SR Fipt with EPDM O-ring Seal - Stainless Steel Collar




235 psi Maximum Internal Pressure rating @ 73°F (23°C)

8098-005SR	1/2	20	120	086	8.01
8098-007SR	3/4	20	80	086	10.91
8098-010SR	1	15	90	086	14.44
8098-012SR	1-1/4	10	0	086	26.85
8098-015SR	1-1/2	10	0	086	33.77
8098-020SR	2	5	0	086	53.07
8098-025SR	2-1/2	5	0	086	107.11
8098-030SR	3	5	0	086	126.32
8098-040SR	4	4	0	086	145.02
8098-060SR	6	1	0	086	322.30

Part Number	Size	Std Pk	Mstr Ctn	Disc Code	Price Each
-------------	------	--------	----------	-----------	------------

Union (Old Style)

Soc with Viton® O-ring Seal




235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

857-005	1/2	10	60	080	11.65
857-007	3/4	10	60	080	14.80
857-010	1	10	40	080	16.88
857-012	1-1/4	5	20	080	33.54
857-015	1-1/2	5	0	080	37.99
857-020	2	5	0	080	51.50
857-025	2-1/2	5	0	080	82.48
857-030	3	5	0	080	95.89
857-040	4	4	0	080	133.56

Union (Old Style)

Soc with EPDM O-ring Seal




235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

897-005	1/2	10	60	080	11.48
897-007	3/4	10	60	080	14.61
897-010	1	10	40	080	16.72
897-012	1-1/4	5	20	080	33.15
897-015	1-1/2	5	0	080	37.51
897-020	2	5	0	080	50.89
897-025	2-1/2	5	0	080	80.90
897-030	3	5	0	080	94.70
897-040	4	4	0	080	130.99

Union (Old Style)

Soc x Fipt with Viton® O-ring Seal




235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

859-005	1/2	10	60	080	14.18
859-007	3/4	10	60	080	19.84
859-010	1	10	40	080	26.38
859-012	1-1/4	5	20	080	50.40
859-015	1-1/2	5	0	080	62.38
859-020	2	5	0	080	96.04
859-025	2-1/2	5	0	080	170.65
859-030	3	5	0	080	226.65
859-040	4	4	0	080	260.48

Union (Old Style)

Soc x Fipt with EPDM O-ring Seal




235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

899-005	1/2	10	60	080	14.00
899-007	3/4	10	60	080	19.59
899-010	1	10	40	080	26.05
899-012	1-1/4	5	20	080	49.80
899-015	1-1/2	5	0	080	61.64
899-020	2	5	0	080	94.84
899-025	2-1/2	5	0	080	134.09
899-030	3	5	0	080	223.81
899-040	4	4	0	080	256.98

Special Reinforced Union (Old Style)

Soc x SR Fipt with Viton® O-ring Seal - Stainless Steel Collar



235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

859-005SR	1/2	10	60	086	7.90
859-007SR	3/4	10	40	086	10.88
859-010SR	1	10	40	086	14.14
859-012SR	1-1/4	5	20	086	27.02
859-015SR	1-1/2	5	0	086	33.34