



## Schedule 80 CPVC Industrial Products & Accessories Unions

Part Number	Size	Std Pk	Mstr Ctn	Disc Code	Price Each
-------------	------	--------	----------	-----------	------------

### Union (Old Style) (continued)

#### Soc with Viton® O-ring Seal

857-010C	1	10	40	090	32.61
857-012C	1-1/4	5	20	090	65.99
857-015C	1-1/2	5	0	090	67.19
857-020C	2	5	0	090	111.38
857-025C	2-1/2	5	0	090	182.67
857-030C	3	5	0	090	231.17
857-040C	4	4	0	090	295.35

### Union (Old Style)

#### Soc with EPDM O-ring Seal

235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

897-005C	1/2	10	60	090	25.93
897-007C	3/4	10	60	090	26.85
897-010C	1	10	40	090	32.17
897-012C	1-1/4	5	20	090	65.14
897-015C	1-1/2	5	0	090	66.38
897-020C	2	5	0	090	110.01
897-025C	2-1/2	5	0	090	182.19
897-030C	3	5	0	090	228.32
897-040C	4	4	0	090	291.99

### Union (Old Style)

#### Soc x Fipt with Viton® O-ring Seal

235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

859-005C	1/2	10	60	090	29.61
859-007C	3/4	10	40	090	51.67
859-010C	1	10	40	090	71.32
859-012C	1-1/4	5	20	090	135.84
859-015C	1-1/2	5	0	090	135.84
859-020C	2	5	0	090	153.57
859-025C	2-1/2	5	0	090	249.32
859-030C	3	5	0	090	294.89
859-040C	4	4	0	090	341.00

### Union (Old Style)

#### Soc x Fipt with EPDM O-ring Seal

235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

899-005C	1/2	10	60	090	28.88
899-007C	3/4	10	60	090	51.06
899-010C	1	10	40	090	70.43
899-012C	1-1/4	5	20	090	134.16
899-015C	1-1/2	5	0	090	134.16
899-020C	2	5	0	090	151.67
899-025C	2-1/2	5	0	090	217.26
899-030C	3	5	0	090	291.27
899-040C	4	4	0	090	336.00

### Union

#### Soc x Fipt with Brass Thread Insert & Viton® O-ring Seal

235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

859-007CBR	3/4	10	20	096	138.86
859-010CBR	1	10	0	096	154.66
859-012CBR	1-1/4	5	0	096	259.26
859-015CBR	1-1/2	5	0	096	294.62
859-020CBR	2	5	0	096	332.98

Not intended to convey or dispense water for human consumption through drinking or cooking

Part Number	Size	Std Pk	Mstr Ctn	Disc Code	Price Each
-------------	------	--------	----------	-----------	------------

### Union

#### Soc x Fipt with Brass Thread Insert & EPDM O-ring Seal

235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

899-007CBR	3/4	10	40	096	136.51
899-010CBR	1	10	0	096	152.76
899-012CBR	1-1/4	5	20	096	255.99
899-015CBR	1-1/2	5	0	096	290.86
899-020CBR	2	5	0	096	328.90

Not intended to convey or dispense water for human consumption through drinking or cooking

### Union (Old Style)

#### Fipt with Viton® O-ring Seal

235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

858-005C	1/2	10	60	090	27.86
858-007C	3/4	10	60	090	49.24
858-010C	1	10	40	090	67.90
858-012C	1-1/4	5	20	090	129.37
858-015C	1-1/2	5	0	090	129.37
858-020C	2	5	0	090	146.23
858-025C	2-1/2	5	0	090	235.59
858-030C	3	5	0	090	447.02
858-040C	4	4	0	090	480.53

### Union (Old Style)

#### Fipt with EPDM O-ring Seal

235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

898-005C	1/2	10	60	090	27.51
898-007C	3/4	10	60	090	48.63
898-010C	1	10	40	090	67.06
898-012C	1-1/4	5	20	090	127.87
898-015C	1-1/2	5	0	090	127.87
898-020C	2	5	0	090	144.46
898-025C	2-1/2	5	0	090	203.51
898-030C	3	5	0	090	404.90
898-040C	4	4	0	090	471.38

### Special Reinforced Union (Old Style)

#### Soc x SR Fipt with Viton® O-ring Seal - Stainless Steel Collar

235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

859-002CSR	1/4	25	150	096	24.11
859-003CSR	3/8	25	100	096	24.11
859-005CSR	1/2	10	60	096	15.32
859-007CSR	3/4	10	40	096	27.03
859-010CSR	1	10	40	096	37.24
859-012CSR	1-1/4	5	20	096	71.00
859-015CSR	1-1/2	5	0	096	77.18
859-020CSR	2	5	0	096	80.35
859-030CSR	3	5	0	096	226.04
859-040CSR	4	4	0	096	263.72

### Special Reinforced Union (Old Style)

#### Soc x SR Fipt with EPDM O-ring Seal - Stainless Steel Collar

235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

899-002CSR	1/4	25	150	096	23.95
899-003CSR	3/8	25	100	096	23.95
899-005CSR	1/2	10	60	096	15.02
899-007CSR	3/4	10	40	096	26.67
899-010CSR	1	10	40	096	36.93
899-012CSR	1-1/4	5	20	096	69.96
899-015CSR	1-1/2	5	0	096	76.09