



Schedule 80 PVC Industrial Products & Accessories Unions

Part Number	Size	Std Pk	Mstr Ctn	Disc Code	Price Each
-------------	------	--------	----------	-----------	------------

Special Reinforced Union (Old Style) (continued) Soc x SR Fipt with Viton® O-ring Seal - Stainless Steel Collar

859-020SR	2	5	0	086	50.91
859-030SR	3	5	0	086	124.40
859-040SR	4	4	0	086	142.83

Special Reinforced Union (Old Style)

Soc x SR Fipt with EPDM O-ring Seal - Stainless Steel Collar



235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

899-002SR	1/4	25	150	086	14.35
899-003SR	3/8	25	100	086	14.35
899-005SR	1/2	10	60	086	7.60
899-007SR	3/4	10	40	086	10.83
899-010SR	1	10	40	086	13.97
899-012SR	1-1/4	5	20	086	24.30
899-015SR	1-1/2	5	0	086	31.49
899-020SR	2	5	0	086	50.68
899-030SR	3	5	0	086	120.69
899-040SR	4	4	0	086	137.74

Union

Soc x Fipt with Brass Thread Insert & Viton® O-ring Seal



235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

859-007BR	3/4	10	40	086	50.53
859-010BR	1	10	0	086	62.36
859-012BR	1-1/4	5	20	086	107.63
859-015BR	1-1/2	5	0	086	142.44
859-020BR	2	5	0	086	189.30

Not intended to convey or dispense water for human consumption through drinking or cooking

Union

Soc x Fipt with Brass Thread Insert & EPDM O-ring Seal



235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

899-007BR	3/4	10	40	086	45.56
899-010BR	1	10	0	086	61.45
899-012BR	1-1/4	5	20	086	103.33
899-015BR	1-1/2	5	0	086	136.76
899-020BR	2	5	0	086	182.30

Not intended to convey or dispense water for human consumption through drinking or cooking

Union (Old Style)

Fipt with Viton® O-ring Seal



235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

858-005	1/2	10	60	080	13.50
858-007	3/4	10	60	080	18.91
858-010	1	10	40	080	25.16
858-012	1-1/4	5	20	080	48.00
858-015	1-1/2	5	0	080	59.44
858-020	2	5	0	080	91.45
858-025	2-1/2	5	0	080	154.68
858-030	3	5	0	080	231.97
858-040	4	4	0	080	272.63

Union (Old Style)

Fipt with EPDM O-ring Seal



235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

898-005	1/2	10	60	080	13.34
898-007	3/4	10	60	080	18.66
898-010	1	10	40	080	24.85
898-012	1-1/4	5	20	080	47.40


Part Number	Size	Std Pk	Mstr Ctn	Disc Code	Price Each
-------------	------	--------	----------	-----------	------------

Union (Old Style) (continued) Fipt with EPDM O-ring Seal

898-015	1-1/2	5	0	080	58.69
898-020	2	5	0	080	90.31
898-025	2-1/2	5	0	080	120.94
898-030	3	5	0	080	229.10
898-040	4	4	0	080	267.95

PVC Transition Union

JIS (mm) Soc x ASTM (in.) Fipt with EPDM O-ring Seal




235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8298-016	16 DN X 1/2	20	160	197	12.60
8298-020	20 DN X 3/4	20	80	197	17.63
8298-025	25 DN X 1	15	90	197	23.46
8298-030	30 DN X 1-1/4	10	0	197	44.59
8298-040	40 DN X 1-1/2	10	0	197	55.46
8298-050	50 DN X 2	5	0	197	85.35
8298-075	75 DN X 3	5	0	197	201.43
8298-100	100 DN X 4	4	0	197	231.28

PVC Transition Union

BSP Thread (in.) x ASTM (in.) Soc with Viton® O-ring Seal




235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8359-005	1/2	20	160	197	12.78
8359-007	3/4	20	80	197	17.86
8359-010	1	15	90	197	23.76
8359-012	1-1/4	10	0	197	45.37
8359-015	1-1/2	10	0	197	56.16
8359-020	2	5	0	197	86.41
8359-030	3	5	0	197	203.98
8359-040	4	4	0	197	234.43

PVC Transition Union

DIN (mm) Soc x ASTM (in.) Soc with Viton® O-ring Seal




235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8657-020	20 d X 1/2	10	60	197	10.46
8657-025	25 d X 3/4	10	40	197	13.32
8657-032	32 d X 1	10	40	197	15.20
8657-040	40 d X 1-1/4	10	0	197	30.19
8657-050	50 d X 1-1/2	10	0	197	34.19
8657-063	63 d X 2	5	0	197	46.37
8657-090	90 d X 3	5	0	197	86.31
8657-110	110 d X 4	4	0	197	120.21

PVC Transition Union

DIN (mm) Soc x ASTM (in.) Fipt with Viton® O-ring Seal




235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8658-020	20 d X 1/2	10	60	197	12.78
8658-025	25 d X 3/4	20	80	197	17.86
8658-032	32 d X 1	15	90	197	23.76
8658-040	40 d X 1-1/4	10	0	197	45.37
8658-050	50 d X 1-1/2	10	0	197	56.16
8658-063	63 d X 2	5	0	197	86.41
8658-090	90 d X 3	5	0	197	203.98
8658-110	110 d X 4	4	0	197	234.43

PVC Transition Union

DIN (mm) Soc x ASTM (in.) Soc with EPDM O-ring Seal



235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8697-020	20 d X 1/2	20	240	197	10.33
8697-025	25 d X 3/4	10	60	197	13.16