



Actuated Valves Electric Actuator Accessories

Contact Spears® for any desired accessories or functions not specified in the Accessory Selection Tables

The following accessories are for use on Spears® electric actuated Ball Valves, Butterfly Valves and Diaphragm Valves. Accessories are individually ordered separately and factory assembled with the selected Premium Actuated Valve Package. See important ordering instructions, *Ordering Premium Valve Packages with Accessory Add-ons*.

Accessory	Description	Accessory Part Number	Price Each Disc Code: 298
Heater	Heater/Thermostat - On 41°F, Off 60.8°F	A-H1	195.33
	Heater/Thermostat - On 62.6°F, Off 80.6°F	A-H2	175.78
Auxiliary Limit Switches	2-SPDT Limit Switch Set (1/2" shaft cam) ¹	A-LS1	175.22
	2-SPDT Limit Switch Set (3/8" shaft cam) ¹	A-LS2	175.22
	2-SPDT Limit Switch Set for Electric Spring Return	A-LS3	157.20
Position Indicators	LED Indicator Lights	A-P2	223.84
Modulating Positioner Boards	115 VAC 4-20 mA	A-PB1	1790.66
	115 VAC 0-5 VDC	A-PB2	1790.66
	115 VAC 0-10 VDC	A-PB3	1790.66
	230 VAC 4-20 mA	A-PB4	1790.66
	230 VAC 0-5 VDC	A-PB5	1790.66
	230 VAC 0-10 VDC	A-PB6	1790.66
	24 VAC 4-20 mA	A-PB7	1790.66
	24 VAC 0-5 VDC	A-PB8	1790.66
	24 VAC 0-10 VDC	A-PB9	1790.66
	24 VDC 4-20 mA	A-PB10	1790.66
	24 VDC 0-5 VDC	A-PB11	1790.66
	24 VDC 0-10 VDC	A-PB12	1790.66
	115 VAC 4-20 mA For Electric Spring Return Actuator	A-PB13	1871.64
Transmitter	4-20mA	A-T1	1313.85
Torque Sensors	Adjustable Electronic Torque Sensor	A-TS1	948.86
Speed Controller	Variable Speed Controller	A-SC1	623.10
"2-Wire" Control (operates as solenoid valve)	Control Relay Switch Setup 115 VAC- Normally Closed ²	A-CR1	221.40
	Control Relay Switch Setup 115 VAC- Normally Open ²	A-CR2	221.40
	Control Relay Switch Setup 24 VAC- Normally Closed ²	A-CR3	221.40
	Control Relay Switch Setup 24 VAC- Normally Open ²	A-CR4	221.40
	Control Relay Switch Setup 230 VAC- Normally Closed ²	A-CR5	221.40
	Control Relay Switch Setup 230 VAC- Normally Open ²	A-CR6	221.40
	Control Relay Switch Setup 12 VDC- Normally Closed ²	A-CR7	221.40
	Control Relay Switch Setup 12 VDC- Normally Open ²	A-CR8	221.40
	Control Relay Switch Setup 24 VDC- Normally Closed ²	A-CR9	221.40
	Control Relay Switch Setup 24 VDC- Normally Open ²	A-CR10	221.40
Friction Brake	Mechanical Brake ³	A-FB1	367.85
Lockout Switch	Power disconnect switch activated when manual override is in use	A-LK1	255.32
ID Tag	Type 316 Stainless Steel ID Tag 1/2" x 3" (3-lines, 12-characters & spaces)	TAG3-015	30.03

Stem Extensions	Ball Valve Stem Extension ⁴	A-BVSE-xxx-000	Call for pricing
	True Union 2000 Ball Valve Stem Extension ⁴	A-BVSE2-xxx-000	
	Butterfly Valve Stem Extension ⁴	A-BFSE-xxx-000	
	Diaphragm Valve Stem Extension ⁴	A-DESE-xxx-000	

- NOTES: 1 - The A-LS2 is used on 1/2" - 2" basic Ball Valve packages; A-LS1 used on all other sizes.
 2 - "2-Wire" Control is not applicable to Diaphragm Valves.
 3 - Friction Brake is standard on Butterfly Valves and not applicable to Diaphragm Valves.
 4 - Stem Extension Part Numbers: Enter size code for "xxx" in part number. Replace "000" with desired length code in part number; length is from top of valve to bottom of actuator.