



**Solvent Cements & Thread Sealants**  
**CPVC Low VOC Cements**

Heavy bodied cements are specifically formulated for CPVC plastic pipe and fittings including a variety of One-Step (no primer required) CPVC specialty cements. These products are ideal for use in hot/cold water plumbing systems, water treatment and chemical plants, as well as industrial piping systems.

- Low VOC emissions comply with *SCAQMD Rule 1168/316A*
- 2-Year Shelf Life

**CPVC-24 GRAY/ORANGE:** Heavy bodied, medium setting CPVC cement for all classes and schedules with interference fit through 24" diameter. High-strength, chemical-resistant solvent cement for use with CPVC piping systems carrying acids, bases, salts, and sodium hypochlorite. Ideal for use in waste water plants. Recommended for use on PVC industrial piping systems for chemical applications; best choice for both PVC and CPVC fume & air duct systems. Listings: ASTM F493, NSF®-PW, DWW, SW, U.P. Code.



**The Most Chemically Resistant Cement Available for Both PVC & CPVC Applications**

**CPVC-24 Gray Heavy Body CPVC Cement**

Part Number	Size	Std Pk	Mstr Ctn	Disc Code	Price Each
CPVC24G-020	<b>Pint</b>	12	0	707	23.30
CPVC24G-030	<b>Quart</b>	12	0	707	41.15
CPVC24G-040	<b>Gallon</b>	6	0	707	142.10

**CPVC-24 Orange Heavy Body CPVC Cement**

Part Number	Size	Std Pk	Mstr Ctn	Disc Code	Price Each
CPVC24O-020	<b>Pint</b>	12	0	707	23.30
CPVC24O-030	<b>Quart</b>	12	0	707	41.15
CPVC24O-040	<b>Gallon</b>	6	0	707	142.10

**CTS-5 EverTUFF® YELLOW:** Medium bodied, fast setting cement for copper tube size pipe and fittings with interference fit through 2" diameter. ONE STEP CEMENT - formulated for use without primer if local code permits. Listings: ASTM F493/D2846, NSF®-PW, DWW, SW, U.P. Code, CSA B137.6, B181.2.



**Approved for All Copper Tube Size (CTS) Hot & Cold Water Distribution Systems, Including Spears® EverTUFF® and FlowGuard Gold®**

**CTS-5 EverTUFF® One-Step CTS CPVC Cement**

Part Number	Size	Std Pk	Mstr Ctn	Disc Code	Price Each
CTS5-005	<b>1/4 Pint</b>	24	0	701	8.05
CTS5-010	<b>1/2 Pint</b>	24	0	701	12.80
CTS5-020	<b>Pint</b>	12	0	701	20.75
CTS5-030	<b>Quart</b>	12	0	701	36.10
CTS5-040	<b>Gallon</b>	6	0	701	123.50

**FS-5 RED:** One-Step (no primer required) CPVC cement specifically formulated and approved for use with Spears® **FlameGuard®** and other approved CPVC Fire Sprinkler Products with interference fit through 3". See publication FG-3, FlameGuard® Installation Instructions for additional application details. Listings: ASTM F493, NSF®-PW, DWW, SW, U.P. Code, UL®, FM® Approved.



**FS-5 FlameGuard® One-Step CPVC Cement**

Part Number	Size	Std Pk	Mstr Ctn	Disc Code	Price Each
FS5-020	<b>Pint</b>	12	0	703	25.23
FS5-030	<b>Quart</b>	12	0	703	46.29

**LW-5 MUSTARD:** One-Step (no primer required) CPVC cement specifically formulated and approved for use with Spears® **LabWaste™** CPVC Corrosive Waste Drainage System Products with interference fit through 24". See Publication LW-4, Technical Information, for application details. Listings: ASTM F493, NSF®-CW, PW, DWW, SW, U.P. Code, ICC-ES PMG.



**The Only Chemically Resistant Cement Approved for Spears® LabWaste™**

**LW-5 LabWaste™ One-Step CPVC Cement**

Part Number	Size	Std Pk	Mstr Ctn	Disc Code	Price Each
LW5-020	<b>Pint</b>	12	0	704	40.64
LW5-030	<b>Quart</b>	12	0	704	54.18
LW5-040	<b>Gallon</b>	6	0	704	220.41
LW5-050	<b>5 Gallon</b>	1	0	704	1102.09