

Lab Specialty Products Gauge Guards



Connections use Spears® Patented Special Reinforced (SR)
Female Threads on Pressure Inlet (1/4" or 1/2")

Pressure Rating
235 psi @ 73°F
16 BAR @ 22°C
Maximum Service Temperature
PVC = 140°F (60°C)
CPVC = 200°F (93°C)
PP = 180°F (82°C)
Temperature/Pressure De-ratings Apply
Rated for Full Vacuum Service

Gauge Guards are pre-filled with glycerin-water
on units with Factory Installed Gauges.
"No Gauge" units are to be filled by end user.

PVC GAUGE GUARDS

Size	1/4" Inlet Connection	1/2" Inlet Connection	Std Pk	Mstr Pk	Disc Code
PTFE Diaphragm					
No Gauge	G0004-002 98.64	G0004-005 98.64	1	18	624
0-30 in-Hg	G30V4-002 166.52	G30V4-005 166.52	1	18	624
0-15 psi	G0154-002 157.41	G0154-005 157.41	1	18	624
0-30 psi	G0304-002 157.41	G0304-005 157.41	1	18	624
0-60 psi	G0604-002 157.41	G0604-005 157.41	1	18	624
0-100 psi	G1004-002 157.41	G1004-005 157.41	1	18	624
0-160 psi	G1604-002 157.41	G1604-005 157.41	1	18	624
0-200 psi	G2004-002 157.41	G2004-005 157.41	1	18	624
0-300 psi	G3004-002 157.41	G3004-005 157.41	1	18	624

Viton® Diaphragm

No Gauge	G0003-002 98.64	G0003-005 98.64	1	18	624
0-30 in-Hg	G30V3-002 166.52	G30V3-005 166.52	1	18	624
0-15 psi	G0153-002 157.41	G0153-005 157.41	1	18	624
0-30 psi	G0303-002 157.41	G0303-005 157.41	1	18	624
0-60 psi	G0603-002 157.41	G0603-005 157.41	1	18	624
0-100 psi	G1003-002 157.41	G1003-005 157.41	1	18	624
0-160 psi	G1603-002 157.41	G1603-005 157.41	1	18	624
0-200 psi	G2003-002 157.41	G2003-005 157.41	1	18	624
0-300 psi	G3003-002 157.41	G3003-005 157.41	1	18	624

EPDM Diaphragm

No Gauge	G0002-002 94.65	G0002-005 94.65	1	18	624
0-30 in-Hg	G30V2-002 159.83	G30V2-005 159.83	1	18	624
0-15 psi	G0152-002 151.16	G0152-005 151.16	1	18	624
0-30 psi	G0302-002 151.16	G0302-005 151.16	1	18	624

PVC GAUGE GUARDS (continued)

Size	1/4" Inlet Connection	1/2" Inlet Connection	Std Pk	Mstr Pk	Disc Code
EPDM Diaphragm					
0-60 psi	G0602-002 151.16	G0602-005 151.16	1	18	624
0-100 psi	G1002-002 151.16	G1002-005 151.16	1	18	624
0-160 psi	G1602-002 151.16	G1602-005 151.16	1	18	624
0-200 psi	G2002-002 151.16	G2002-005 151.16	1	18	624
0-300 psi	G3002-002 151.16	G3002-005 151.16	1	18	624

CPVC GAUGE GUARDS

Size	1/4" Inlet Connection	1/2" Inlet Connection	Std Pk	Mstr Pk	Disc Code
PTFE Diaphragm					
No Gauge	G0004-002C 128.23	G0004-005C 128.23	1	18	625
0-30 in-Hg	G30V4-002C 216.49	G30V4-005C 216.49	1	18	625
0-15 psi	G0154-002C 204.66	G0154-005C 204.66	1	18	625
0-30 psi	G0304-002C 204.66	G0304-005C 204.66	1	18	625
0-60 psi	G0604-002C 204.66	G0604-005C 204.66	1	18	625
0-100 psi	G1004-002C 204.66	G1004-005C 204.66	1	18	625
0-160 psi	G1604-002C 204.66	G1604-005C 204.66	1	18	625
0-200 psi	G2004-002C 204.66	G2004-005C 204.66	1	18	625
0-300 psi	G3004-002C 204.66	G3004-005C 204.66	1	18	625

Viton® Diaphragm

No Gauge	G0003-002C 128.23	G0003-005C 128.23	1	18	625
0-30 in-Hg	G30V3-002C 216.49	G30V3-005C 216.49	1	18	625
0-15 psi	G0153-002C 204.66	G0153-005C 204.66	1	18	625
0-30 psi	G0303-002C 204.66	G0303-005C 204.66	1	18	625
0-60 psi	G0603-002C 204.66	G0603-005C 204.66	1	18	625
0-100 psi	G1003-002C 204.66	G1003-005C 204.66	1	18	625

Schedule 80 PVC Industrial Products & Accessories Gauge Guards



Connections use Spears® Patented Special Reinforced (SR)
Female Threads on Pressure Inlet (1/4" or 1/2")

Pressure Rating
235 psi @ 73°F
16 BAR @ 22°C
Maximum Service Temperature
PVC = 140°F (60°C)
Temperature/Pressure De-ratings Apply
Rated for Full Vacuum Service

Gauge Guards are pre-filled with glycerin-water
on units with Factory Installed Gauges.
"No Gauge" units are to be filled by end user.

PVC GAUGE GUARDS

Size	1/4" Inlet Connection	1/2" Inlet Connection	Std Pk	Mstr Pk	Disc Code
No Gauge	G0004-002 98.64	G0004-005 98.64	1	18	624
0-30 in-Hg	G30V4-002 166.52	G30V4-005 166.52	1	18	624
0-15 psi	G0154-002 157.41	G0154-005 157.41	1	18	624
0-30 psi	G0304-002 157.41	G0304-005 157.41	1	18	624
0-60 psi	G0604-002 157.41	G0604-005 157.41	1	18	624
0-100 psi	G1004-002 157.41	G1004-005 157.41	1	18	624
0-160 psi	G1604-002 157.41	G1604-005 157.41	1	18	624
0-200 psi	G2004-002 157.41	G2004-005 157.41	1	18	624
0-300 psi	G3004-002 157.41	G3004-005 157.41	1	18	624

PTFE Diaphragm

No Gauge	G0003-002 98.64	G0003-005 98.64	1	18	624
0-30 in-Hg	G30V3-002 166.52	G30V3-005 166.52	1	18	624
0-15 psi	G0153-002 157.41	G0153-005 157.41	1	18	624
0-30 psi	G0303-002 157.41	G0303-005 157.41	1	18	624
0-60 psi	G0603-002 157.41	G0603-005 157.41	1	18	624
0-100 psi	G1003-002 157.41	G1003-005 157.41	1	18	624
0-160 psi	G1603-002 157.41	G1603-005 157.41	1	18	624
0-200 psi	G2003-002 157.41	G2003-005 157.41	1	18	624
0-300 psi	G3003-002 157.41	G3003-005 157.41	1	18	624

EPDM Diaphragm

No Gauge	G0002-002 94.65	G0002-005 94.65	1	18	624
0-30 in-Hg	G30V2-002 159.83	G30V2-005 159.83	1	18	624
0-15 psi	G0152-002 151.16	G0152-005 151.16	1	18	624
0-30 psi	G0302-002 151.16	G0302-005 151.16	1	18	624
0-60 psi	G0602-002 151.16	G0602-005 151.16	1	18	624
0-100 psi	G1002-002 151.16	G1002-005 151.16	1	18	624
0-160 psi	G1602-002 151.16	G1602-005 151.16	1	18	624
0-200 psi	G2002-002 151.16	G2002-005 151.16	1	18	624

PVC GAUGE GUARDS (continued)

Size	1/4" Inlet Connection	1/2" Inlet Connection	Std Pk	Mstr Pk	Disc Code
0-300 psi	G3002-002 151.16	G3002-005 151.16	1	18	624