



**Thermoplastic Valves  
PVC In-line Adjustable Spring Check Valves**




Fipt x Mipt



Mipt x Fipt



Fipt x Fipt



Pressure Rating @ 73°F (23°C), Water  
200 psi  
Maximum Service Temperature  
PVC = 140°F (60°C)  
Temperature/Pressure De-ratings Apply

2 - 14 lbs. Adjustable Spring Tension  
(5 to 32 feet of head)  
Factory Preset to Approx. 5 psi  
(12 feet of head)  
Each full turn of adjustment nut = 1 psi  
(2.3 feet of head)  
Stainless Steel Adjustment Hardware  
EPDM Seat

**Standard Unit - Female Inlet x Male Outlet**

Part Number	Size	Std Pk	Mstr Ctn	Disc Code	Price Each
-------------	------	-----------	-------------	--------------	---------------

**Fipt x Mipt (Inlet x Outlet)**

S1102-05	1/2	30	180	026	10.40
S1102-07	3/4	25	150	026	10.64
S1102-10	1	25	150	026	17.66
S1102-05-07	1/2X3/4	25	150	026	15.18

**Male Inlet x Female Outlet Option**

Part Number	Size	Std Pk	Mstr Ctn	Disc Code	Price Each
-------------	------	-----------	-------------	--------------	---------------

**Mipt x Fipt (Inlet x Outlet)**

S1101-05	1/2	30	180	026	10.40
----------	-----	----	-----	-----	-------

**Female Inlet x Female Outlet Option**

Part Number	Size	Std Pk	Mstr Ctn	Disc Code	Price Each
-------------	------	-----------	-------------	--------------	---------------

**Fipt x Fipt (Inlet x Outlet)**

S1100-07	3/4	25	150	026	10.99
----------	-----	----	-----	-----	-------