



Expansion Joints Repair Couplings

(S119) Socket x Socket



(S118) Spigot x Socket

- Multi-function Telescoping Design
- Socket x Socket Configuration for Pipe Repair or Use as a Short-Stroke Expansion Joint
- Spigot x Socket Configuration for Replacing Damaged Fittings
- Both Configurations can be Easily Modified for Opposite Use
- Available in PVC White and PVC Gray
- Double O-ring Seal in EPDM or genuine Viton®
- 1/2" - 2" Pressure Rated to 235 PSI @ 73°F (23°C)
- 2-1/2" - 4" Pressure Rated to 200 PSI @ 73°F (23°C)
- 6" Pressure Rated to 150 PSI @ 73°F (23°C)
- NSF® Certified for Potable Water Use

Part Number	Size	Std Pk	Mstr Ctn	Disc Code	Price Each
-------------	------	--------	----------	-----------	------------

Part Number	Size	Std Pk	Mstr Ctn	Disc Code	Price Each
-------------	------	--------	----------	-----------	------------

PVC - Spig x Soc

PVC White with EPDM O-ring



Can be used as short-stroke Expansion Joint

S118-05	1/2	25	0	025	5.28
S118-07	3/4	30	0	025	6.00
S118-10	1	15	0	025	6.93
S118-12	1-1/4	23	0	025	13.05
S118-15	1-1/2	25	0	025	14.21
S118-20	2	12	0	025	21.98
S118-25	2-1/2	5	0	025	31.89
S118-30	3	4	0	025	39.84
S118-40	4	2	0	025	69.73
S118-60	6	1	0	025	170.62

PVC - Soc x Soc (continued)

PVC White with EPDM O-ring

S119-25	2-1/2	5	0	025	31.89
S119-30	3	4	0	025	39.84
S119-40	4	2	0	025	69.73
S119-60	6	1	0	025	170.62

PVC - Soc x Soc

PVC Gray with Viton® O-ring



Can be used as short-stroke Expansion Joint

S119V-05G	1/2	28	0	025	6.71
S119V-07G	3/4	24	0	025	7.65
S119V-10G	1	20	0	025	8.84
S119V-12G	1-1/4	10	0	025	16.62
S119V-15G	1-1/2	16	0	025	18.12
S119V-20G	2	10	0	025	28.03
S119V-25G	2-1/2	5	0	025	42.15
S119V-30G	3	4	0	025	52.65
S119V-40G	4	2	0	025	92.17
S119V-60G	6	1	0	025	249.22

PVC - Spig x Soc

PVC Gray with EPDM O-ring



Can be used as short-stroke Expansion Joint

S118E-05G	1/2	25	0	025	6.14
S118E-07G	3/4	24	0	025	6.97
S118E-10G	1	15	0	025	8.07
S118E-12G	1-1/4	12	0	025	15.17
S118E-15G	1-1/2	25	0	025	16.52
S118E-20G	2	12	0	025	25.57
S118E-25G	2-1/2	5	0	025	37.51
S118E-30G	3	4	0	025	46.86
S118E-40G	4	2	0	025	82.04
S118E-60G	6	1	0	025	219.31

PVC - Soc x Soc

PVC Gray with EPDM O-ring



Can be used as short-stroke Expansion Joint

S119E-05G	1/2	28	0	025	6.14
S119E-07G	3/4	24	0	025	6.97
S119E-10G	1	20	0	025	8.07
S119E-12G	1-1/4	10	0	025	15.17
S119E-15G	1-1/2	16	0	025	16.52
S119E-20G	2	10	0	025	25.57
S119E-25G	2-1/2	5	0	025	37.51
S119E-30G	3	4	0	025	46.86
S119E-40G	4	2	0	025	82.04
S119E-60G	6	1	0	025	219.31

PVC - Spig x Soc

PVC Gray with Viton® O-ring



Can be used as short-stroke Expansion Joint

S118V-05G	1/2	25	0	025	6.71
S118V-07G	3/4	24	0	025	7.65
S118V-10G	1	15	0	025	8.84
S118V-12G	1-1/4	12	0	025	16.62
S118V-15G	1-1/2	25	0	025	18.12
S118V-20G	2	12	0	025	28.03
S118V-25G	2-1/2	5	0	025	42.15
S118V-30G	3	4	0	025	52.65
S118V-40G	4	2	0	025	92.17
S118V-60G	6	1	0	025	249.22

PVC - Soc x Soc

PVC White with EPDM O-ring



Can be used as short-stroke Expansion Joint

S119-05	1/2	30	0	025	5.28
S119-07	3/4	24	0	025	6.00
S119-10	1	20	0	025	6.93
S119-12	1-1/4	10	0	025	13.05
S119-15	1-1/2	16	0	025	14.21
S119-20	2	10	0	025	21.98