

Thermoplastic Valves True Union Utility Swing Check Valves & Compression Utility Swing Check Valves



True Union Utility Swing Check Valves

PVC White True Union Swing Check (continued)

Size	Socket	Threaded	SR Thread	Std Pk	Mstr Pk	Disc Code
1	S1720-10 19.35	S1720-10F 19.35	S1720-10FSR 24.60	18	0	026
1-1/4	S1720-12 20.37	S1720-12F 20.37	S1720-12FSR 28.76	12	0	026
1-1/2	S1720-15 22.39	S1720-15F 22.39	S1720-15FSR 36.77	10	0	026
2	S1720-20 33.64	S1720-20F 33.64	S1720-20FSR 49.15	10	0	026
2-1/2	S1720-25 56.09	S1720-25F 56.09	S1720-25FSR 80.22	2	0	026
3	S1720-30 71.61	S1720-30F 71.61	S1720-30FSR 113.27	2	0	026
4	S1720-40 96.66	S1720-40F 96.66	S1720-40FSR 139.38	1	0	026

PVC Clear True Union Swing Check (continued)

Size	Socket	Threaded	SR Thread	Std Pk	Mstr Pk	Disc Code
3/4	S1720C07 23.73	S1720C07F 23.73	S1720C07FSR 27.51	30	0	026
1	S1720C10 25.93	S1720C10F 25.93	S1720C10FSR 31.16	18	0	026
1-1/4	S1720C12 27.31	S1720C12F 27.31	S1720C12FSR 35.69	12	0	026
1-1/2	S1720C15 29.29	S1720C15F 29.29	S1720C15FSR 43.66	10	0	026
2	S1720C20 41.20	S1720C20F 41.20	S1720C20FSR 56.79	10	0	026
2-1/2	S1720C25 67.66	S1720C25F 67.66	S1720C25FSR 91.81	2	0	026
3	S1720C30 77.87	S1720C30F 77.87	S1720C30FSR 119.51	2	0	026
4	S1720C40 103.83	S1720C40F 103.83	S1720C40FSR 146.91	1	0	026

PVC Clear True Union Swing Check

Size	Socket	Threaded	SR Thread	Std Pk	Mstr Pk	Disc Code
1/2	S1720C05 23.34	S1720C05F 23.34	S1720C05FSR 25.96	35	0	026

Compression Utility Swing Check Valves



Pressure Rating @ 73°F (23°C), Water
 Full Flow (open) 150 psi
 Back Pressure (closed) 75 psi
 Maximum Service Temperature
 140°F (60°C)
 Temperature/Pressure De-ratings Apply

- Standard Swing Check Assembly Maintains a Positive Seal
- Convenient Compression Ends for Quick Connections
- Engineered for Maximum Flow, Quick Response & Positive Shut-off
- Excellent for Pool & Spa, OEM and General Purpose Applications
- Compact, Space-Saving Design
- Replaceable PVC White or Clear Sealed Unit
- High Grade EPDM Seat
- Suitable for Horizontal or Vertical Up-flow Installations
- Pressure Rated to 150 psi @ 73°F Full Flow (open), 75 psi Back Pressure (closed)
- Maximum Service Temperature 140°F (temperature/pressure de-ratings apply)

General Installation Information: Swing check valves are designed for horizontal installations, but may be installed in up-flow only vertical position. Check valves MUST be installed with the valve's FLOW arrow pointing in the direction of the flow. Do not install valve upside down. Flow velocity should not exceed 5 ft./sec. Minimum opening pressure less than 0.5 psi.

PVC White Compression End Swing Check

Part Number	Size	Std Pk	Mstr Ctn	Disc Code	Price Each
Compression End					
S1500-05	1/2	20	0	026	21.06
S1500-07	3/4	35	0	026	22.16
S1500-10	1	20	0	026	23.09
S1500-12	1-1/4	12	0	026	27.12
S1500-15	1-1/2	12	0	026	30.26
S1500-20	2	10	0	026	47.73
S1500-25	2-1/2	5	0	026	79.71
S1500-30	3	4	0	026	103.48
S1500-40	4	2	0	026	158.97

PVC Clear Compression End Swing Check

Part Number	Size	Std Pk	Mstr Ctn	Disc Code	Price Each
Compression End					
S1500C05	1/2	35	0	026	23.16
S1500C07	3/4	20	0	026	24.93
S1500C10	1	20	0	026	25.44
S1500C12	1-1/4	12	0	026	28.56
S1500C15	1-1/2	12	0	026	32.19
S1500C20	2	10	0	026	48.05
S1500C25	2-1/2	5	0	026	80.60
S1500C30	3	4	0	026	117.72
S1500C40	4	2	0	026	162.20

Compression Coupling Nut Wrenches

Part Number	Size	Std Pk	Mstr Ctn	Disc Code	Price Each
CCW-005	1/2	1	50	299	11.33
CCW-007	3/4	1	50	299	11.53
CCW-010	1	1	50	299	12.02
CCW-012	1-1/4	1	50	299	13.60
CCW-015	1-1/2	1	50	299	14.67
CCW-020*	2	1	50	299	16.39
CCW-030**	3	1	25	299	20.16

* CCW-20 - Wrench also fits 2-1/2" Coupling Body

**CCW-30 - Wrench also fits 4" Coupling Body

Compression Coupling Nut Wrench Sets

Part Number	Size	Std Pk	Mstr Ctn	Disc Code	Price Each
CCW-000	Set	1	50	299	94.70

Complete Set of Wrenches, Sizes 1/2" - 3"