



**Schedule 40 Fittings & Accessories**  
**True Union Utility Spring Check Valves & PVC In-line Adjustable Spring Check Valves**

**True Union Utility Spring Check Valves**

**PVC White True Union Spring Check (Spring Assisted Swing Check)**

Size	Socket	Thread	SR Thread	Std Pk	Mstr Pk	Disc Code
1/2	S1780-05 41.49	S1780-05F 41.49	S1780-05FSR 44.12	20	0	026
3/4	S1780-07 47.06	S1780-07F 47.06	S1780-07FSR 50.84	30	0	026
1	S1780-10 49.05	S1780-10F 49.05	S1780-10FSR 54.26	18	0	026
1-1/4	S1780-12 51.09	S1780-12F 51.09	S1780-12FSR 59.44	12	0	026
1-1/2	S1780-15 54.43	S1780-15F 54.43	S1780-15FSR 68.82	10	0	026
2	S1780-20 56.67	S1780-20F 56.67	S1780-20FSR 72.23	10	0	026
2-1/2	S1780-25 101.14	S1780-25F 101.14	S1780-25FSR 125.24	2	0	026
3	S1780-30 105.51	S1780-30F 105.51	S1780-30FSR 147.15	2	0	026
4	S1780-40 149.71	S1780-40F 149.71	S1780-40FSR 192.89	1	0	026

**PVC Clear True Union Spring Check (Spring Assisted Swing Check)**

Size	Socket	Thread	SR Thread	Std Pk	Mstr Pk	Disc Code
1/2	S1780C05 42.80	S1780C05F 42.80	S1780C05FSR 45.43	20	0	026
3/4	S1780C07 48.54	S1780C07F 48.54	S1780C07FSR 52.32	30	0	026
1	S1780C10 50.56	S1780C10F 50.56	S1780C10FSR 55.82	18	0	026
1-1/4	S1780C12 52.64	S1780C12F 52.64	S1780C12FSR 61.00	12	0	026
1-1/2	S1780C15 55.82	S1780C15F 55.82	S1780C15FSR 70.50	10	0	026
2	S1780C20 57.45	S1780C20F 57.45	S1780C20FSR 73.94	10	0	026
2-1/2	S1780C25 104.27	S1780C25F 104.27	S1780C25FSR 128.43	2	0	026
3	S1780C30 108.76	S1780C30F 108.76	S1780C30FSR 150.39	2	0	026
4	S1780C40 154.36	S1780C40F 154.36	S1780C40FSR 197.53	1	0	026

**PVC In-line Adjustable Spring Check Valves**




Mipt x Mipt



Mipt x Fipt



Fipt x Fipt



Pressure Rating @ 73°F (23°C), Water  
200 psi  
Maximum Service Temperature  
PVC = 140°F (60°C)  
Temperature/Pressure De-ratings Apply

2 - 14 lbs. Adjustable Spring Tension  
(5 to 32 feet of head)  
Factory Preset to Approx. 5 psi  
(12 feet of head)  
Each full turn of adjustment nut = 1 psi  
(2.3 feet of head)  
Stainless Steel Adjustment Hardware  
EPDM Seat

**Standard Unit - Female Inlet x Male Outlet**

Part Number	Size	Std Pk	Mstr Ctn	Disc Code	Price Each
<b>Fipt x Mipt (Inlet x Outlet)</b>					
S1102-05	1/2	30	180	026	10.40
S1102-07	3/4	25	150	026	10.64
S1102-10	1	25	150	026	17.66
S1102-05-07	1/2X3/4	25	150	026	15.18

**Male Inlet x Female Outlet Option**

Part Number	Size	Std Pk	Mstr Ctn	Disc Code	Price Each
<b>Mipt x Fipt (Inlet x Outlet)</b>					
S1101-05	1/2	30	180	026	10.40

**Female Inlet x Female Outlet Option**

Part Number	Size	Std Pk	Mstr Ctn	Disc Code	Price Each
<b>Fipt x Fipt (Inlet x Outlet)</b>					
S1100-07	3/4	25	150	026	10.99